



PRODUCT-DETAILS

E2.2V-A 250 Ekip Hi-Touch LSIG 3p WMP

E2.2V-A 250 Ekip Hi-Touch LSIG 3p WMP



General Information

Extended Product Type	E2.2V-A 250 Ekip Hi-Touch LSIG 3p WMP
Product ID	1SDA077686R1
EAN	8015644841096
Catalog Description	E2.2V-A 250 Ekip Hi-Touch LSIG 3p WMP
Long Description	MOVING PART FOR C.BREAKER SACE EMAX2 E2.2V-A 250 UL THREE-POLE WITH SOLID-STATE RELEASE IN AC EKIP/HI-TOUCH-LSIG R 250 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

ABB EcoSolutions

ABB EcoSolutions	Yes
------------------	-----

Circular Value

Circular Design Principles	Design for Closing Resource Loops - Standard EN45555 - 79.1 %
Recyclability Rate	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658

End of Life Instructions	9AKK108468A2361
Group Waste to Landfill Target	UL 2799 Zero Waste To Landfill Validation available
Toxic Substances Control Act - TSCA	9AKK108467A8326

Eco Transparency

Environmental Product Declaration - EPD	9AKK108468A1906
---	-----------------

Environmental

Environmental Information	9AKK108467A6707
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
SCIP	9fb5a037-697d-4732-9427-f1ab19aa91f0 Italy (IT)
Simplified SCIP	d6880e8a-0b47-4d2a-a19f-207c8f977e46 Bulgaria (BG) 14cd8efc-f2b2-4207-80f5-4a77fe9fb7fa Estonia (EE) 67d397da-6999-4193-a71a-23162597d5a3 Norway (NO) 5dfb3f96-3249-48a4-a566-5ec0df59b88e Denmark (DK) 0f9d41f1-579c-4521-88b9-48f147391db0 Portugal (PT) 31172d92-e751-4206-9dcb-c63deeed8974 Czech Republic (CZ) 89180b9b-e41a-4d5c-adb9-85d505fa2da9 Belgium (BE) 6fbdb6e0-92b2-47d7-adbe-1e25f88e7482 Netherlands (NL) f952208c-5a7b-4a8b-ae60-d211eabf46e6 Croatia (HR) 5e466283-10e9-46f8-990a-a21f2d7e7807 Belgium (BE) 08091065-d81e-4b93-85b9-a8e0a01f8ee0 Germany (DE) 601b69ed-9254-4145-9c61-b9a123ba4448 France (FR) 563d56dd-5a71-42d5-8467-6fd276770834 Spain (ES) 063bce05-16b4-411c-817b-f406e9034651 Hungary (HU) bbeb06b8-4177-419b-992c-f520008ecd5d Germany (DE) 31477605-adc7-4578-b2d7-8e26777ce35d France (FR) 983ac9d6-354b-47f0-8c74-555a7384e73c Sweden (SE) cc4dea73-b27f-4691-93f5-27630c5fc176 Poland (PL) 71ebf6c4-d034-4569-b31d-65cbacf29497 Sweden (SE) 9e0a0641-0ea9-4c1a-9b15-b87cbd450ed5 Greece (GR) 25515a12-0762-46b0-9e46-e251988ed175 Germany (DE) 00886c54-fd13-4c3e-8e67-b980254706f5 Poland (PL) fa215040-b257-4d20-9e53-c3c6d0b55f36 Hungary (HU) 023237c9-bfd1-4fab-876c-59d911e1ff1b Germany (DE) 5db722a1-6fe2-4b6c-8923-b054a1d0fd60 Finland (FI) d4430def-1c1e-495f-8a91-8d0e8779267b Germany (DE) 024701b7-325c-4e29-a978-a84eadc8af33 Poland (PL)

Ordering

Order Code US and Canada	Z2VAUCAK200A000000XX
EAN	8015644841096
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	317 mm
Product Net Height	425 mm
Product Net Depth / Length	393 mm
Product Net Weight	49 kg

Container Information	
Package Level 1 Units	box 1 piece
Package Level 1 Width	515 mm
Package Level 1 Height	610 mm
Package Level 1 Depth / Length	515 mm
Package Level 1 Gross Weight	59 kg
Package Level 1 EAN	8015644841096

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 15000 cycle Ue = 508 ... 635 V 15000 cycle 30 cycles per hour
Mechanical Durability	25000 cycle 60 cycles per hour
Number of Poles	3
Product Main Type	SACE Emax 2
Product Name	Air Circuit Breaker
Product Type	Air Circuit Breaker
Rated Current (I _n)	250 A
Rated Voltage (U _r)	600 V
Rated Insulation Voltage (U _i)	AC 635 V
Rated Operational Voltage	600 V AC
Release	Ekip Hi-Touch LSIG
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL
Sub-type	E2.2
Version	W

Technical UL/CSA	
Interrupting Rating acc. to UL1066	(254 V) 100 kA (508 V) 100 kA (635 V) 85 kA

Certificates and Declarations	
Data Sheet, Technical Information	1SXU200040C0201
Declaration of Conformity - CE	9AKK106713A5902
Instructions and Manuals	1SDH001000R0002
Instructions and Manuals (Part 2)	1SDH001316R1002

Classifications	
ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
IDEA Granular Category Code (IGCC)	4926 >> Air circuit breakers

UNSPSC	39121615
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax 2

