



PRODUCT-DETAILS

E2.2V-A 1600 Ekip Hi-Touch LSIG 3p WMP

E2.2V-A 1600 Ekip Hi-Touch LSIG 3p WMP



General Information	
Extended Product Type	E2.2V-A 1600 Ekip Hi-Touch LSIG 3p WMP
Product ID	1SDA077726R1
EAN	8015644841492
Catalog Description	E2.2V-A 1600 Ekip Hi-Touch LSIG 3p WMP
Long Description	MOVING PART FOR C.BREAKER SACE EMAX2 E2.2V-A 1600 UL THREE-POLE WITH SOLID -STATE RELEASE IN AC EKIP/HI-TOUCH-LSIG R 1600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

ABB EcoSolutions	
ABB EcoSolutions	Yes

Circular Value	
Circular Design	Design for Closing Resource Loops - Standard EN45555 - 79.1 %
Principles Recyclability Rate	
Conflict Minerals	9AKK108467A5658

Reporting Template (CMRT)	
End of Life Instructions	9AKK108468A2361
Group Waste to Landfill Target	UL 2799 Zero Waste To Landfill Validation available
Toxic Substances Control Act - TSCA	9AKK108467A8326

Eco Transparency

Environmental Product Declaration - EPD	9AKK108468A1906
---	-----------------

Environmental

Environmental Information	9AKK108467A6707
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
SCIP	ab818a0e-694c-4af9-9d79-7982e909bb7f Italy (IT)
Simplified SCIP	03f5f971-cc37-4669-9708-5dd732ce1711 Germany (DE) eb7e1b25-0faa-4100-960d-22b182f5d56d Hungary (HU) b8a0d231-041b-40c2-8cb8-0f16d5f222c4 Estonia (EE) f2abc70d-9aea-4b71-901d-66848a26c882 Greece (GR) 0d9643fc-a36c-4390-95ec-14d792648c90 Portugal (PT) 1a62248a-d9ce-447e-a294-233fcc35c3fc Denmark (DK) 54a8fada-7c3e-4227-9e47-c246ab9079c5 Bulgaria (BG) ffdac652-3550-441b-817c-27a21db2d22f Poland (PL) fe73b79a-a8d3-4d0c-bf73-0b6c95bdb656 Sweden (SE) 6b623cb0-855d-4019-ad82-c58c4ca0331c Poland (PL) 099bb524-6722-4ee1-86eb-c6a0b82d8645 Germany (DE) 650ad202-220c-40d2-b1a8-8d5a17f92939 France (FR) de72dc46-6d0e-403c-adad-0be1b15c72f3 Norway (NO) c9e5160c-61bc-433a-bb10-204bd483aeb0 Croatia (HR) 4f7555f9-629d-4497-94e1-27af241bcedc Finland (FI) 57a365ab-8262-448a-b2dd-bb3dd88e7d2c Sweden (SE) 2bf1786b-945e-4965-8deb-74f52723e6bb Czech Republic (CZ) f767f788-b1ad-4edc-9707-0d10110062f7 Belgium (BE) 0f460004-8749-4c55-9a62-42a5439738bb Germany (DE) 17f089b0-515a-46b7-b240-e3e8bbac5129 Germany (DE) 886ad606-a06b-473c-8ee5-4a376c45943b Spain (ES) d028c10d-2263-49b9-9b07-a58c422feb01 France (FR) 3677adfc-902f-47f4-b092-eb9e0fff86c7 Germany (DE) 3a160b1d-6baa-4f75-820a-914a03a8e55d Poland (PL) 8f54adc6-a254-473f-a624-5d522dd79dd8 Netherlands (NL) a5f0b6d6-a724-4dd9-9495-d6a9c8980b17 Hungary (HU) 7b4d646e-93fa-444b-a1a8-d5c62b00ca8f Belgium (BE)

Ordering

Order Code US and Canada	Z2VEUJAK200A000000XX
EAN	8015644841492
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	317 mm
-------------------	--------

Product Net Height	425 mm
Product Net Depth / Length	393 mm
Product Net Weight	49 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	515 mm
Package Level 1 Height	610 mm
Package Level 1 Depth / Length	515 mm
Package Level 1 Gross Weight	59 kg
Package Level 1 EAN	8015644841492

Additional Information

Current Type	AC
Electrical Durability	Ue = < 508 V 12000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	25000 cycle 60 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 233 W
Product Main Type	SACE Emax 2
Product Name	Air Circuit Breaker
Product Type	Air Circuit Breaker
Rated Current (I _n)	1600 A
Rated Voltage (U _r)	600 V
Rated Insulation Voltage (U _i)	AC 635 V
Rated Operational Voltage	600 V AC
Release	Ekip Hi-Touch LSIG
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL
Sub-type	E2.2
Version	W

Technical UL/CSA

Interrupting Rating acc. to UL1066	(254 V) 100 kA (508 V) 100 kA (635 V) 85 kA
------------------------------------	---

Certificates and Declarations

Data Sheet, Technical Information	1SXU200040C0201
Declaration of Conformity - CE	9AKK106713A5902

Instructions and Manuals	1SDH001000R0002
Instructions and Manuals (Part 2)	1SDH001316R1002

Classifications

ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
IDEA Granular Category Code (IGCC)	4926 >> Air circuit breakers
UNSPSC	39121615
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax 2

