



PRODUCT-DETAILS

E4.2S-A 2500 Ekip Touch LSIG 4p F HR

E4.2S-A 2500 Ekip Touch LSIG 4p F HR



General Information	
Extended Product Type	E4.2S-A 2500 Ekip Touch LSIG 4p F HR
Product ID	1SDA078233R1
EAN	8015644846565
Catalog Description	E4.2S-A 2500 Ekip Touch LSIG 4p F HR
Long Description	C.BREAKER SACE EMAX2 E4.2S-A 2500 UL FIXED FOUR-POLE WITH TERMINALS REAR HORIZONTAL AND SOLID-STATE RELEASE IN AC EKIP/TOUCH-LSIG R 2500 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

ABB EcoSolutions	
ABB EcoSolutions	Yes

Circular Value	
Circular Design	Design for Closing Resource Loops - Standard EN45555 - 79.3 %
Principles Recyclability Rate	
Conflict Minerals	9AKK108467A5658

Reporting Template (CMRT)	
End of Life Instructions	9AKK108468A2363
Group Waste to Landfill Target	UL 2799 Zero Waste To Landfill Validation available
Toxic Substances Control Act - TSCA	9AKK108467A8326

Eco Transparency

Environmental Product Declaration - EPD	9AKK108468A1907
---	-----------------

Environmental

Environmental Information	9AKK108467A6707
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
SCIP	530efcb1-ef94-40a8-babb-c48572cfbb18 Italy (IT)
Simplified SCIP	03e9c8a3-9a59-4ba6-88b5-cae138e0f4fc Germany (DE) b0c2e091-b0d2-4e82-896a-e25e54ffda9d Estonia (EE) f74ee150-f962-4e9c-92d6-98a63ece49b8 Greece (GR) 0651927a-eaff-44e4-9843-c747b1fd8381 Bulgaria (BG) 2302db18-e177-4c19-b00f-951e6e14fec7 Portugal (PT) b808b5b0-3d67-4209-bf70-ce921f237b02 Denmark (DK) fcd4d8a9-e4d3-4d13-8b4f-c47a6f3cf47a Finland (FI) f99a7b08-eba6-4b54-9094-9fa8442d1d79 Croatia (HR) 7c43c266-68f3-4fc4-99e7-10320f9688d0 Norway (NO) ff626bb2-02ee-4e66-9c8f-c64e76a706e7 Poland (PL) 75405118-532d-4545-90d1-7f4ffb7172c8 France (FR) 90f75fa3-c0f3-4de0-b559-31206c70bf30 Germany (DE) ceaf8fcf-c82f-4cce-9849-132b73fbbc7e Poland (PL) ad9113c3-7817-42ed-ae32-fb6d8a83c0ab Sweden (SE) bba735d3-2162-497b-a0d4-87578251d4b6 Hungary (HU) 9835c713-0ebe-4be9-bb41-d9390492c472 Belgium (BE) 362636c4-0649-4cca-9b96-b6b9c7d763e6 Germany (DE) 78e13212-6a80-4cca-b8da-176ee6023180 Poland (PL) d6acec8d-91aa-4b7f-aa82-162c44124e77 Netherlands (NL) 23c953e6-fbb7-47e1-9278-b659c8370516 France (FR) 190bb87b-4dcc-44e0-9544-953a7fbedc4 Hungary (HU) f8972652-4543-4713-8ab4-98e4c2641ac3 Germany (DE) 9fc1fb3c-650f-49aa-8be9-db41dd257c06 Germany (DE) 1f831a93-4d18-4755-b449-95f834b6b81a Czech Republic (CZ) 562e33d1-1b0c-4804-8492-7f26c82834ba Sweden (SE) 3b69045d-c78a-4a30-ad75-8dfd687a6e66 Belgium (BE) 190a4869-bb82-47a0-83ff-b8dba64bedec Spain (ES)

Ordering

Order Code US and Canada	ZCSGULBF000A000000XX
EAN	8015644846565
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	510 mm
-------------------	--------

Product Net Height	371 mm
Product Net Depth / Length	270 mm
Product Net Weight	81 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	515 mm
Package Level 1 Height	610 mm
Package Level 1 Depth / Length	785 mm
Package Level 1 Gross Weight	81 kg
Package Level 1 EAN	8015644846565

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 20 cycles per hour
Mechanical Durability	20000 cycle 60 cycles per hour
Neutral Pole Current ([% Iu])	100 %
Number of Poles	4
Power Loss	at Rated Operating Conditions per Pole 310 W
Product Main Type	SACE Emax 2
Product Name	Air Circuit Breaker
Product Type	Air Circuit Breaker
Rated Current (I _n)	2500 A
Rated Voltage (U _r)	600 V
Rated Insulation Voltage (U _i)	AC 635 V
Rated Operational Voltage	600 V AC
Release	Ekip Touch LSIG
Release Type	EL
Short-Circuit Performance Level	S
Standards	UL
Sub-type	E4.2
Terminal Connection Type	Rear flat Horizontal
Version	F

Technical UL/CSA

Interrupting Rating acc. to UL1066	(254 V) 65 kA (508 V) 65 kA (635 V) 65 kA
------------------------------------	---

Certificates and Declarations

Data Sheet, Technical Information	1SXU200040C0201
Declaration of Conformity - CE	9AKK106713A5545
Instructions and Manuals	1SDH001000R0002
Instructions and Manuals (Part 2)	1SDH001316R1002

Classifications

ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
IDEA Granular Category Code (IGCC)	4926 >> Air circuit breakers
UNSPSC	39121615
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax 2

