



PRODUCT-DETAILS

E4.2V-A 3200 Ekip Touch LI 3p WMP

E4.2V-A 3200 Ekip Touch LI 3p WMP



General Information	
Extended Product Type	E4.2V-A 3200 Ekip Touch LI 3p WMP
Product ID	1SDA078531R1
EAN	8015644849542
Catalog Description	E4.2V-A 3200 Ekip Touch LI 3p WMP
Long Description	MOVING PART FOR C.BREAKER SACE EMAX2 E4.2V-A 3200 UL THREE-POLE WITH SOLID -STATE RELEASE IN AC EKIP/TOUCH-LI R 3200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

ABB EcoSolutions	
ABB EcoSolutions	Yes

Circular Value	
Circular Design	Design for Closing Resource Loops - Standard EN45555 - 79.3 %
Principles Recyclability Rate	
Conflict Minerals	9AKK108467A5658

Reporting Template (CMRT)		
End of Life Instructions		9AKK108468A2363
Group Waste to Landfill Target	UL 2799 Zero Waste To Landfill Validation available	
Toxic Substances Control Act - TSCA		9AKK108467A8326

Eco Transparency

Environmental Product Declaration - EPD	9AKK108468A1907
---	-----------------

Environmental

Environmental Information	9AKK108467A6707
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

Order Code US and Canada	Z4VHUNAD000A000000XX
EAN	8015644849542
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	425 mm
Product Net Height	425 mm
Product Net Depth / Length	393 mm
Product Net Weight	85 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	515 mm
Package Level 1 Height	610 mm
Package Level 1 Depth / Length	615 mm
Package Level 1 Gross Weight	75 kg
Package Level 1 EAN	8015644849542

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 7000 cycle

	20 cycles per hour
Mechanical Durability	20000 cycle
	60 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 610 W
Product Main Type	SACE Emax 2
Product Name	Air Circuit Breaker
Product Type	Air Circuit Breaker
Rated Current (I _n)	3200 A
Rated Voltage (U _r)	600 V
Rated Insulation Voltage (U _i)	AC 635 V
Rated Operational Voltage	600 V AC
Release	Ekip Touch LI
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL
Sub-type	E4.2
Version	W

Technical UL/CSA

Interrupting Rating acc. to UL1066	(254 V) 100 kA (508 V) 100 kA (635 V) 100 kA
------------------------------------	--

Certificates and Declarations

Data Sheet, Technical Information	1SXU200040C0201
Declaration of Conformity - CE	9AKK106713A5545
Instructions and Manuals	1SDH001000R0002
Instructions and Manuals (Part 2)	1SDH001316R1002

Classifications

ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
IDEA Granular Category Code (IGCC)	4926 >> Air circuit breakers
UNSPSC	39121615
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax 2

