



PRODUCT-DETAILS

E4.2H-A 2500 Ekip G Hi-Touch LSIG 4p WMP

E4.2H-A 2500 Ekip G Hi-Touch LSIG 4p WMP



General Information	
Extended Product Type	E4.2H-A 2500 Ekip G Hi-Touch LSIG 4p WMP
Product ID	1SDA078607R1
EAN	8015644850302
Catalog Description	E4.2H-A 2500 Ekip G Hi-Touch LSIG 4p WMP
Long Description	MOVING PART FOR C.BREAKER SACE EMAX2 E4.2H-A 2500 UL FOUR-POLE WITH SOLID-STATE RELEASE IN AC EKIP/G/HI-TOUCH-LSIG R 2500 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED
ABB EcoSolutions	
ABB EcoSolutions	Yes
Circular Value	
Circular Design Principles	Design for Closing Resource Loops - Standard EN45555 - 79.3 %
Recyclability Rate	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658

End of Life Instructions	9AKK108468A2363
Group Waste to Landfill Target	UL 2799 Zero Waste To Landfill Validation available
Toxic Substances Control Act - TSCA	9AKK108467A8326

Eco Transparency

Environmental Product Declaration - EPD	9AKK108468A1907
---	-----------------

Environmental

Environmental Information	9AKK108467A6707
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

Order Code US and Canada	ZCHGULAQ200A000000XX
EAN	8015644850302
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	551 mm
Product Net Height	425 mm
Product Net Depth / Length	393 mm
Product Net Weight	85 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	515 mm
Package Level 1 Height	610 mm
Package Level 1 Depth / Length	785 mm
Package Level 1 Gross Weight	91 kg
Package Level 1 EAN	8015644850302

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 20 cycles per hour
Mechanical Durability	20000 cycle 60 cycles per hour
Neutral Pole Current ([% Iu])	100 %
Number of Poles	4
Power Loss	at Rated Operating Conditions per Pole 410 W

Product Main Type	SACE Emax 2
Product Name	Air Circuit Breaker
Product Type	Air Circuit Breaker
Rated Current (I_n)	2500 A
Rated Voltage (U_r)	600 V
Rated Insulation Voltage (U_i)	AC 635 V
Rated Operational Voltage	600 V AC
Release	Ekip G Hi-Touch LSIG
Release Type	EL
Short-Circuit Performance Level	H
Standards	UL
Sub-type	E4.2
Version	W

Technical UL/CSA

Interrupting Rating acc. to UL1066	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA
------------------------------------	---

Certificates and Declarations

Data Sheet, Technical Information	1SXU200040C0201
Declaration of Conformity - CE	9AKK106713A5545
Instructions and Manuals	1SDH001000R0002
Instructions and Manuals (Part 2)	1SDH001316R1002

Classifications

ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
IDEA Granular Category Code (IGCC)	4926 >> Air circuit breakers
UNSPSC	39121615
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax 2

