



PRODUCT-DETAILS

# E4.2V-A 2500 Ekip Touch LSIG 4p WMP

# E4.2V-A 2500 Ekip Touch LSIG 4p WMP



| General Information   |                                                                                                                                                                                             |
|-----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | E4.2V-A 2500 Ekip Touch LSIG 4p WMP                                                                                                                                                         |
| Product ID            | 1SDA078753R1                                                                                                                                                                                |
| EAN                   | 8015644851767                                                                                                                                                                               |
| Catalog Description   | E4.2V-A 2500 Ekip Touch LSIG 4p WMP                                                                                                                                                         |
| Long Description      | MOVING PART FOR C.BREAKER SACE EMAX2 E4.2V-A 2500 UL FOUR-POLE WITH SOLID-STATE RELEASE IN AC EKIP/TOUCH-LSIG R 2500 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED |

| ABB EcoSolutions |     |
|------------------|-----|
| ABB EcoSolutions | Yes |

| Circular Value                                    |                                                               |
|---------------------------------------------------|---------------------------------------------------------------|
| Circular Design Principles<br>Recyclability Rate  | Design for Closing Resource Loops - Standard EN45555 - 79.3 % |
| Conflict Minerals<br>Reporting Template<br>(CMRT) | 9AKK108467A5658                                               |

|                                     |                                                     |
|-------------------------------------|-----------------------------------------------------|
| End of Life Instructions            | 9AKK108468A2363                                     |
| Group Waste to Landfill Target      | UL 2799 Zero Waste To Landfill Validation available |
| Toxic Substances Control Act - TSCA | 9AKK108467A8326                                     |

Eco Transparency

|                                         |                 |
|-----------------------------------------|-----------------|
| Environmental Product Declaration - EPD | 9AKK108468A1907 |
|-----------------------------------------|-----------------|

Environmental

|                           |                                                                        |
|---------------------------|------------------------------------------------------------------------|
| Environmental Information | 9AKK108467A6707                                                        |
| REACH Declaration         | 9AKK108466A1425                                                        |
| RoHS Information          | 9AKK108466A1424                                                        |
| RoHS Status               | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |

Ordering

|                          |                      |
|--------------------------|----------------------|
| Order Code US and Canada | ZCVGULAF000A000000XX |
| EAN                      | 8015644851767        |
| Minimum Order Quantity   | 1 piece              |
| Customs Tariff Number    | 85362090             |

Dimensions

|                            |        |
|----------------------------|--------|
| Product Net Width          | 551 mm |
| Product Net Height         | 425 mm |
| Product Net Depth / Length | 393 mm |
| Product Net Weight         | 85 kg  |

Container Information

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Units          | box 1 piece   |
| Package Level 1 Width          | 515 mm        |
| Package Level 1 Height         | 610 mm        |
| Package Level 1 Depth / Length | 785 mm        |
| Package Level 1 Gross Weight   | 91 kg         |
| Package Level 1 EAN            | 8015644851767 |

Additional Information

|                               |                                                                               |
|-------------------------------|-------------------------------------------------------------------------------|
| Current Type                  | AC                                                                            |
| Electrical Durability         | Ue =< 508 V 8000 cycle<br>Ue = 508 ... 635 V 8000 cycle<br>20 cycles per hour |
| Mechanical Durability         | 20000 cycle<br>60 cycles per hour                                             |
| Neutral Pole Current ([% Iu]) | 100 %                                                                         |
| Number of Poles               | 4                                                                             |
| Power Loss                    | at Rated Operating Conditions per Pole 410 W                                  |

|                                            |                     |
|--------------------------------------------|---------------------|
| Product Main Type                          | SACE Emax 2         |
| Product Name                               | Air Circuit Breaker |
| Product Type                               | Air Circuit Breaker |
| Rated Current (I <sub>n</sub> )            | 2500 A              |
| Rated Voltage (U <sub>r</sub> )            | 600 V               |
| Rated Insulation Voltage (U <sub>i</sub> ) | AC 635 V            |
| Rated Operational Voltage                  | 600 V AC            |
| Release                                    | Ekip Touch LSIG     |
| Release Type                               | EL                  |
| Short-Circuit Performance Level            | V                   |
| Standards                                  | UL                  |
| Sub-type                                   | E4.2                |
| Version                                    | W                   |

Technical UL/CSA

|                                    |                                                    |
|------------------------------------|----------------------------------------------------|
| Interrupting Rating acc. to UL1066 | (254 V) 100 kA<br>(508 V) 100 kA<br>(635 V) 100 kA |
|------------------------------------|----------------------------------------------------|

Certificates and Declarations

|                                   |                 |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 1SXU200040C0201 |
| Declaration of Conformity - CE    | 9AKK106713A5545 |
| Instructions and Manuals          | 1SDH001000R0002 |
| Instructions and Manuals (Part 2) | 1SDH001316R1002 |

Classifications

|                                    |                                                                              |
|------------------------------------|------------------------------------------------------------------------------|
| ETIM 7                             | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| ETIM 8                             | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| ETIM 9                             | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| IDEA Granular Category Code (IGCC) | 4926 >> Air circuit breakers                                                 |
| UNSPSC                             | 39121615                                                                     |
| WEEE Category                      | 4. Large Equipment (Any External Dimension More Than 50 cm)                  |
| eClass                             | V11.1 : 27370409                                                             |

Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax 2

