



PRODUCT-DETAILS

E2.2S-A/MS 1600 4p WMP

E2.2S-A/MS 1600 4p WMP



General Information	
Extended Product Type	E2.2S-A/MS 1600 4p WMP
Product ID	1SDA079589R1
EAN	8015644860127
Catalog Description	E2.2S-A/MS 1600 4p WMP
Long Description	MOVING PART FOR C.BREAKER SWITCH-DISCONNECTOR SACE EMAX2 E2.2S-A/MS 1600 UL FOUR-POLE

ABB EcoSolutions	
ABB EcoSolutions	Yes

Circular Value	
Circular Design Principles Recyclability Rate	Design for Closing Resource Loops - Standard EN45555 - 79.1 %
Conflict Minerals Reporting Template	9AKK108467A5658

(CMRT)		
End of Life Instructions		9AKK108468A2361
Group Waste to Landfill Target	UL 2799 Zero Waste To Landfill Validation available	
Toxic Substances Control Act - TSCA		9AKK108467A8326

Eco Transparency

Environmental Product Declaration - EPD	9AKK108468A1906
---	-----------------

Environmental

Environmental Information	9AKK108467A6707
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

Order Code US and Canada	ZBSE00A00000000000XX
EAN	8015644860127
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	407 mm
Product Net Height	425 mm
Product Net Depth / Length	393 mm
Product Net Weight	49 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	515 mm
Package Level 1 Height	610 mm
Package Level 1 Depth / Length	615 mm
Package Level 1 Gross Weight	68 kg
Package Level 1 EAN	8015644860127

Additional Information

Current Type	AC
Electrical Durability	Ue = < 508 V 12000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour

Mechanical Durability	25000 cycle 60 cycles per hour
Neutral Pole Current ([% I _N])	100 %
Number of Poles	4
Power Loss	at Rated Operating Conditions per Pole 260 W
Product Main Type	SACE Emax 2
Product Name	Switch Disconnecter
Product Type	Switch Disconnecter
Rated Current (I _N)	1600 A
Rated Voltage (U _r)	600 V
Rated Insulation Voltage (U _i)	AC 635 V
Rated Operational Voltage	600 V AC
Short-Circuit Performance Level	S
Standards	UL
Sub-type	E2.2
Version	W

Certificates and Declarations

Data Sheet, Technical Information	1SXU200040C0201
Declaration of Conformity - CE	9AKK106713A5902
Instructions and Manuals	1SDH001000R0002

Classifications

ETIM 7	EC000216 - Switch disconnecter
ETIM 8	EC000216 - Switch disconnecter
ETIM 9	EC000216 - Switch disconnecter (low voltage)
IDEA Granular Category Code (IGCC)	5293 >> Switch disconnecter
UNSPSC	39122233
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27371403

Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax 2

