



PRODUCT-DETAILS

E4.2V-A/MS 2500 3p F HR

E4.2V-A/MS 2500 3p F HR



General Information	
Extended Product Type	E4.2V-A/MS 2500 3p F HR
Product ID	1SDA079602R1
EAN	8015644860257
Catalog Description	E4.2V-A/MS 2500 3p F HR
Long Description	C.BREAKER SWITCH-DISCONNECTOR SACE EMAX2 E4.2V-A/MS 2500 UL FIXED THREE-POLE WITH TERMINALS REAR HORIZONTAL

ABB EcoSolutions	
ABB EcoSolutions	Yes

Circular Value	
Circular Design Principles	Design for Closing Resource Loops - Standard EN45555 - 79.3 %
Recyclability Rate	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
End of Life Instructions	9AKK108468A2363

Group Waste to Landfill Target	UL 2799 Zero Waste To Landfill Validation available
Toxic Substances Control Act - TSCA	9AKK108467A8326

Eco Transparency

Environmental Product Declaration - EPD	9AKK108468A1907
---	-----------------

Environmental

Environmental Information	9AKK108467A6707
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

Order Code US and Canada	Z4VG00B00000000000XX
EAN	8015644860257
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	384 mm
Product Net Height	371 mm
Product Net Depth / Length	270 mm
Product Net Weight	81 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	515 mm
Package Level 1 Height	610 mm
Package Level 1 Depth / Length	615 mm
Package Level 1 Gross Weight	66 kg
Package Level 1 EAN	8015644860257

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 20 cycles per hour
Mechanical Durability	20000 cycle 60 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 310 W
Product Main Type	SACE Emax 2
Product Name	Switch Disconnecter
Product Type	Switch Disconnecter

Rated Current (I_n)	2500 A
Rated Voltage (U_r)	600 V
Rated Insulation Voltage (U_i)	AC 635 V
Rated Operational Voltage	600 V AC
Short-Circuit Performance Level	V
Standards	UL
Sub-type	E4.2
Terminal Connection Type	Rear flat Horizontal
Version	F

Certificates and Declarations

Data Sheet, Technical Information	1SXU200040C0201
Declaration of Conformity - CE	9AKK106713A5545
Instructions and Manuals	1SDH001000R0002

Classifications

ETIM 7	EC000216 - Switch disconnect
ETIM 8	EC000216 - Switch disconnect
ETIM 9	EC000216 - Switch disconnect (low voltage)
IDEA Granular Category Code (IGCC)	5293 >> Switch disconnect
UNSPSC	39122233
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27371403

Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax 2

