



PRODUCT-DETAILS

E6.2L-A/MS 6000 3p WMP

E6.2L-A/MS 6000 3p WMP



General Information	
Extended Product Type	E6.2L-A/MS 6000 3p WMP
Product ID	1SDA079674R1
EAN	8015644860974
Catalog Description	E6.2L-A/MS 6000 3p WMP
Long Description	MOVING PART FOR C.BREAKER SWITCH-DISCONNECTOR SACE EMAX2 E6.2L-A/MS 6000 UL THREE-POLE

ABB EcoSolutions	
ABB EcoSolutions	Yes

Circular Value	
Circular Design Principles	Design for Closing Resource Loops - Standard EN45555 - 77 %
Recyclability Rate	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
End of Life Instructions	9AKK108468A2364

Group Waste to Landfill Target	UL 2799 Zero Waste To Landfill Validation available
Toxic Substances Control Act - TSCA	9AKK108467A8326

Eco Transparency

Environmental Product Declaration - EPD	9AKK108468A1908
---	-----------------

Environmental

Environmental Information	9AKK108467A6707
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

Order Code US and Canada	Z6LL00A00000000000XX
EAN	8015644860974
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	803 mm
Product Net Height	425 mm
Product Net Depth / Length	393 mm
Product Net Weight	116 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	515 mm
Package Level 1 Height	610 mm
Package Level 1 Depth / Length	1000 mm
Package Level 1 Gross Weight	147 kg
Package Level 1 EAN	8015644860974

Additional Information

Current Type	AC
Electrical Durability	Ue = 500 ... 690 V 2000 cycle
Mechanical Durability	12000 cycle
Number of Poles	3
Product Main Type	SACE Emax 2
Product Name	Switch-disconnector
Product Type	Switch-disconnector
Rated Current (I _n)	6000 A
Rated Voltage (U _r)	600 V
Rated Insulation Voltage	AC 635 V

(U _i)	
Rated Operational Voltage	600 V AC
Rated Short-time Withstand Current Low Voltage (I _{cw})	100 kA
Short-Circuit Performance Level	L
Standards	UL
Sub-type	E6.2
Version	W

Certificates and Declarations

Data Sheet, Technical Information	1SXU200040C0201
Declaration of Conformity - CE	9AKK106713A5544
Instructions and Manuals	1SDH001000R0002
Instructions and Manuals (Part 2)	1SDH001316R1002

Classifications

ETIM 7	EC000216 - Switch disconnecter
ETIM 8	EC000216 - Switch disconnecter
ETIM 9	EC000216 - Switch disconnecter (low voltage)
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)
eClass	V11.1 : 27371403

Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax 2

