



PRODUCT-DETAILS

XT1H 160 TMF 16-450 3p F F

XT1H 160 TMF 16-450 3p F F



General Information	
Extended Product Type	XT1H 160 TMF 16-450 3p F F
Product ID	1SDA080835R1
EAN	8015644873639
Catalog Description	XT1H 160 TMF 16-450 3p F F
Long Description	C.BREAKER TMAX XT1H 160 FIXED THREE-POLE WITH FRONT TERMINALS AND THERMOMAGNETIC RELEASE TMF R 16-450 A

ABB EcoSolutions	
ABB EcoSolutions	Yes

Circular Value	
Circular Design Principles Recyclability Rate	Design for Closing Resource Loops - Standard EN45555 - 55.9 %
Conflict Minerals Reporting Template	9AKK108467A5658

(CMRT)

End of Life Instructions	9AKK108468A2347
Group Waste to Landfill Target	UL 2799 Zero Waste To Landfill Validation available
Toxic Substances Control Act - TSCA	9AKK108467A8326

Eco Transparency

Environmental Product Declaration - EPD	9AKK108468A1890 9AKK108468A7793
---	------------------------------------

Environmental

Environmental Information	9AKK108467A6707
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

Order Code US and Canada	XT1HE3016AFF000XXX
EAN	8015644873639
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	76.2 mm
Product Net Height	130 mm
Product Net Depth / Length	70 mm
Product Net Weight	1 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	128 mm
Package Level 1 Height	135 mm
Package Level 1 Depth / Length	143 mm
Package Level 1 Gross Weight	1.1 kg
Package Level 1 EAN	8015644873639

Additional Information

Circuit Breaker Type to be Associated	Power Distribution
Current Type	AC/DC
Electrical Durability	120 cycles per hour

	8000 cycle
Mechanical Durability	240 cycles per hour 25000 cycle
Number of Poles	3
Opening Time	CB with SOR 15 ms CB with UVR 15 ms
Order Multiple	1 piece
Product Main Type	SACE Tmax XT
Product Name	Moulded Case Circuit Breaker
Product Type	Automatic Circuit Breaker
Rated Current (I_n)	16 A
Rated Voltage (U_r)	690 V
Rated Impulse Withstand Voltage (U_{imp})	8 kV
Rated Instantaneous Short-Circuit Current Setting (I_i)	450 A
Rated Insulation Voltage (U_i)	800 V
Rated Operational Voltage	690 V AC 500 V DC
Rated Service Short- Circuit Breaking Capacity (I_{cs})	(220 V AC) 75 kA (230 V AC) 75 kA (240 V AC) 75 kA (380 V AC) 52.5 kA (415 V AC) 37.5 kA (440 V AC) 32.5 kA (500 V AC) 25 kA (525 V AC) 17.5 kA (690 V AC) 5 kA (250 V DC) 2 Poles in Series 52.5 kA (500 V DC) 3 Poles in Series 52.5 kA
Rated Ultimate Short- Circuit Breaking Capacity (I_{cu})	(220 V AC) 100 kA (230 V AC) 100 kA (240 V AC) 100 kA (380 V AC) 70 kA (415 V AC) 70 kA (440 V AC) 65 kA (500 V AC) 50 kA (525 V AC) 35 kA (690 V AC) 10 kA (250 V DC) 2 Poles in Series 70 kA (500 V DC) 3 Poles in Series 70 kA
Rated Uninterrupted Current (I_u)	160 A
Release	TMF
Release Type	TM
Setting Range	16 A
Short-Circuit Performance Level	H
Standards	IEC60947-2
Sub-type	XT1
Terminal Connection Type	Front
Version	F
CAD Dimensional Drawing	1SDH001295R0008

Certificates and Declarations

Data Sheet, Technical Information	1SDC210100D0206 1SDC210099D0206
Declaration of Conformity - CE	9AKK106713A5532
Mechanical Drawings	1SDH000719R0100
Wiring Diagram	1SDM000068R0001
Instructions and Manuals	1SDH000719R0001

Classifications

ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax XT

