



PRODUCT-DETAILS

XT2X 125 TMA 110 550..1100 4p F F UL/CSA

XT2X 125 TMA 110 550..1100 4p F F UL/CSA



General Information

Extended Product Type	XT2X 125 TMA 110 550..1100 4p F F UL/CSA
Product ID	1SDA081930R1
EAN	8015644885038
Catalog Description	XT2X 125 TMA 110 550..1100 4p F F UL/CSA
Long Description	C.BREAKER TMAX XT2X 125 UL/CSA FIXED FOUR-POLE WITH FRONT TERMINALS AND THERMOMAGNETIC RELEASE TMA R 100 I3=550..1000 A

ABB EcoSolutions

ABB EcoSolutions	Yes
------------------	-----

Circular Value

Circular Design Principles	Design for Closing Resource Loops - Standard EN45555 - 55.70 %
Recyclability Rate	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
End of Life Instructions	9AKK108468A2348

Group Waste to Landfill Target	UL 2799 Zero Waste To Landfill Validation available
Toxic Substances Control Act - TSCA	9AKK108467A8326

Eco Transparency

Environmental Product Declaration - EPD	9AKK108468A1891
---	-----------------

Environmental

Environmental Information	9AKK108467A6707
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

Order Code US and Canada	XT2XU4110BFF000XXX
EAN	8015644885038
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	120 mm
Product Net Height	130 mm
Product Net Depth / Length	82.5 mm
Product Net Weight	1.45 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	130 mm
Package Level 1 Height	208 mm
Package Level 1 Depth / Length	145 mm
Package Level 1 Gross Weight	1.55 kg
Package Level 1 EAN	8015644885038

Additional Information

Circuit Breaker Type to be Associated	Power Distribution
Current Type	AC/DC
Electrical Durability	120 cycles per hour 8000 cycle
Mechanical Durability	240 cycles per hour 25000 cycle
Number of Poles	4
Opening Time	CB with SOR 15 ms CB with UVR 15 ms
Order Multiple	1 piece

Power Loss	at Rated Operating Conditions per Pole 8.8 W
Product Main Type	SACE Tmax XT
Product Name	Moulded Case Circuit Breaker
Product Type	Automatic Circuit Breaker
Rated Current (I _n)	110 A
Rated Voltage (U _r)	600 V
Rated Instantaneous Short-Circuit Current Setting (I _i)	550...1100 A
Rated Operational Voltage	600 V AC 500 V DC
Rated Uninterrupted Current (I _u)	125 A
Release	TMA
Release Type	TM
Setting Range	77...110 A
Short-Circuit Performance Level	X
Standards	UL489
Sub-type	XT2
Suitable for Product Class	SACE Tmax XT
Terminal Connection Type	Front
Version	F
CAD Dimensional Drawing	1SDH002230A1002

Technical UL/CSA

Interrupting Rating acc. to UL489	(240 V AC) 200 kA (480 V AC) 200 kA (600 V AC) 42 kA (250 V DC) 2 Poles in Series 85 kA (500 V DC) 3 Poles in Series 85 kA
-----------------------------------	--

Certificates and Declarations

Data Sheet, Technical Information	1SDC210200D0206 1SDC210199D0206
Declaration of Conformity - CE	9AKK106713A5901
Mechanical Drawings	1SDH000721R0100
Wiring Diagram	1SDM000068R0001
Instructions and Manuals	1SDH000721R0003 1SDH000721R0505

Classifications

ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
IDEA Granular Category Code (IGCC)	4927 >> Molded case circuit breakers
UNSPSC	39121616
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax XT

