




PRODUCT-DETAILS

XT4S-D 150 MCS-UL/CSA Im=3000 4p F F

XT4S-D 150 MCS-UL/CSA Im=3000 4p F F



General Information	
Extended Product Type	XT4S-D 150 MCS-UL/CSA Im=3000 4p F F
Product ID	1SDA083044R1
EAN	8015644897789
Catalog Description	XT4S-D 150 MCS-UL/CSA Im=3000 4p F F
Long Description	SWITCH-DISCONNECTOR TMAX XT4S-D 150 MCS-UL/CSA FIXED FOUR-POLE WITH FRONT TERMINALS Im 3000A

ABB EcoSolutions	
ABB EcoSolutions	Yes

Circular Value	
Circular Design Principles Recyclability Rate	Design for Closing Resource Loops - Standard EN45555 - 56.30 %
Conflict Minerals Reporting Template	9AKK108467A5658

(CMRT)

End of Life Instructions	9AKK108468A2351
Group Waste to Landfill Target	UL 2799 Zero Waste To Landfill Validation available
Toxic Substances Control Act - TSCA	9AKK108467A8326

Eco Transparency

Environmental Product Declaration - EPD	9AKK108468A1892
---	-----------------

Environmental

Environmental Information	9AKK108467A6707
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

Order Code US and Canada	XT4SU4150DFF000XXX
EAN	8015644897789
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	140 mm
Product Net Height	160 mm
Product Net Depth / Length	82.5 mm
Product Net Weight	2.35 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	171 mm
Package Level 1 Height	215 mm
Package Level 1 Depth / Length	151 mm
Package Level 1 Gross Weight	2.6 kg
Package Level 1 EAN	8015644897789

Additional Information

Number of Poles	4
Order Multiple	1 piece
Power Loss	at Rated Operating Conditions per Pole 7.8 W
Product Main Type	SACE Tmax XT

Product Name	Moulded Case Circuit Breaker
Product Type	Switch Disconnecter
Rated Frequency (f)	50 / 60 Hz
Rated Operational Voltage	600 V AC 600 V DC
Rated Short-time Withstand Current Low Voltage (I_{cw})	for 1 s 3.5 kA
Rated Uninterrupted Current (I_u)	150 A
Short-Circuit Performance Level	S
Standards	UL489
Sub-type	XT4
Suitable for Product Class	SACE Tmax XT
Terminal Connection Type	Front
Version	F
CAD Dimensional Drawing	1SDH001295R0677

Technical UL/CSA

Interrupting Rating acc. to UL489	(240 V AC) 100 kA (480 V AC) 35 kA (600 V AC) 22 kA (250 V DC) 2 Poles in Series 42 kA (600 V DC) 3 Poles in Series 50 kA
-----------------------------------	---

Certificates and Declarations

Data Sheet, Technical Information	1SDC210200D0206 1SDC210199D0206
Declaration of Conformity - CE	9AKK106713A5529
Mechanical Drawings	1SDH000722R0100
Wiring Diagram	1SDM000068R0001
Instructions and Manuals	1SDH000722R0003

Classifications

ETIM 7	EC000216 - Switch disconnecter
ETIM 8	EC000216 - Switch disconnecter
ETIM 9	EC000216 - Switch disconnecter (low voltage)
IDEA Granular Category Code (IGCC)	4927 >> Molded case circuit breakers
UNSPSC	39121616
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27371403

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax XT

