



PRODUCT-DETAILS

XT2S 160 Ekip Dip LIG In=25A 3p F F

XT2S 160 Ekip Dip LIG In=25A 3p F F



| General Information | |
|-----------------------|---|
| Extended Product Type | XT2S 160 Ekip Dip LIG In=25A 3p F F |
| Product ID | 1SDA100041R1 |
| EAN | 8056221000956 |
| Catalog Description | XT2S 160 Ekip Dip LIG In=25A 3p F F |
| Long Description | C.BREAKER TMAX XT2S 160 FIXED THREE-POLE WITH FRONT TERMINALS AND SOLID-STATE RELEASE IN AC EKIP DIP LIG R 25 A |

| ABB EcoSolutions | |
|------------------|-----|
| ABB EcoSolutions | Yes |

| Circular Value | |
|---|--|
| Circular Design Principles Recyclability Rate | Design for Closing Resource Loops - Standard EN45555 - 55.70 % |
| Conflict Minerals Reporting Template | 9AKK108467A5658 |

(CMRT)

| | |
|-------------------------------------|---|
| End of Life Instructions | 9AKK108468A2349 |
| Group Waste to Landfill Target | UL 2799 Zero Waste To Landfill Validation available |
| Toxic Substances Control Act - TSCA | 9AKK108467A8326 |

Eco Transparency

| | |
|---|-----------------|
| Environmental Product Declaration - EPD | 9AKK108469A1855 |
| | 9AKK108468A1897 |

Environmental

| | |
|---------------------------|--|
| Environmental Information | 9AKK108467A6707 |
| REACH Declaration | 9AKK108466A1425 |
| RoHS Information | 9AKK108466A1424 |
| RoHS Status | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |

Ordering

| | |
|--------------------------|--------------------|
| Order Code US and Canada | XT2SE3025CFF000XXX |
| EAN | 8056221000956 |
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85362090 |

Dimensions

| | |
|----------------------------|---------|
| Product Net Width | 90 mm |
| Product Net Height | 130 mm |
| Product Net Depth / Length | 82.5 mm |
| Product Net Weight | 1.12 kg |

Container Information

| | |
|--------------------------------|---------------|
| Package Level 1 Units | box 1 piece |
| Package Level 1 Width | 130 mm |
| Package Level 1 Height | 208 mm |
| Package Level 1 Depth / Length | 145 mm |
| Package Level 1 Gross Weight | 1.22 kg |
| Package Level 1 EAN | 8056221000956 |

Additional Information

| | |
|---------------------------------------|---------------------|
| Circuit Breaker Type to be Associated | Power Distribution |
| Current Type | AC |
| Electrical Durability | 120 cycles per hour |

| | |
|--|--|
| | 8000 cycle |
| Mechanical Durability | 240 cycles per hour 25000 cycle |
| Number of Poles | 3 |
| Order Multiple | 1 piece |
| Power Loss | at Rated Operating Conditions per Pole 0.8 W |
| Product Main Type | SACE Tmax XT |
| Product Name | Moulded Case Circuit Breaker |
| Product Type | Automatic Circuit Breaker |
| Rated Current (I _n) | 25 A |
| Rated Impulse Withstand Voltage (U _{imp}) | 8 kV |
| Rated Insulation Voltage (U _i) | 1000 V |
| Rated Operational Voltage | 690 V AC |
| Rated Service Short- Circuit Breaking Capacity (I _{cs}) | (220 V AC) 85 kA (230 V AC) 85 kA (240 V AC) 85 kA (380 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 36 kA (525 V AC) 25 kA (690 V AC) 12 kA |
| Rated Ultimate Short- Circuit Breaking Capacity (I _{cu}) | (220 V AC) 85 kA (230 V AC) 85 kA (240 V AC) 85 kA (380 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 36 kA (525 V AC) 25 kA (690 V AC) 12 kA |
| Rated Uninterrupted Current (I _u) | 160 A |
| Release | Ekip Dip LIG |
| Release Type | EL |
| Short-Circuit Performance Level | S |
| Standards | IEC60947-2 |
| Sub-type | XT2 |
| Terminal Connection Type | Front |
| Version | F |
| CAD Dimensional Drawing | 1SDH002230A1001 |

Certificates and Declarations

| | |
|--------------------------------------|------------------------------------|
| Data Sheet, Technical Information | 1SDC210100D0206 1SDC210099D0206 |
| Declaration of Conformity - CE | 9AKK106713A5901 |
| Mechanical Drawings | 1SDH000721R0100 |
| Wiring Diagram | 1SDM000068R0001 |
| Instructions and Manuals | 1SDH000721R0001 1SDH000721R0505 |

Classifications

| | |
|----------------------------|--|
| ETIM 7 | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| ETIM 8 | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| ETIM 9 | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| Object Classification Code | Q |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |
| eClass | V11.1 : 27370409 |

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax XT

