



PRODUCT-DETAILS

XT5D 400 3p F F

XT5D 400 3p F F



General Information

Extended Product Type	XT5D 400 3p F F
Product ID	1SDA100546R1
EAN	8056221006224
Catalog Description	XT5D 400 3p F F
Long Description	SWITCH-DISCONNECTOR TMAX XT5D 400 FIXED THREE-POLE WITH FRONT TERMINALS

ABB EcoSolutions

ABB EcoSolutions	Yes
------------------	-----

Circular Value

Circular Design Principles	Design for Closing Resource Loops - Standard EN45555 - 59.6 %
Recyclability Rate	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
End of Life Instructions	9AKK108468A2353

Group Waste to Landfill Target	UL 2799 Zero Waste To Landfill Validation available
Toxic Substances Control Act - TSCA	9AKK108467A8326

Eco Transparency

Environmental Product Declaration - EPD	9AKK108468A9746 9AKK108468A1893
---	------------------------------------

Environmental

Environmental Information	9AKK108467A6707
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
SCIP	045f2cf1-be91-4bcd-b731-887c182e83ea Italy (IT)
Simplified SCIP	01556332-ded2-46e1-9b05-5bac73208121 Germany (DE) eca2a49d-5ad5-4433-9d0b-ae19f16d4e1e Netherlands (NL) dfffb741f-f5c2-479b-9106-31c31ef4ba06 Spain (ES) 6db88e9e-6479-44af-b0b8-e0992f955076 Netherlands (NL) 258f9dcb-4302-4ea1-a8a1-7f689f5848a9 Germany (DE) b76a69cc-0ba2-4ce6-a88f-d186d6966edb Poland (PL) 33c28849-7754-420d-b8c6-f0ccd6b8478a Norway (NO) 22dbb777-bf42-4d24-b54c-a33d1ef48256 Finland (FI) cc90bdc9-48d5-47fe-8df3-adfc2441d412 Netherlands (NL) bf889582-80b0-49a5-9d4a-da0ae1270d58 Germany (DE) 920585fb-c0f9-4371-9465-4fd58eb943c Denmark (DK) 2da870f5-97d8-4cab-8f69-149222185209 Croatia (HR) bc285540-b9a2-4b97-b115-6f6facc2c63a Czech Republic (CZ) 2bc3ddfb-c0b7-4ba1-832a-334db1e85f80 Poland (PL) ae596363-cc3a-4281-ab4b-bdd592d898ba Netherlands (NL) 105bada4-2430-485d-b15c-1103f09a8efc Netherlands (NL) 5b1492c2-10b7-4d22-a2ba-8fdff2fc7c60 Estonia (EE) 87d124d6-f585-4b1b-b84c-9bf107adccde Portugal (PT) 2faf0f7f-1867-4b9d-a79d-316ffcf75e19 Bulgaria (BG) 1b48d7d0-a21e-4f4a-90df-4ac8e1dd4efd Sweden (SE) 29174ac2-3ba6-4cb6-85b4-21b8b9223727 Poland (PL) f7397b96-d7c2-48ef-b3ad-8111935e8936 France (FR) fc258431-4cd3-4234-a135-b43d565660b3 Sweden (SE) 0a5b42b9-53bb-44c0-9816-693d5c0c3532 Greece (GR) 6fb9b86c-8590-43e0-916b-4810ed98fa78 Germany (DE) 0d8844a6-9003-453b-8076-a44f2f970364 Germany (DE) 8fb7fda3-253d-427e-9d0b-e7bf2da3f504 France (FR)

Ordering

Order Code US and Canada	XT5DE340ADFF000XXX
EAN	8056221006224
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	140 mm
Product Net Height	205 mm
Product Net Depth / Length	103.5 mm
Product Net Weight	4.775 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	248 mm
Package Level 1 Height	240 mm
Package Level 1 Depth / Length	285 mm
Package Level 1 Gross Weight	5.263 kg
Package Level 1 EAN	8056221006224

Additional Information

Electrical Durability	120 cycles per hour 7000 cycle
Mechanical Durability	240 cycles per hour 20000 cycle
Number of Poles	3
Order Multiple	1 piece
Product Main Type	SACE Tmax XT
Product Name	Moulded Case Circuit Breaker
Product Type	Switch Disconnecter
Rated Impulse Withstand Voltage (U _{imp})	8 kV
Rated Insulation Voltage (U _i)	1000 V
Rated Operational Current AC-23A (I _e)	(400 V) 400 A (690 V) 400 A
Rated Operational Voltage	690 V AC 750 V DC
Rated Short-time Withstand Current Low Voltage (I _{cw})	5 kA
Rated Uninterrupted Current (I _u)	400 A
RoHS Date	NA
Standards	IEC60947-2
Sub-type	XT5
Terminal Connection Type	Front
Version	F
CAD Dimensional Drawing	1SDH002065A1115 1SDH002065A1131

Certificates and Declarations

Data Sheet, Technical Information	1SDC210100D0206 1SDC210099D0206
Declaration of Conformity - CE	9AKK107680A2824
Mechanical Drawings	1SDH002011A1101
Wiring Diagram	1SDM000005A1001
Instructions and Manuals	1SDH002011A1001

Classifications

ETIM 7	EC000216 - Switch disconnecter
ETIM 8	EC000216 - Switch disconnecter
ETIM 9	EC000216 - Switch disconnecter (low voltage)
Object Classification Code	Q
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27371403

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax XT

