




PRODUCT-DETAILS

XT5D 630 4p F F

XT5D 630 4p F F



General Information	
Extended Product Type	XT5D 630 4p F F
Product ID	1SDA100549R1
EAN	8056221006255
Catalog Description	XT5D 630 4p F F
Long Description	SWITCH-DISCONNECTOR TMAX XT5D 630 FIXED FOUR-POLE WITH FRONT TERMINALS

ABB EcoSolutions	
ABB EcoSolutions	Yes

Circular Value	
Circular Design Principles	Design for Closing Resource Loops - Standard EN45555 - 59.6 %
Recyclability Rate	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
End of Life Instructions	9AKK108468A2353

Group Waste to Landfill Target	UL 2799 Zero Waste To Landfill Validation available
Toxic Substances Control Act - TSCA	9AKK108467A8326

Eco Transparency

Environmental Product Declaration - EPD	9AKK108468A9746 9AKK108468A1893
---	------------------------------------

Environmental

Environmental Information	9AKK108467A6707
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
SCIP	bf15f994-6831-4b5a-8a1d-08ff18684528 Italy (IT)
Simplified SCIP	b8ed9c1f-2415-4d42-9c32-b2becb3b5c0c Germany (DE) e13cdd0b-909b-4787-803c-fa77750dd19a Germany (DE) 953d7c07-5c4d-4af7-b279-138196e17b5f Poland (PL) 55687a76-c562-4e8d-bb42-49cdabe1199e Norway (NO) a18baa3c-7020-41d1-a72c-f13671d21b36 Finland (FI) 7d64434c-7722-4d62-9b3e-908ac2a7539f Netherlands (NL) c2697ba4-1c25-471f-b7d7-ae8731ad3c52 Germany (DE) b6a89e0f-1cd9-47f2-a01e-25e07a4425a5 Denmark (DK) 1fccba85-d044-47b0-b0b7-8b18bbc87015 Croatia (HR) d2dd09ce-cef0-4837-a976-65f4c6e6d872 Czech Republic (CZ) f18c772a-f5e2-418d-83a2-7fa4d57b9911 Poland (PL) fd2f2615-c0a9-4111-a6ba-3136479a3873 Netherlands (NL) cee2832c-72ff-4eef-9bec-22a52d64d496 Netherlands (NL) decfd2a6-3cd8-4eed-adbf-c16e9c9d2a44 Estonia (EE) 5f41e7ad-9a19-4e17-838e-cf2ec0222cd0 Portugal (PT) 34e7d555-b375-43e5-985d-51401b776d23 Bulgaria (BG) ed1e52be-0e22-4118-bafb-6e0aff8b39f6 Sweden (SE) 01c98c44-9950-4bb1-88c7-178a0e9a477d Poland (PL) d2748ad4-97e1-4430-88b1-6f3de75de0d1 France (FR) 33f5a350-2a8c-4ec2-b6ed-ee19926c271b Sweden (SE) 8e6ba879-e194-47fc-9cc0-45b3a7f732c4 Greece (GR) 0e971679-8bea-4de6-8b34-5905ab243498 Germany (DE) ee9a92f2-885e-452d-89a7-89a449ae9259 Germany (DE) ee806ff4-9fb6-4d27-8587-b4fd115b4aa8 France (FR) daadbc90-2a33-4be2-bd50-7736d56e4a5a Netherlands (NL) ac09edab-8219-472c-a9e4-e646b309df69 Spain (ES) b333577e-9c43-4856-bdb2-0470740cadb6 Netherlands (NL)

Ordering

Order Code US and Canada	XT5DE4600DFF000XXX
EAN	8056221006255
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	186 mm
Product Net Height	205 mm
Product Net Depth / Length	103.5 mm
Product Net Weight	5.6 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	248 mm
Package Level 1 Height	240 mm
Package Level 1 Depth / Length	285 mm
Package Level 1 Gross Weight	6.088 kg
Package Level 1 EAN	8056221006255

Additional Information

Electrical Durability	120 cycles per hour 5000 cycle
Mechanical Durability	240 cycles per hour 20000 cycle
Number of Poles	4
Order Multiple	1 piece
Product Main Type	SACE Tmax XT
Product Name	Moulded Case Circuit Breaker
Product Type	Switch Disconnecter
Rated Impulse Withstand Voltage (U _{imp})	8 kV
Rated Insulation Voltage (U _i)	1000 V
Rated Operational Current AC-23A (I _e)	(400 V) 630 A (690 V) 630 A
Rated Operational Voltage	690 V AC 750 V DC
Rated Short-time Withstand Current Low Voltage (I _{cw})	7.6 kA
Rated Uninterrupted Current (I _u)	630 A
Standards	IEC60947-2
Sub-type	XT5
Terminal Connection Type	Front
Version	F
CAD Dimensional Drawing	1SDH002065A1183 1SDH002065A1131

Certificates and Declarations

Data Sheet, Technical Information	1SDC210100D0206 1SDC210099D0206
Declaration of Conformity - CE	9AKK107680A2824
Mechanical Drawings	1SDH002011A1101
Wiring Diagram	1SDM000005A1001
Instructions and Manuals	1SDH002011A1001

Classifications

ETIM 7	EC000216 - Switch disconnecter
ETIM 8	EC000216 - Switch disconnecter
ETIM 9	EC000216 - Switch disconnecter (low voltage)
Object Classification Code	Q
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27371403

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax XT

