



PRODUCT-DETAILS

XT6S 1000 Ekip Dip LIG In=1000 3p F F

XT6S 1000 Ekip Dip LIG In=1000 3p F F



General Information	
Extended Product Type	XT6S 1000 Ekip Dip LIG In=1000 3p F F
Product ID	1SDA100751R1
EAN	8056221008051
Catalog Description	XT6S 1000 Ekip Dip LIG In=1000 3p F F
Long Description	C.BREAKER TMAX XT6S 1000 FIXED THREE-POLE WITH FRONT TERMINALS AND SOLID-STATE RELEASE IN AC EKIP DIP LIG R 1000

ABB EcoSolutions	
ABB EcoSolutions	Yes

Circular Value	
Circular Design Principles Recyclability Rate	Design for Closing Resource Loops - Standard EN45555 - 60 %
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
End of Life Instructions	9AKK108468A2356

Group Waste to Landfill Target	UL 2799 Zero Waste To Landfill Validation available
Toxic Substances Control Act - TSCA	9AKK108467A8326

**Eco Transparency**

Environmental Product Declaration - EPD	9AKK108468A9752 9AKK108468A2295
---	------------------------------------

**Environmental**

Environmental Information	9AKK108467A6707
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

**Ordering**

Order Code US and Canada	XT6SE31K0CFF000XXX
EAN	8056221008051
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

**Dimensions**

Product Net Width	210 mm
Product Net Height	268 mm
Product Net Depth / Length	103.5 mm
Product Net Weight	9.5 kg

**Container Information**

Package Level 1 Units	box 1 piece
Package Level 1 Width	305 mm
Package Level 1 Height	285 mm
Package Level 1 Depth / Length	370 mm
Package Level 1 Gross Weight	11 kg
Package Level 1 EAN	8056221008051

**Additional Information**

Circuit Breaker Type to be Associated	Power Distribution
Current Type	AC
Electrical Durability	120 cycles per hour 5000 cycle
Mechanical Durability	240 cycles per hour 20000 cycle
Number of Poles	3
Order Multiple	1 piece
Power Loss	83.5 W
Product Main Type	SACE Tmax XT

Product Name	Moulded Case Circuit Breaker
Product Type	Automatic Circuit Breaker
Rated Current ( $I_n$ )	1000 A
Rated Impulse Withstand Voltage ( $U_{imp}$ )	8 kV
Rated Insulation Voltage ( $U_i$ )	1000 V
Rated Operational Voltage	690 V AC
Rated Service Short-Circuit Breaking Capacity ( $I_{cs}$ )	(220 V AC) 85 kA (230 V AC) 85 kA (240 V AC) 85 kA (380 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 45 kA (500 V AC) 35 kA (525 V AC) 35 kA (690 V AC) 22 kA
Rated Short-time Withstand Current Low Voltage ( $I_{cwl}$ )	10 kA
Rated Ultimate Short-Circuit Breaking Capacity ( $I_{cu}$ )	(220 V AC) 85 kA (230 V AC) 85 kA (240 V AC) 85 kA (380 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 45 kA (500 V AC) 35 kA (525 V AC) 35 kA (690 V AC) 22 kA (250 V DC) 2 Poles in Series 50 kA (500 V DC) 2 Poles in Series 35 kA (750 V DC) 3 Poles in Series 24 kA
Rated Uninterrupted Current ( $I_u$ )	1000 A
Release	Ekip Dip LIG
Release Type	EL
Short-Circuit Performance Level	S
Standards	IEC60947-2
Sub-type	XT6
Terminal Connection Type	Front
Version	F
CAD Dimensional Drawing	1SDH002065A1190 1SDH002065A1245

### Certificates and Declarations

Data Sheet, Technical Information	1SDC210100D0206 1SDC210099D0206
Declaration of Conformity - CE	9AKK107680A2825
Mechanical Drawings	1SDH002012A1101
Wiring Diagram	1SDM000005A1001
Instructions and Manuals	1SDH002012A1001

### Classifications

ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
Object Classification Code	Q
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

---

## Categories

---

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax XT

