




PRODUCT-DETAILS

XT6N 1000 BREAKING PART 4p F F

XT6N 1000 BREAKING PART 4p F F



General Information

|                       |                                                                   |
|-----------------------|-------------------------------------------------------------------|
| Extended Product Type | XT6N 1000 BREAKING PART 4p F F                                    |
| Product ID            | 1SDA100791R1                                                      |
| EAN                   | 8056221008457                                                     |
| Catalog Description   | XT6N 1000 BREAKING PART 4p F F                                    |
| Long Description      | BREAKING PART TMAX XT6N 1000 FIXED FOUR-POLE WITH FRONT TERMINALS |

ABB EcoSolutions

|                  |     |
|------------------|-----|
| ABB EcoSolutions | Yes |
|------------------|-----|

Circular Value

|                                             |                                                             |
|---------------------------------------------|-------------------------------------------------------------|
| Circular Design Principles                  | Design for Closing Resource Loops - Standard EN45555 - 60 % |
| Recyclability Rate                          |                                                             |
| Conflict Minerals Reporting Template (CMRT) | 9AKK108467A5658                                             |
| End of Life Instructions                    | 9AKK108468A2355                                             |
| Group Waste to Landfill                     | UL 2799 Zero Waste To Landfill Validation available         |

|                                     |                 |
|-------------------------------------|-----------------|
| Target                              |                 |
| Toxic Substances Control Act - TSCA | 9AKK108467A8326 |

Eco Transparency

|                                         |                                    |
|-----------------------------------------|------------------------------------|
| Environmental Product Declaration - EPD | 9AKK108468A9751<br>9AKK108468A1894 |
|-----------------------------------------|------------------------------------|

Environmental

|                           |                                                                        |
|---------------------------|------------------------------------------------------------------------|
| Environmental Information | 9AKK108467A6707                                                        |
| REACH Declaration         | 9AKK108466A1425                                                        |
| RoHS Information          | 9AKK108466A1424                                                        |
| RoHS Status               | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |

Ordering

|                        |               |
|------------------------|---------------|
| EAN                    | 8056221008457 |
| Minimum Order Quantity | 1 piece       |
| Customs Tariff Number  | 85389099      |

Dimensions

|                            |          |
|----------------------------|----------|
| Product Net Width          | 280 mm   |
| Product Net Height         | 268 mm   |
| Product Net Depth / Length | 103.5 mm |
| Product Net Weight         | 10.5 kg  |

Container Information

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Units          | box 1 piece   |
| Package Level 1 Width          | 305 mm        |
| Package Level 1 Height         | 285 mm        |
| Package Level 1 Depth / Length | 370 mm        |
| Package Level 1 Gross Weight   | 12.5 kg       |
| Package Level 1 EAN            | 8056221008457 |

Additional Information

|                                                     |                                    |
|-----------------------------------------------------|------------------------------------|
| Electrical Durability                               | 120 cycles per hour<br>5000 cycle  |
| Mechanical Durability                               | 240 cycles per hour<br>20000 cycle |
| Number of Poles                                     | 4                                  |
| Order Multiple                                      | 1 piece                            |
| Product Main Type                                   | SACE Tmax XT                       |
| Product Name                                        | Moulded Case Circuit Breaker       |
| Product Type                                        | Breaking Part                      |
| Rated Impulse Withstand Voltage (U <sub>imp</sub> ) | 8 kV                               |
| Rated Insulation Voltage (U <sub>i</sub> )          | 1000 V                             |

|                                                                   |                                                                                                                                                                                                                                                                                                    |
|-------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Rated Operational Voltage                                         | 690 V AC<br>750 V DC                                                                                                                                                                                                                                                                               |
| Rated Service Short-Circuit Breaking Capacity (I <sub>cs</sub> )  | (220 V AC) 70 kA<br>(230 V AC) 70 kA<br>(240 V AC) 70 kA<br>(380 V AC) 36 kA<br>(415 V AC) 36 kA<br>(440 V AC) 30 kA<br>(500 V AC) 25 kA<br>(525 V AC) 25 kA<br>(690 V AC) 20 kA<br>(250 V DC) 2 Poles in Series 18 kA<br>(500 V DC) 2 Poles in Series 10 kA<br>(750 V DC) 3 Poles in Series 8 kA  |
| Rated Short-time Withstand Current Low Voltage (I <sub>cw</sub> ) | 10 kA                                                                                                                                                                                                                                                                                              |
| Rated Ultimate Short-Circuit Breaking Capacity (I <sub>cu</sub> ) | (220 V AC) 70 kA<br>(230 V AC) 70 kA<br>(240 V AC) 70 kA<br>(380 V AC) 36 kA<br>(415 V AC) 36 kA<br>(440 V AC) 30 kA<br>(500 V AC) 25 kA<br>(525 V AC) 25 kA<br>(690 V AC) 20 kA<br>(250 V DC) 2 Poles in Series 36 kA<br>(500 V DC) 2 Poles in Series 20 kA<br>(750 V DC) 3 Poles in Series 18 kA |
| Rated Uninterrupted Current (I <sub>u</sub> )                     | 1000 A                                                                                                                                                                                                                                                                                             |
| Short-Circuit Performance Level                                   | N                                                                                                                                                                                                                                                                                                  |
| Standards                                                         | IEC60947-2                                                                                                                                                                                                                                                                                         |
| Sub-type                                                          | XT6                                                                                                                                                                                                                                                                                                |
| Terminal Connection Type                                          | Front                                                                                                                                                                                                                                                                                              |
| Version                                                           | F                                                                                                                                                                                                                                                                                                  |

Certificates and Declarations

|                                   |                                    |
|-----------------------------------|------------------------------------|
| Data Sheet, Technical Information | 1SDC210100D0206<br>1SDC210099D0206 |
| Declaration of Conformity - CE    | 9AKK107680A2825                    |
| Instructions and Manuals          | 1SDH002012A1001                    |

Classifications

|                            |                                                                              |
|----------------------------|------------------------------------------------------------------------------|
| ETIM 7                     | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| ETIM 8                     | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| ETIM 9                     | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| Object Classification Code | Q                                                                            |
| WEEE Category              | 5. Small Equipment (No External Dimension More Than 50 cm)                   |
| eClass                     | V11.1 : 27370409                                                             |

---

## Categories

---

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax XT

