



PRODUCT-DETAILS

XT7H 800 Ekip Touch Meas.LSI In800 4p FF

XT7H 800 Ekip Touch Meas.LSI In800 4p FF



General Information	
Extended Product Type	XT7H 800 Ekip Touch Meas.LSI In800 4p FF
Product ID	1SDA101190R1
EAN	8056221014939
Catalog Description	XT7H 800 Ekip Touch Meas.LSI In800 4p FF
Long Description	C.BREAKER TMAX XT7H 800 FIXED FOUR-POLE WITH FRONT TERMINALS AND LEVER OPERATING MECHANISM AND SOLID-STATE RELEASE IN AC EKIP TOUCH MEASURING LSI R 800

ABB EcoSolutions	
ABB EcoSolutions	Yes

Circular Value	
Circular Design	Design for Closing Resource Loops - Standard EN45555 - 64.1 %
Principles Recyclability Rate	
Conflict Minerals	9AKK108467A5658

Reporting Template (CMRT)	
End of Life Instructions	9AKK108468A2357
Group Waste to Landfill Target	UL 2799 Zero Waste To Landfill Validation available
Toxic Substances Control Act - TSCA	9AKK108467A8326

Eco Transparency

Environmental Product Declaration - EPD	9AKK108468A1895 9AKK108468A4404
---	------------------------------------

Environmental

Ambient Air Temperature	Operation -40 ... 125 °C
Environmental Information	9AKK108467A6707
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
SCIP	257eee95-cf62-4a57-8418-1979d7ae5c71 Italy (IT)
Simplified SCIP	968ac715-1b1f-48c3-aaf7-28af0765ba59 Germany (DE) 656967f9-90dd-458e-9d61-ad3da498c44e France (FR) bf08281e-b113-4fdd-b504-a09fe872fbf5 Sweden (SE) e781a362-c443-49ee-855d-dd5a299992ec Croatia (HR) a25a9899-0547-4f9f-9ee7-6f107422502b Netherlands (NL) 8377fb49-95d4-4ed6-9477-bd9f7e1149b1 Bulgaria (BG) 59e8471c-86b4-48f2-b456-e7dcebdf6a6d Portugal (PT) 8cec32e5-9ee7-458d-b772-f3ad0e40714b Greece (GR) a0115d85-c9bc-4e00-8b79-6965f8b67bb2 Spain (ES) 5e9431d3-e4de-4792-8b76-221708a6a70c Hungary (HU) 116ec71f-08ed-443a-987a-2dfb1938853d Belgium (BE) 588a5361-2e7e-4bb6-a53b-c9d44f20790e Czech Republic (CZ) fde147cd-24b8-485f-b4cd-34b1e559f514 Poland (PL) 45f39d80-51bc-4d2d-94e7-6dde1265c7b2 Poland (PL) e03175a6-9762-411a-9a42-8f4863c12eb2 Hungary (HU) 67aee78c-bacb-420f-aad1-ee6fa3db2766 Norway (NO) 194e03ac-e276-43b6-8c26-3a96dd54c69c Poland (PL) 3f68c489-30e3-4d08-be04-77839454d4ee France (FR) b3114cc6-2040-4a6c-ac36-cd7d5f21f3bd Finland (FI) fbad39d4-b8ce-4ce7-a032-8f7e14086551 Germany (DE) b223325e-bad1-45ab-b492-1c7b33594741 Germany (DE) a7981924-38a8-4409-85af-118587d0c5a3 Germany (DE) c4044263-53f6-4f4c-a534-4a229cea5b8f Denmark (DK) f89d5f01-3e76-461e-9fd4-efdb1c8ad1dd Estonia (EE) 7fbd4c1c-1cb0-400e-96ad-86ef238c0ae9 Germany (DE) 5e669c58-2fd1-46f7-ab14-5ab4102b4ec0 Sweden (SE) 258c46d5-f137-44d0-8e4c-81caa316d319 Belgium (BE)

Ordering

Order Code US and Canada	XT7HE480CRFF000XXX
EAN	8056221014939
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	280 mm
Product Net Height	268 mm
Product Net Depth / Length	166 mm
Product Net Weight	12.5 kg

Container Information	
Package Level 1 Units	box 1 piece
Package Level 1 Width	360 mm
Package Level 1 Height	350 mm
Package Level 1 Depth / Length	360 mm
Package Level 1 Gross Weight	14 kg
Package Level 1 EAN	8056221014939

Additional Information	
Circuit Breaker Type to be Associated	Power Distribution
Current Type	AC
Electrical Durability	120 cycles per hour 3000 cycle
Mechanical Durability	240 cycles per hour 10000 cycle
Number of Poles	4
Order Multiple	1 piece
Power Loss	at Rated Operating Conditions per Pole 24 W
Product Main Type	SACE Tmax XT
Product Name	Moulded Case Circuit Breaker
Product Type	Automatic Circuit Breaker
Rated Current (I_n)	800 A
Rated Impulse Withstand Voltage (U_{imp})	8 kV
Rated Insulation Voltage (U_i)	1000 V
Rated Operational Voltage	690 V AC
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(220 V AC) 100 kA (230 V AC) 100 kA (240 V AC) 100 kA (380 V AC) 70 kA (415 V AC) 70 kA (440 V AC) 65 kA (500 V AC) 50 kA (525 V AC) 50 kA (690 V AC) 42 kA
Rated Short-time Withstand Current Low Voltage (I_{cw})	20 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu})	(220 V AC) 100 kA (230 V AC) 100 kA (240 V AC) 100 kA (380 V AC) 70 kA (415 V AC) 70 kA

	(440 V AC) 65 kA (500 V AC) 50 kA (525 V AC) 50 kA (690 V AC) 42 kA
Rated Uninterrupted Current (I _u)	800 A
Release	Ekip Touch Measuring LSI
Release Type	EL
Short-Circuit Performance Level	H
Standards	IEC60947-2
Sub-type	XT7
Terminal Connection Type	Front
Version	F
CAD Dimensional Drawing	1SDH002065A1390 1SDH002065A1338

Certificates and Declarations

Data Sheet, Technical Information	1SDC210100D0206 1SDC210099D0206
Declaration of Conformity - CE	9AKK107046A9648
Mechanical Drawings	1SDH002013A1101
Wiring Diagram	1SDM000002A1001
Instructions and Manuals	1SDH002013A1001 1SDH002013A1002 1SDH001821A1001

Classifications

ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
Object Classification Code	Q
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax XT

