



PRODUCT-DETAILS

XT7L 1250 Ekip Dip LS/I In=1250A 4p F F

XT7L 1250 Ekip Dip LS/I In=1250A 4p F F



| General Information   |                                                                                                                                                |
|-----------------------|------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | XT7L 1250 Ekip Dip LS/I In=1250A 4p F F                                                                                                        |
| Product ID            | 1SDA101228R1                                                                                                                                   |
| EAN                   | 8056221015318                                                                                                                                  |
| Catalog Description   | XT7L 1250 Ekip Dip LS/I In=1250A 4p F F                                                                                                        |
| Long Description      | C.BREAKER TMAX XT7L 1250 FIXED FOUR-POLE WITH FRONT TERMINALS AND LEVER OPERATING MECHANISM AND SOLID-STATE RELEASE IN AC EKIP DIP LS/I R 1250 |

| ABB EcoSolutions |     |
|------------------|-----|
| ABB EcoSolutions | Yes |

| Circular Value                                |                                                               |
|-----------------------------------------------|---------------------------------------------------------------|
| Circular Design Principles Recyclability Rate | Design for Closing Resource Loops - Standard EN45555 - 64.1 % |
| Conflict Minerals Reporting Template          | 9AKK108467A5658                                               |

(CMRT)

|                                     |                                                     |
|-------------------------------------|-----------------------------------------------------|
| End of Life Instructions            | 9AKK108468A2357                                     |
| Group Waste to Landfill Target      | UL 2799 Zero Waste To Landfill Validation available |
| Toxic Substances Control Act - TSCA | 9AKK108467A8326                                     |

Eco Transparency

|                                         |                                    |
|-----------------------------------------|------------------------------------|
| Environmental Product Declaration - EPD | 9AKK108468A1895<br>9AKK108468A4404 |
|-----------------------------------------|------------------------------------|

Environmental

|                           |                                                                        |
|---------------------------|------------------------------------------------------------------------|
| Ambient Air Temperature   | Operation -40 ... 125 °C                                               |
| Environmental Information | 9AKK108467A6707                                                        |
| REACH Declaration         | 9AKK108466A1425                                                        |
| RoHS Information          | 9AKK108466A1424                                                        |
| RoHS Status               | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |

Ordering

|                          |                    |
|--------------------------|--------------------|
| Order Code US and Canada | XT7LE412EEFF000XXX |
| EAN                      | 8056221015318      |
| Minimum Order Quantity   | 1 piece            |
| Customs Tariff Number    | 85362090           |

Dimensions

|                            |          |
|----------------------------|----------|
| Product Net Width          | 280 mm   |
| Product Net Height         | 268 mm   |
| Product Net Depth / Length | 166 mm   |
| Product Net Weight         | 17.67 kg |

Container Information

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Units          | box 1 piece   |
| Package Level 1 Width          | 360 mm        |
| Package Level 1 Height         | 350 mm        |
| Package Level 1 Depth / Length | 360 mm        |
| Package Level 1 Gross Weight   | 18.6 kg       |
| Package Level 1 EAN            | 8056221015318 |

Additional Information

|                                       |                    |
|---------------------------------------|--------------------|
| Circuit Breaker Type to be Associated | Power Distribution |
|---------------------------------------|--------------------|

|                                                                    |                                                                                                                                                                                        |
|--------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Current Type                                                       | AC                                                                                                                                                                                     |
| Electrical Durability                                              | 120 cycles per hour<br>3000 cycle                                                                                                                                                      |
| Mechanical Durability                                              | 240 cycles per hour<br>10000 cycle                                                                                                                                                     |
| Number of Poles                                                    | 4                                                                                                                                                                                      |
| Order Multiple                                                     | 1 piece                                                                                                                                                                                |
| Power Loss                                                         | at Rated Operating Conditions per Pole 57 W                                                                                                                                            |
| Product Main Type                                                  | SACE Tmax XT                                                                                                                                                                           |
| Product Name                                                       | Moulded Case Circuit Breaker                                                                                                                                                           |
| Product Type                                                       | Automatic Circuit Breaker                                                                                                                                                              |
| Rated Current ( $I_n$ )                                            | 1250 A                                                                                                                                                                                 |
| Rated Impulse<br>Withstand Voltage ( $U_{imp}$ )                   | 8 kV                                                                                                                                                                                   |
| Rated Insulation Voltage<br>( $U_i$ )                              | 1000 V                                                                                                                                                                                 |
| Rated Operational<br>Voltage                                       | 690 V AC                                                                                                                                                                               |
| Rated Service Short-<br>Circuit Breaking<br>Capacity ( $I_{cs}$ )  | (220 V AC) 200 kA<br>(230 V AC) 200 kA<br>(240 V AC) 200 kA<br>(380 V AC) 120 kA<br>(415 V AC) 120 kA<br>(440 V AC) 100 kA<br>(500 V AC) 85 kA<br>(525 V AC) 65 kA<br>(690 V AC) 50 kA |
| Rated Short-time<br>Withstand Current Low<br>Voltage ( $I_{cw}$ )  | 20 kA                                                                                                                                                                                  |
| Rated Ultimate Short-<br>Circuit Breaking<br>Capacity ( $I_{cu}$ ) | (220 V AC) 200 kA<br>(230 V AC) 200 kA<br>(240 V AC) 200 kA<br>(380 V AC) 120 kA<br>(415 V AC) 120 kA<br>(440 V AC) 100 kA<br>(500 V AC) 85 kA<br>(525 V AC) 65 kA<br>(690 V AC) 50 kA |
| Rated Uninterrupted<br>Current ( $I_u$ )                           | 1250 A                                                                                                                                                                                 |
| Release                                                            | Ekip Dip LS/I                                                                                                                                                                          |
| Release Type                                                       | EL                                                                                                                                                                                     |
| Short-Circuit<br>Performance Level                                 | L                                                                                                                                                                                      |
| Standards                                                          | IEC60947-2                                                                                                                                                                             |
| Sub-type                                                           | XT7                                                                                                                                                                                    |
| Terminal Connection<br>Type                                        | Front                                                                                                                                                                                  |
| Version                                                            | F                                                                                                                                                                                      |
| CAD Dimensional<br>Drawing                                         | 1SDH002065A1390<br>1SDH002065A1338                                                                                                                                                     |

## Certificates and Declarations

|                                      |                                    |
|--------------------------------------|------------------------------------|
| Data Sheet, Technical<br>Information | 1SDC210100D0206<br>1SDC210099D0206 |
| Declaration of<br>Conformity - CE    | 9AKK107046A9648                    |
| Mechanical Drawings                  | 1SDH002013A1101                    |

|                  |                 |
|------------------|-----------------|
| Wiring Diagram   | 1SDM000002A1001 |
| Instructions and | 1SDH002013A1001 |
| Manuals          | 1SDH002013A1002 |

Classifications

|                            |                                                                              |
|----------------------------|------------------------------------------------------------------------------|
| ETIM 7                     | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| ETIM 8                     | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| ETIM 9                     | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| Object Classification Code | Q                                                                            |
| WEEE Category              | 5. Small Equipment (No External Dimension More Than 50 cm)                   |
| eClass                     | V11.1 : 27370409                                                             |

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax XT

