



PRODUCT-DETAILS

XT2L 160 Ekip Dip LIG In=10A 4p F F

XT2L 160 Ekip Dip LIG In=10A 4p F F



General Information	
Extended Product Type	XT2L 160 Ekip Dip LIG In=10A 4p F F
Product ID	1SDA101951R1
EAN	8056221019958
Catalog Description	XT2L 160 Ekip Dip LIG In=10A 4p F F
Long Description	C.BREAKER TMAX XT2L 160 FIXED FOUR-POLE WITH FRONT TERMINALS AND SOLID-STATE RELEASE IN AC EKIP DIP LIG R 10 A

Circular Value	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Toxic Substances Control Act - TSCA	9AKK108467A8326

Environmental	
Environmental	9AKK108467A6707

Information	
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

Order Code US and Canada	XT2LE4010CFF000XXX
EAN	8056221019958
Minimum Order Quantity	1 piece
Customs Tariff Number	85389099

Dimensions

Product Net Width	120 mm
Product Net Height	130 mm
Product Net Depth / Length	82.5 mm
Product Net Weight	1.3 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	120 mm
Package Level 1 Height	160 mm
Package Level 1 Depth / Length	190 mm
Package Level 1 Gross Weight	1.4 kg
Package Level 1 EAN	8056221019958

Additional Information

Circuit Breaker Type to be Associated	Power Distribution
Current Type	AC
Electrical Durability	120 cycles per hour 8000 cycle
Mechanical Durability	240 cycles per hour 25000 cycle
Number of Poles	4
Order Multiple	1 piece
Power Loss	at Rated Operating Conditions per Pole 0.1 W
Product Main Type	SACE Tmax XT
Product Name	Moulded Case Circuit Breaker
Product Type	Automatic Circuit Breaker
Rated Current (I_n)	10 A
Rated Impulse Withstand Voltage (U_{imp})	8 kV
Rated Insulation Voltage (U_i)	1000 V
Rated Operational Voltage	690 V AC 500 V DC

Rated Service Short-Circuit Breaking Capacity (I _{cs})	(220 V AC) 150 kA
	(230 V AC) 150 kA
	(240 V AC) 150 kA
	(380 V AC) 120 kA
	(415 V AC) 120 kA
	(440 V AC) 100 kA
	(500 V AC) 60 kA
	(525 V AC) 36 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu})	(690 V AC) 15 kA
	(220 V AC) 150 kA
	(230 V AC) 150 kA
	(240 V AC) 150 kA
	(380 V AC) 120 kA
	(415 V AC) 120 kA
	(440 V AC) 100 kA
	(500 V AC) 60 kA
Rated Uninterrupted Current (I _u)	(525 V AC) 36 kA
	(690 V AC) 18 kA
	160 A
Release	Ekip Dip LIG
Release Type	EL
Short-Circuit Performance Level	L
Standards	IEC60947-2
Sub-type	XT2
Terminal Connection Type	Front
Version	F
CAD Dimensional Drawing	1SDH002230A1002

Certificates and Declarations

Data Sheet, Technical Information	1SDC210100D0206
	1SDC210099D0206
Declaration of Conformity - CE	9AKK106713A5901
Mechanical Drawings	1SDH000721R0100
Wiring Diagram	1SDM000068R0001
Instructions and Manuals	1SDH000722R0001
	1SDH000721R0505

Classifications

ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
Object Classification Code	Q
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax XT

