



PRODUCT-DETAILS

XT2H 125 Ekip Dip LIG In10A 4p FF UL/CSA

XT2H 125 Ekip Dip LIG In10A 4p FF UL/CSA



| General Information | |
|-----------------------|---|
| Extended Product Type | XT2H 125 Ekip Dip LIG In10A 4p FF UL/CSA |
| Product ID | 1SDA102142R1 |
| EAN | 8015644026530 |
| Catalog Description | XT2H 125 Ekip Dip LIG In10A 4p FF UL/CSA |
| Long Description | C.BREAKER TMAX XT2H 125 UL/CSA FIXED FOUR-POLE WITH FRONT TERMINALS AND SOLID-STATE RELEASE IN AC EKIP DIP LIG R 10 A |

| ABB EcoSolutions | |
|------------------|-----|
| ABB EcoSolutions | Yes |

| Circular Value | |
|---|--|
| Circular Design Principles Recyclability Rate | Design for Closing Resource Loops - Standard EN45555 - 55.70 % |
| Conflict Minerals Reporting Template | 9AKK108467A5658 |

(CMRT)

| | |
|-------------------------------------|---|
| End of Life Instructions | 9AKK108468A2349 |
| Group Waste to Landfill Target | UL 2799 Zero Waste To Landfill Validation available |
| Toxic Substances Control Act - TSCA | 9AKK108467A8326 |

Eco Transparency

| | |
|---|-----------------|
| Environmental Product Declaration - EPD | 9AKK108468A1897 |
|---|-----------------|

Environmental

| | |
|---------------------------|--|
| Environmental Information | 9AKK108467A6707 |
| REACH Declaration | 9AKK108466A1425 |
| RoHS Information | 9AKK108466A1424 |
| RoHS Status | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |

Ordering

| | |
|--------------------------|--------------------|
| Order Code US and Canada | XT2HU4010CFF000XXX |
| EAN | 8015644026530 |
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85362090 |

Dimensions

| | |
|----------------------------|---------|
| Product Net Width | 120 mm |
| Product Net Height | 130 mm |
| Product Net Depth / Length | 82.5 mm |
| Product Net Weight | 1.5 kg |

Container Information

| | |
|--------------------------------|---------------|
| Package Level 1 Units | box 1 piece |
| Package Level 1 Width | 130 mm |
| Package Level 1 Height | 208 mm |
| Package Level 1 Depth / Length | 145 mm |
| Package Level 1 Gross Weight | 1.6 kg |
| Package Level 1 EAN | 8015644026530 |

Additional Information

| | |
|---------------------------------------|---------------------|
| Circuit Breaker Type to be Associated | Power Distribution |
| Current Type | AC |
| Mechanical Durability | 240 cycles per hour |

| | |
|---|--|
| | 25000 cycle |
| Number of Poles | 4 |
| Order Multiple | 1 piece |
| Power Loss | at Rated Operating Conditions per Pole 0.1 W |
| Product Main Type | SACE Tmax XT |
| Product Name | Moulded Case Circuit Breaker |
| Product Type | Automatic Circuit Breaker |
| Rated Current (I _n) | 10 A |
| Rated Frequency (f) | 50 / 60 Hz |
| Rated Operational Voltage | 600 V AC 500 V DC |
| Rated Uninterrupted Current (I _u) | 125 A |
| Release | Ekip Dip LIG |
| Release Type | EL |
| Short-Circuit Performance Level | H |
| Standards | UL489 |
| Sub-type | XT2 |
| Suitable for Product Class | SACE Tmax XT |
| Terminal Connection Type | Front |
| Version | F |
| CAD Dimensional Drawing | 1SDH002230A1002 |

Technical UL/CSA

| | |
|-----------------------------------|---|
| Interrupting Rating acc. to UL489 | (240 V AC) 150 kA (480 V AC) 65 kA (600 V AC) 25 kA |
|-----------------------------------|---|

Certificates and Declarations

| | |
|-----------------------------------|------------------------------------|
| Data Sheet, Technical Information | 1SDC210200D0206 1SDC210199D0206 |
| Declaration of Conformity - CE | 9AKK106713A5901 |
| Mechanical Drawings | 1SDH000721R0100 |
| Wiring Diagram | 1SDM000068R0001 |
| Instructions and Manuals | 1SDH000721R0003 1SDH000721R0505 |

Classifications

| | |
|------------------------------------|--|
| ETIM 7 | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| ETIM 8 | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| ETIM 9 | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| IDEA Granular Category Code (IGCC) | 4934 >> 4 Pole Non-Interchangeable Trip Electronic Circuit Breakers |
| UNSPSC | 39121616 |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax XT

