



PRODUCT-DETAILS

XT4V 250 EkipMTouchLRIU(MPCB)200 3pFF UL

XT4V 250 EkipMTouchLRIU(MPCB)200 3pFF UL



General Information	
Extended Product Type	XT4V 250 EkipMTouchLRIU(MPCB)200 3pFF UL
Product ID	1SDA102297R1
EAN	8015644028084
Catalog Description	XT4V 250 EkipMTouchLRIU(MPCB)200 3pFF UL
Long Description	C.BREAKER TMAX XT4V 250 UL/CSA FIXED THREE-POLE WITH FRONT TERMINALS AND LEVER OPERATING MECHANISM AND SOLID-STATE RELEASE IN AC EKIP M TOUCH LRIU R 200 (MPCB)

Circular Value	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Toxic Substances Control Act - TSCA	9AKK108467A8326

Environmental	
Environmental Information	9AKK108467A6707
REACH Declaration	9AKK108466A1425

RoHS Information 9AKK108466A1424
 RoHS Status Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

Order Code US and Canada XT4VU3200WFF000XXX
 EAN 8015644028084
 Minimum Order Quantity 1 piece
 Customs Tariff Number 85362090

Dimensions

Product Net Width 105 mm
 Product Net Height 160 mm
 Product Net Depth / Length 82.5 mm
 Product Net Weight 9.7 kg

Container Information

Package Level 1 Units box 1 piece
 Package Level 1 Width 280 mm
 Package Level 1 Height 350 mm
 Package Level 1 Depth / Length 360 mm
 Package Level 1 Gross Weight 11.2 kg
 Package Level 1 EAN 8015644028084

Additional Information

Circuit Breaker Type to be Associated Motor Protection
 Current Type AC
 Mechanical Durability 240 cycles per hour
 25000 cycle
 Number of Poles 3
 Order Multiple 1 piece
 Power Loss at Rated Operating Conditions per Pole 10.5 W
 Product Main Type SACE Tmax XT
 Product Name Moulded Case Circuit Breaker
 Product Type Automatic Circuit Breaker
 Rated Current (I_n) 200 A
 Rated Frequency (f) 50 / 60 Hz
 Rated Operational Voltage 600 V AC
 600 V DC
 Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}) (220 V AC) 200 kA
 (230 V AC) 200 kA
 (240 V AC) 200 kA
 (380 V AC) 150 kA
 (415 V AC) 150 kA
 (440 V AC) 150 kA
 (500 V AC) 85 kA
 (525 V AC) 70 kA
 (690 V AC) 50 kA
 (250 V DC) 2 Poles in Series 100 kA
 (500 V DC) 2 Poles in Series 100 kA
 (500 V DC) 3 Poles in Series 100 kA
 (750 V DC) 3 Poles in Series 50 kA
 Rated Uninterrupted 250 A

Current (I _u)	
Release	Ekip M Touch LRIU
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL489
Sub-type	XT4
Suitable for Product Class	SACE Tmax XT
Terminal Connection Type	Front
Version	F
CAD Dimensional Drawing	1SDH002230A1003

Technical UL/CSA

Interrupting Rating acc. to UL489	(240 V AC) 200 kA (480 V AC) 150 kA (600 V AC) 65 kA
-----------------------------------	--

Certificates and Declarations

Data Sheet, Technical Information	1SDC210200D0206 1SDC210199D0206
Declaration of Conformity - CE	9AKK106713A5529
Wiring Diagram	1SDM000068R0001
Instructions and Manuals	1SDH000722R0003 1SDH002031A1002

Classifications

ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
IDEA Granular Category Code (IGCC)	4932 >> 3 Pole Non-Interchangeable Trip Electronic Circuit Breakers
UNSPSC	39121616
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax XT

