



PRODUCT-DETAILS

XT4N 250 Ekip Dip LIG In225 4p FF UL/CSA  
XT4N 250 Ekip Dip LIG In225 4p FF UL/CSA



| General Information   |                                                                                                                                                                |
|-----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | XT4N 250 Ekip Dip LIG In225 4p FF UL/CSA                                                                                                                       |
| Product ID            | 1SDA102310R1                                                                                                                                                   |
| EAN                   | 8015644028213                                                                                                                                                  |
| Catalog Description   | XT4N 250 Ekip Dip LIG In225 4p FF UL/CSA                                                                                                                       |
| Long Description      | XT4N 250 Ekip Dip LSIG 250 4p FF UL/CSA C.BREAKER TMAX XT4N 250 UL/CSA FIXED FOUR-POLE WITH FRONT TERMINALS AND SOLID-STATE RELEASE IN AC EKIP DIP LIG R 225 A |

| ABB EcoSolutions |     |
|------------------|-----|
| ABB EcoSolutions | Yes |

| Circular Value                |                                                                |
|-------------------------------|----------------------------------------------------------------|
| Circular Design               | Design for Closing Resource Loops - Standard EN45555 - 56.30 % |
| Principles Recyclability Rate |                                                                |
| Conflict Minerals             | 9AKK108467A5658                                                |

Reporting Template  
(CMRT)

|                                     |                                                     |
|-------------------------------------|-----------------------------------------------------|
| End of Life Instructions            | 9AKK108468A2352                                     |
| Group Waste to Landfill Target      | UL 2799 Zero Waste To Landfill Validation available |
| Toxic Substances Control Act - TSCA | 9AKK108467A8326                                     |

Eco Transparency

|                                         |                 |
|-----------------------------------------|-----------------|
| Environmental Product Declaration - EPD | 9AKK108468A1898 |
|-----------------------------------------|-----------------|

Environmental

|                           |                                                                        |
|---------------------------|------------------------------------------------------------------------|
| Environmental Information | 9AKK108467A6707                                                        |
| REACH Declaration         | 9AKK108466A1425                                                        |
| RoHS Information          | 9AKK108466A1424                                                        |
| RoHS Status               | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |

Ordering

|                          |                    |
|--------------------------|--------------------|
| Order Code US and Canada | XT4NU4225CFF000XXX |
| EAN                      | 8015644028213      |
| Minimum Order Quantity   | 1 piece            |
| Customs Tariff Number    | 85362090           |

Dimensions

|                            |         |
|----------------------------|---------|
| Product Net Width          | 140 mm  |
| Product Net Height         | 160 mm  |
| Product Net Depth / Length | 82.5 mm |
| Product Net Weight         | 3.05 kg |

Container Information

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Units          | box 1 piece   |
| Package Level 1 Width          | 145 mm        |
| Package Level 1 Height         | 210 mm        |
| Package Level 1 Depth / Length | 168 mm        |
| Package Level 1 Gross Weight   | 3.5 kg        |
| Package Level 1 EAN            | 8015644028213 |

Additional Information

|                                       |                    |
|---------------------------------------|--------------------|
| Circuit Breaker Type to be Associated | Power Distribution |
| Current Type                          | AC                 |

|                                               |                                               |
|-----------------------------------------------|-----------------------------------------------|
| Mechanical Durability                         | 240 cycles per hour<br>25000 cycle            |
| Number of Poles                               | 4                                             |
| Order Multiple                                | 1 piece                                       |
| Power Loss                                    | at Rated Operating Conditions per Pole 13.3 W |
| Product Main Type                             | SACE Tmax XT                                  |
| Product Name                                  | Moulded Case Circuit Breaker                  |
| Product Type                                  | Automatic Circuit Breaker                     |
| Rated Current (I <sub>n</sub> )               | 225 A                                         |
| Rated Frequency (f)                           | 50 / 60 Hz                                    |
| Rated Operational Voltage                     | 600 V AC<br>600 V DC                          |
| Rated Uninterrupted Current (I <sub>u</sub> ) | 250 A                                         |
| Release                                       | Ekip Dip LIG                                  |
| Release Type                                  | EL                                            |
| Short-Circuit Performance Level               | N                                             |
| Standards                                     | UL489                                         |
| Sub-type                                      | XT4                                           |
| Suitable for Product Class                    | SACE Tmax XT                                  |
| Terminal Connection Type                      | Front                                         |
| Version                                       | F                                             |
| CAD Dimensional Drawing                       | 1SDH001295R0677                               |

Technical UL/CSA

|                                   |                                                          |
|-----------------------------------|----------------------------------------------------------|
| Interrupting Rating acc. to UL489 | (240 V AC) 65 kA<br>(480 V AC) 25 kA<br>(600 V AC) 18 kA |
|-----------------------------------|----------------------------------------------------------|

Certificates and Declarations

|                                   |                                    |
|-----------------------------------|------------------------------------|
| Data Sheet, Technical Information | 1SDC210200D0206<br>1SDC210199D0206 |
| Declaration of Conformity - CE    | 9AKK106713A5529                    |
| Mechanical Drawings               | 1SDH000722R0100                    |
| Wiring Diagram                    | 1SDM000068R0001                    |
| Instructions and Manuals          | 1SDH000722R0003<br>1SDH000721R0505 |

Classifications

|                                    |                                                                              |
|------------------------------------|------------------------------------------------------------------------------|
| ETIM 7                             | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| ETIM 8                             | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| ETIM 9                             | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| IDEA Granular Category Code (IGCC) | 4934 >> 4 Pole Non-Interchangeable Trip Electronic Circuit Breakers          |
| UNSPSC                             | 39121616                                                                     |

|               |                                                            |
|---------------|------------------------------------------------------------|
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |
| eClass        | V11.1 : 27370409                                           |

---

## Categories

---

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax XT

