



PRODUCT-DETAILS

XT5N 400 Ekip Dip LS/I 400 3p FF UL/CSA

XT5N 400 Ekip Dip LS/I 400 3p FF UL/CSA



General Information	
Extended Product Type	XT5N 400 Ekip Dip LS/I 400 3p FF UL/CSA
Product ID	1SDA102449R1
EAN	8056221021807
Catalog Description	XT5N 400 Ekip Dip LS/I 400 3p FF UL/CSA
Long Description	C.BREAKER TMAX XT5N 400 UL/CSA FIXED THREE-POLE WITH FRONT TERMINALS AND SOLID-STATE RELEASE IN AC EKIP DIP LS/I R 400

ABB EcoSolutions	
ABB EcoSolutions	Yes

Circular Value	
Circular Design Principles	Design for Closing Resource Loops - Standard EN45555 - 59.6 %
Recyclability Rate	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
End of Life Instructions	9AKK108468A2354

Group Waste to Landfill Target	UL 2799 Zero Waste To Landfill Validation available
Toxic Substances Control Act - TSCA	9AKK108467A8326

Eco Transparency

Environmental Product Declaration - EPD	9AKK108468A1899
---	-----------------

Environmental

Environmental Information	9AKK108467A6707
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
SCIP	a26de2e9-ccdc-4a00-acff-236bb3f8c913 Italy (IT)
Simplified SCIP	3137446f-5243-45de-9747-0b60c0d19bbe Germany (DE) af5b8474-8afd-4fb2-a7af-5a3d1ca209f3 Netherlands (NL) 708e883a-0be6-46ed-a81d-b839a765315f Hungary (HU) 7aa6c81a-e199-49ec-98b1-399e5664f642 Denmark (DK) 9e8c11e4-f32c-4e65-8f91-82b1d1a4590d Sweden (SE) 106a4413-8a8e-43f1-965c-f1b533e565ad Poland (PL) 00a9fb46-4b32-4ce3-a72c-66410f394be0 Bulgaria (BG) 800f40f5-923b-4e35-8d33-e1165af8b5dc Portugal (PT) c25ef05c-c032-4f31-a6fe-491588f4f864 Greece (GR) 64935929-4360-4550-822d-25e041006830 Estonia (EE) 1582c82e-f4ba-466a-aa83-6911479a7e7f Germany (DE) 5b8a334a-fa2e-4942-8758-3449c17c3743 Poland (PL) d3b80abd-ab31-49e2-b063-a78b2a153a2f Norway (NO) 6de4c68f-15f6-42b2-b04b-5c14bf749ff9 Croatia (HR) df4b58c7-ec23-4c8d-a56d-259c8d53cfa3 Belgium (BE) 45992ad2-2332-461f-8ba3-30647b763ff3 Czech Republic (CZ) 5882b174-f903-419b-a642-ab86fad085b4 Germany (DE) 27b38213-143f-4e6a-8116-8238256c0a95 Germany (DE) d14ef011-3bc9-4d56-8b5d-be45a80b00e0 France (FR) c7cab6eb-3167-4588-aa3c-8bd2c1f4428c Sweden (SE) b4d2c07f-38e7-4aae-ada6-6d85e39cc95e Finland (FI) e63d016d-4c26-46e0-8ffb-18a32cd37650 Belgium (BE) 568d4abc-3378-479c-8977-f258740683f3 France (FR) 9de2a9fc-bca6-4867-abaf-feed0a06bf76 Germany (DE) f0802dd0-908b-4f8e-a4b6-6ed08bbb49a Spain (ES) 02daf472-cc9e-4a64-9395-088559afadb9 Poland (PL) 9698e365-e035-4269-b574-ef3f161949be Hungary (HU)

Ordering

Order Code US and Canada	XT5NU340AEFF000XXX
EAN	8056221021807
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	140 mm
Product Net Height	205 mm
Product Net Depth / Length	103.5 mm
Product Net Weight	5.1 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	248 mm
Package Level 1 Height	240 mm
Package Level 1 Depth / Length	285 mm
Package Level 1 Gross Weight	5.1 kg
Package Level 1 EAN	8056221021807

Additional Information

Circuit Breaker Type to be Associated	Power Distribution
Current Type	AC
Mechanical Durability	240 cycles per hour 20000 cycle
Number of Poles	3
Order Multiple	1 piece
Power Loss	at Rated Operating Conditions per Pole 19.3 W
Product Main Type	SACE Tmax XT
Product Name	Moulded Case Circuit Breaker
Product Type	Automatic Circuit Breaker
Rated Current (I _n)	400 A
Rated Operational Voltage	600 V AC 600 V DC
Rated Uninterrupted Current (I _u)	400 A
Release	Ekip Dip LS/I
Release Type	EL
Short-Circuit Performance Level	N
Standards	UL489
Sub-type	XT5
Suitable for Product Class	SACE Tmax XT
Terminal Connection Type	Front
Version	F
CAD Dimensional Drawing	1SDH002065A1115 1SDH002065A1131

Technical UL/CSA

Interrupting Rating acc. to UL489	(240 V AC) 65 kA (480 V AC) 35 kA (600 V AC) 18 kA
-----------------------------------	--

Certificates and Declarations

Data Sheet, Technical Information	1SDC210200D0206 1SDC210199D0206
Declaration of Conformity - CE	9AKK107680A2824
Mechanical Drawings	1SDH002011A1101
Wiring Diagram	1SDM000005A1001
Instructions and Manuals	1SDH002011A1002

Classifications

ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection

ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
IDEA Granular Category Code (IGCC)	4932 >> 3 Pole Non-Interchangeable Trip Electronic Circuit Breakers
UNSPSC	39121616
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax XT

