



PRODUCT-DETAILS

XT5S 400 Ekip Dip LS/I 400 3p FF UL/CSA
XT5S 400 Ekip Dip LS/I 400 3p FF UL/CSA



General Information	
Extended Product Type	XT5S 400 Ekip Dip LS/I 400 3p FF UL/CSA
Product ID	1SDA102487R1
EAN	8056221022156
Catalog Description	XT5S 400 Ekip Dip LS/I 400 3p FF UL/CSA
Long Description	C.BREAKER TMAX XT5S 400 UL/CSA FIXED THREE-POLE WITH FRONT TERMINALS AND SOLID-STATE RELEASE IN AC EKIP DIP LS/I R 400

ABB EcoSolutions	
ABB EcoSolutions	Yes

Circular Value	
Circular Design Principles Recyclability Rate	Design for Closing Resource Loops - Standard EN45555 - 59.6 %
Conflict Minerals Reporting Template	9AKK108467A5658

(CMRT)

End of Life Instructions	9AKK108468A2354
Group Waste to Landfill Target	UL 2799 Zero Waste To Landfill Validation available
Toxic Substances Control Act - TSCA	9AKK108467A8326

Eco Transparency

Environmental Product Declaration - EPD	9AKK108468A1899
---	-----------------

Environmental

Environmental Information	9AKK108467A6707
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
SCIP	d7faa09f-3241-4a27-a44f-66ba1c9e4655 Italy (IT)
Simplified SCIP	808e9167-9201-4388-be26-2080593f7d17 Germany (DE) fc3099d0-bdd2-4508-a855-fa675ec9fa5b Germany (DE) bfe77987-52cf-4f90-b8b8-76f2f17e042d Poland (PL) 3cd4856a-e4c2-4221-9695-07690ddfc3d Norway (NO) a132c21d-8492-44f4-b258-ece81a8b4602 Finland (FI) fd9654a8-c941-467f-a267-ee2e278aeea6 Netherlands (NL) 89c18b3b-ebc7-4603-8b91-23f449ea850a Germany (DE) 045b3715-eddb-4309-8609-e2b39c297934 Denmark (DK) 76b3ffbc-226f-4a81-b80f-4bebf86f3a2d Germany (DE) 6a62b6c4-ef9d-491c-bc7c-152293d41ce1 Croatia (HR) 74cfbf9f-d3f0-46c6-94bc-176c71b06b23 Czech Republic (CZ) 553972a9-5ec1-4254-a115-56eb50b6d872 Poland (PL) 2f845074-fa2c-422d-aa0f-739428a96776 Netherlands (NL) 180189eb-43fc-4bd1-881f-97a11459ca93 Netherlands (NL) 8903cd05-f0c1-46c9-af06-72eae61d28d7 Estonia (EE) 8e469ef3-e5f3-4086-a95a-01ce782fe71e Greece (GR) faeb65cc-bf8b-4831-ac82-93655826ef58 Portugal (PT) 670aeb2d-c5a3-4085-812b-de804f8a01e9 Bulgaria (BG) 9e0f51ec-5299-4b2f-9662-8f7c46b2283a Sweden (SE) 50e0c754-579f-47d7-adab-bd9cc05554cd Poland (PL) 7756b726-b0d3-40c5-bc2d-270b76661000 France (FR) b7acffd8-b5e6-4ce8-b167-4b8eb892d104 Netherlands (NL) 102a88ed-2f7d-4867-a602-406a577f0ae0 Spain (ES) 16273876-68e1-4d29-9eb9-0bfd775d727e Netherlands (NL) ff7752eb-2fa1-4bfd-8a6a-a358ad458fcd France (FR) 31478a9c-934c-4022-90d8-25786e4a6a31 Sweden (SE) 1516d8cf-59f0-4df5-998e-198170ba0d45 Germany (DE)

Ordering

Order Code US and Canada	XT5SU340AEFF000XXX
EAN	8056221022156
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	140 mm
-------------------	--------

Product Net Height	205 mm
Product Net Depth / Length	103.5 mm
Product Net Weight	5.1 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	248 mm
Package Level 1 Height	240 mm
Package Level 1 Depth / Length	285 mm
Package Level 1 Gross Weight	5.1 kg
Package Level 1 EAN	8056221022156

Additional Information

Circuit Breaker Type to be Associated	Power Distribution
Current Type	AC
Mechanical Durability	240 cycles per hour 20000 cycle
Number of Poles	3
Order Multiple	1 piece
Power Loss	at Rated Operating Conditions per Pole 19.3 W
Product Main Type	SACE Tmax XT
Product Name	Moulded Case Circuit Breaker
Product Type	Automatic Circuit Breaker
Rated Current (I _n)	400 A
Rated Operational Voltage	600 V AC 600 V DC
Rated Uninterrupted Current (I _u)	400 A
Release	Ekip Dip LS/I
Release Type	EL
Short-Circuit Performance Level	S
Standards	UL489
Sub-type	XT5
Suitable for Product Class	SACE Tmax XT
Terminal Connection Type	Front
Version	F
CAD Dimensional Drawing	1SDH002065A1115 1SDH002065A1131

Technical UL/CSA

Interrupting Rating acc. to UL489	(240 V AC) 100 kA (480 V AC) 50 kA (600 V AC) 25 kA
-----------------------------------	---

Certificates and Declarations

Data Sheet, Technical Information	1SDC210200D0206 1SDC210199D0206
Declaration of Conformity - CE	9AKK107680A2824
Mechanical Drawings	1SDH002011A1101
Wiring Diagram	1SDM000005A1001
Instructions and Manuals	1SDH002011A1002

Classifications

ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
IDEA Granular Category Code (IGCC)	4932 >> 3 Pole Non-Interchangeable Trip Electronic Circuit Breakers
UNSPSC	39121616
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax XT

