




PRODUCT-DETAILS

XT5L 600 BREAKING PART 3p F F UL/CSA
XT5L 600 BREAKING PART 3p F F UL/CSA



General Information	
Extended Product Type	XT5L 600 BREAKING PART 3p F F UL/CSA
Product ID	1SDA102686R1
EAN	8056221023795
Catalog Description	XT5L 600 BREAKING PART 3p F F UL/CSA
Long Description	BREAKING PART TMAX XT5L 600 UL/CSA FIXED THREE-POLE WITH FRONT TERMINALS

ABB EcoSolutions	
ABB EcoSolutions	Yes

Circular Value	
Circular Design Principles	Design for Closing Resource Loops - Standard EN45555 - 59.6 %
Recyclability Rate	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
End of Life Instructions	9AKK108468A2353

Group Waste to Landfill Target	UL 2799 Zero Waste To Landfill Validation available
Toxic Substances Control Act - TSCA	9AKK108467A8326

Eco Transparency

Environmental Product Declaration - EPD	9AKK108468A1893
---	-----------------

Environmental

Environmental Information	9AKK108467A6707
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
SCIP	4bc23d4e-9287-446a-a022-18178513c65d Italy (IT)
Simplified SCIP	b93591bd-c159-4c4c-b7c6-44c24f270dfe Germany (DE) 93c67751-3cea-4047-beed-e6ad7e35569a Poland (PL) 77d278b7-b6f7-4adf-af59-bdfc723a3000 Norway (NO) e43d1f73-8e51-45c5-84f9-3735fa1280f2 Finland (FI) df65d694-0f70-4a36-a163-cee3d14fa9fc Netherlands (NL) bd57eb8e-849a-4208-a31d-d3529d461b28 Germany (DE) 376f35c5-1dd9-4804-a22f-629c50538000 Denmark (DK) c7bea5a0-5e21-4cc1-9a40-a72c903ba0a6 Germany (DE) f1fad3ba-dcc1-4968-94cb-48a115990001 Croatia (HR) 180321ea-ee8d-407a-9d7a-fc961b2120c9 Czech Republic (CZ) 6f818233-182d-4d3b-afa0-05e3a917c3bf Poland (PL) e6613477-8b8c-4813-836d-3480224d5c99 Netherlands (NL) 03b483f1-13c5-42c6-8dbb-6cf5e7a77f7b Netherlands (NL) a33f5cd5-ae50-4e83-b2af-5eac6635bc51 Estonia (EE) 36d858c4-4d80-4df6-a325-973e6970339c Greece (GR) 5ca949a7-e1f3-4f13-907d-ec2f065689bd Portugal (PT) 8aedb8f5-07e9-4a9a-b9fe-bf57850878db Bulgaria (BG) e7a2615f-ebd0-46e2-87ea-420de38fb4ad Sweden (SE) 69222f5e-03c6-40c4-80db-4ea87e60dc4e Poland (PL) 16219348-02c8-41fb-bd1b-b5ba627684fe France (FR) a264911e-ca4f-495c-8f47-fe4a7eb3a069 Sweden (SE) c8f2aaa0-5184-4e87-a4cd-a4731ce1c766 Germany (DE) 4cf6f882-1137-4fb0-b22b-60a8457388af Germany (DE) df5cdf80-89ce-4b1c-852c-2802d6e6a134 France (FR) d222abd4-a317-4f3b-8454-7a4e58988f9f Netherlands (NL) 0549e0ff-dfa5-4243-a373-be7aa98485fc Spain (ES) 0f99afe3-647e-4258-ba70-437c833ad94e Netherlands (NL)

Ordering

EAN	8056221023795
Minimum Order Quantity	1 piece
Customs Tariff Number	85389099

Dimensions

Product Net Width	140 mm
Product Net Height	205 mm
Product Net Depth / Length	103.5 mm
Product Net Weight	3.25 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	248 mm

Package Level 1 Height	240 mm
Package Level 1 Depth / Length	285 mm
Package Level 1 Gross Weight	3.8 kg
Package Level 1 EAN	8056221023795

Additional Information

Mechanical Durability	240 cycles per hour 20000 cycle
Number of Poles	3
Order Multiple	1 piece
Product Main Type	SACE Tmax XT
Product Name	Moulded Case Circuit Breaker
Product Type	Breaking Part
Rated Operational Voltage	600 V AC 600 V DC
Rated Uninterrupted Current (I _u)	600 A
Short-Circuit Performance Level	L
Standards	UL489
Sub-type	XT5
Suitable for Product Class	SACE Tmax XT
Terminal Connection Type	Front
Version	F

Technical UL/CSA

Interrupting Rating acc. to UL489	(240 V AC) 200 kA (480 V AC) 100 kA (600 V AC) 65 kA (250 V DC) 2 Poles in Series 100 kA (500 V DC) 2 Poles in Series 70 kA (600 V DC) 3 Poles in Series 50 kA
-----------------------------------	---

Certificates and Declarations

Data Sheet, Technical Information	1SDC210200D0206 1SDC210199D0206
Declaration of Conformity - CE	9AKK107680A2824
Instructions and Manuals	1SDH002011A1002

Classifications

ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax XT

