




PRODUCT-DETAILS

XT5N 400 BREAKING PART 4p F F UL/CSA
XT5N 400 BREAKING PART 4p F F UL/CSA



General Information

Extended Product Type	XT5N 400 BREAKING PART 4p F F UL/CSA
Product ID	1SDA102691R1
EAN	8056221023825
Catalog Description	XT5N 400 BREAKING PART 4p F F UL/CSA
Long Description	BREAKING PART TMAX XT5N 400 UL/CSA FIXED FOUR-POLE WITH FRONT TERMINALS

ABB EcoSolutions

ABB EcoSolutions	Yes
------------------	-----

Circular Value

Circular Design Principles	Design for Closing Resource Loops - Standard EN45555 - 59.6 %
Recyclability Rate	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
End of Life Instructions	9AKK108468A2353

Group Waste to Landfill Target	UL 2799 Zero Waste To Landfill Validation available
Toxic Substances Control Act - TSCA	9AKK108467A8326

Eco Transparency

Environmental Product Declaration - EPD	9AKK108468A1893
---	-----------------

Environmental

Environmental Information	9AKK108467A6707
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
SCIP	4c2dd61c-ac10-449e-9067-acf16d93a8f7 Italy (IT)
Simplified SCIP	e9b92849-9172-4e41-833e-7408e91a2de2 Germany (DE) 67ea3c94-6b56-4fb2-b208-b05fcc99965 Netherlands (NL) 17ac093f-61a9-453f-b59d-8da7853e3a8c Estonia (EE) debf5bbb-5b2b-4c0b-8e80-e4dd8d789024 Greece (GR) 0422dee0-5e19-4b04-890e-c070738c5449 Portugal (PT) f21d3c00-01e7-4d78-a927-f4b4d14db02a Bulgaria (BG) 74c822c9-fbd2-436f-839f-931a9dd3fe2e Sweden (SE) c89109be-cb6d-4992-8b5d-de1583ce45df Poland (PL) c0619f4f-d7a1-4b2d-a969-0399c22142af France (FR) b7ff3f79-4571-457c-92ae-cf30f846df97 Sweden (SE) 1bef87ab-65e4-4e4f-8269-3e4b206ed2a7 Germany (DE) bffa2f51-0ae1-4cb7-85ec-7e0622e49f04 Germany (DE) 0f95ee41-5693-47f1-a49b-fc302e3afbcd France (FR) e4200aea-388f-42bd-888e-3ce2a5eca42e Netherlands (NL) e53b3c63-d3e5-4808-ab9c-deddf7a7360f Spain (ES) c085a2e4-c749-487e-bdba-83b4a7b1f7f4 Netherlands (NL) ef303154-eedc-4b60-9638-f09f6b3e2a2c Poland (PL) 22d1d0e4-3b23-4809-9c56-1b8fcb1c7864 Norway (NO) b2213076-4d3b-499a-b09a-19097178a025 Finland (FI) 3f414246-d973-488d-80bb-74925972554b Netherlands (NL) b0d518d8-6b84-4bbb-9a3d-defb07a88fe5 Germany (DE) 14fd1493-f953-46f5-9bce-78215f746f3c Denmark (DK) b95042db-5878-4ecf-8258-cc3ded35eea1 Germany (DE) 96453867-c5ab-4c5f-93cd-d405e210390b Croatia (HR) b9c56d1d-96bb-4a4c-9759-0954611f4afd Czech Republic (CZ) ffd81b7a-316e-4a28-93a3-11210df4da6e Poland (PL) 4275a62e-e774-43f4-8efc-41626e5ac70e Netherlands (NL)

Ordering

EAN	8056221023825
Minimum Order Quantity	1 piece
Customs Tariff Number	85389099

Dimensions

Product Net Width	186 mm
Product Net Height	205 mm
Product Net Depth / Length	103.5 mm
Product Net Weight	4.15 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	248 mm

Package Level 1 Height	240 mm
Package Level 1 Depth / Length	285 mm
Package Level 1 Gross Weight	4.5 kg
Package Level 1 EAN	8056221023825

Additional Information

Mechanical Durability	240 cycles per hour 20000 cycle
Number of Poles	4
Order Multiple	1 piece
Product Main Type	SACE Tmax XT
Product Name	Moulded Case Circuit Breaker
Product Type	Breaking Part
Rated Operational Voltage	600 V AC 600 V DC
Rated Uninterrupted Current (I _u)	400 A
Short-Circuit Performance Level	N
Standards	UL489
Sub-type	XT5
Suitable for Product Class	SACE Tmax XT
Terminal Connection Type	Front
Version	F

Technical UL/CSA

Interrupting Rating acc. to UL489	(240 V AC) 65 kA (480 V AC) 35 kA (600 V AC) 18 kA (250 V DC) 2 Poles in Series 35 kA (500 V DC) 2 Poles in Series 25 kA (600 V DC) 3 Poles in Series 16 kA
-----------------------------------	--

Certificates and Declarations

Data Sheet, Technical Information	1SDC210200D0206 1SDC210199D0206
Declaration of Conformity - CE	9AKK107680A2824
Instructions and Manuals	1SDH002011A1002

Classifications

ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax XT

