




PRODUCT-DETAILS

XT5S 400 BREAKING PART 4p F F UL/CSA
XT5S 400 BREAKING PART 4p F F UL/CSA



General Information

Extended Product Type	XT5S 400 BREAKING PART 4p F F UL/CSA
Product ID	1SDA102693R1
EAN	8056221023849
Catalog Description	XT5S 400 BREAKING PART 4p F F UL/CSA
Long Description	BREAKING PART TMAX XT5S 400 UL/CSA FIXED FOUR-POLE WITH FRONT TERMINALS

ABB EcoSolutions

ABB EcoSolutions	Yes
------------------	-----

Circular Value

Circular Design Principles	Design for Closing Resource Loops - Standard EN45555 - 59.6 %
Recyclability Rate	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
End of Life Instructions	9AKK108468A2353

Group Waste to Landfill Target	UL 2799 Zero Waste To Landfill Validation available
Toxic Substances Control Act - TSCA	9AKK108467A8326

Eco Transparency

Environmental Product Declaration - EPD	9AKK108468A1893
---	-----------------

Environmental

Environmental Information	9AKK108467A6707
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
SCIP	ec6e3cc4-f7d4-475e-934a-e8310b922b58 Italy (IT)
Simplified SCIP	b5e04ec8-1fc5-4b34-ae2e-6c8036480206 Germany (DE) ce2a9dfe-61da-4f73-86fa-e8fdb280ede Poland (PL) 7dd9d463-f180-4277-b82a-0e8f53739742 Norway (NO) 59bf19bc-7cdb-485f-9bcd-abc35d66e1f4 Finland (FI) 623435e3-b367-408a-b7cf-726f95908632 Netherlands (NL) 83396eea-34f9-4a1d-b2ef-33a70a502b7c Germany (DE) dfb302d2-68b2-400a-9c99-fb073e183fe4 Denmark (DK) 652be731-1429-429d-bb98-7b285f4cc9c9 Germany (DE) 7f19b7d0-c634-465b-82c0-f8f4b4ac34c3 Croatia (HR) 6fd914ce-f0d5-4a07-ac33-1fd01f946a3b Czech Republic (CZ) 2486118c-d266-4e7a-9d5d-813ec37e03fc Poland (PL) e0c4346d-53d4-4efb-858f-12305755f576 Netherlands (NL) bb6ce2a4-c87c-40db-8c2a-60d049cc1024 Netherlands (NL) 62a08977-1dc6-4cb5-b264-31cb3c0d0640 Estonia (EE) 0819d9b9-3269-4371-b919-591e056c8e56 Greece (GR) ef2ce6e3-c542-4d62-8117-8263485e0ec9 Portugal (PT) a5666858-3cda-468f-9ffa-34c2e9718f45 Bulgaria (BG) da22bf38-9c85-491d-ad99-5928f4b1f40d Sweden (SE) 0ed3cc4d-daa1-4f5f-b11e-32326b3a44eb Poland (PL) 52150dd5-4f00-4bf8-b329-b74ef8e66f12 France (FR) 1a87f5bf-021e-4ef5-86ac-84ff4d6cb290 Sweden (SE) 75623c75-542d-4cb5-a8be-d0f92ac9ddfc Germany (DE) d87dd864-08a9-456c-bde9-3142da58aace Germany (DE) b1f56316-fbe9-460b-b735-9fbdefa6ce49 France (FR) 8034ba48-db21-44ba-8855-756ca2059470 Netherlands (NL) c1f41c8b-50d8-44b2-a6cb-dccf899e9d48 Spain (ES) 5c5b0f22-425a-496e-8302-f4cc783143dc Netherlands (NL)

Ordering

EAN	8056221023849
Minimum Order Quantity	1 piece
Customs Tariff Number	85389099

Dimensions

Product Net Width	186 mm
Product Net Height	205 mm
Product Net Depth / Length	103.5 mm
Product Net Weight	4.15 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	248 mm

Package Level 1 Height	240 mm
Package Level 1 Depth / Length	285 mm
Package Level 1 Gross Weight	4.5 kg
Package Level 1 EAN	8056221023849

Additional Information

Mechanical Durability	240 cycles per hour 20000 cycle
Number of Poles	4
Order Multiple	1 piece
Product Main Type	SACE Tmax XT
Product Name	Moulded Case Circuit Breaker
Product Type	Breaking Part
Rated Operational Voltage	600 V AC 600 V DC
Rated Uninterrupted Current (I _u)	400 A
Short-Circuit Performance Level	S
Standards	UL489
Sub-type	XT5
Suitable for Product Class	SACE Tmax XT
Terminal Connection Type	Front
Version	F

Technical UL/CSA

Interrupting Rating acc. to UL489	(240 V AC) 100 kA (480 V AC) 50 kA (600 V AC) 25 kA (250 V DC) 2 Poles in Series 50 kA (500 V DC) 2 Poles in Series 35 kA (600 V DC) 3 Poles in Series 25 kA
-----------------------------------	---

Certificates and Declarations

Data Sheet, Technical Information	1SDC210200D0206 1SDC210199D0206
Declaration of Conformity - CE	9AKK107680A2824
Instructions and Manuals	1SDH002011A1002

Classifications

ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax XT

