




PRODUCT-DETAILS

XT5S 600 BREAKING PART 4p F F UL/CSA
XT5S 600 BREAKING PART 4p F F UL/CSA



General Information	
Extended Product Type	XT5S 600 BREAKING PART 4p F F UL/CSA
Product ID	1SDA102694R1
EAN	8015644032050
Catalog Description	XT5S 600 BREAKING PART 4p F F UL/CSA
Long Description	BREAKING PART TMAX XT5S 600 UL/CSA FIXED FOUR-POLE WITH FRONT TERMINALS

ABB EcoSolutions	
ABB EcoSolutions	Yes

Circular Value	
Circular Design Principles Recyclability Rate	Design for Closing Resource Loops - Standard EN45555 - 59.6 %
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658

End of Life Instructions	9AKK108468A2353
Group Waste to Landfill Target	UL 2799 Zero Waste To Landfill Validation available
Toxic Substances Control Act - TSCA	9AKK108467A8326

Eco Transparency

Environmental Product Declaration - EPD	9AKK108468A1893
---	-----------------

Environmental

Environmental Information	9AKK108467A6707
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
SCIP	f18e38c8-c2a8-4efd-a952-839ae87f12d2 Italy (IT)
Simplified SCIP	f47fb634-c862-4e18-8ed0-d83f435b7b65 Germany (DE) b93a5aa9-644e-4bc6-80e3-616af6031b66 Spain (ES) 2304ecb4-cb1c-4f7c-914d-93c3e459efdc Netherlands (NL) f92ed5fe-29f6-4742-ac6e-7d3d2f21bcbe Poland (PL) bb4d2c93-9268-47bb-9d78-87c0f0748388 Norway (NO) ce4dc426-2f38-44d8-89ad-40d726b59436 Finland (FI) 402fd06e-2e73-40a3-844b-09e0febb4029 Netherlands (NL) 1b955a0c-4c28-42ef-8ad7-7bdce05a160e Germany (DE) bef740c1-8eef-446f-8ba8-03bd65e30920 Denmark (DK) d3958d5a-6fb8-492e-8a95-8d244ee595ae Germany (DE) 5259928a-fa53-4265-b811-761758174262 Croatia (HR) 50ca4ed7-61c9-4241-9e78-c1c63b90555b Czech Republic (CZ) 511d244a-6e9b-4e65-973e-7aa632583008 Poland (PL) d091679c-9eb3-4387-b0d2-bd31c20e2a2e Netherlands (NL) 72f503b6-bf5a-4ba0-a011-52523e8ed866 Netherlands (NL) d21e707a-e1c0-4827-85c0-773d2318836a Estonia (EE) a3767305-789a-46f7-b545-6acca5c5fe21 Greece (GR) 07f49afd-9473-462f-a693-fefdf2d07a3f Portugal (PT) 84bb16a4-0bd3-4d2f-b297-716dbd29730c Bulgaria (BG) b6d6176b-6d1d-4409-ae51-b1e2d12dde3f Sweden (SE) 2945f6c0-af30-4227-a59e-93d0dbfcdc0c Poland (PL) 66af39ec-67ae-499e-bb87-2d07931fb66a France (FR) 536092e7-6687-40d3-bb2d-6a9de8622ce3 Sweden (SE) 2e19ae4e-eec5-4379-bc1c-5815ba882f4b Germany (DE) e16dc0aa-d7b1-4780-b647-763a6443af74 Germany (DE) a0be3c0e-882c-4fbd-9907-571411ad2310 France (FR) 122b4dcb-040f-49b0-a403-e0620a09eac2 Netherlands (NL)

Ordering

EAN	8015644032050
Minimum Order Quantity	1 piece
Customs Tariff Number	85389099

Dimensions

Product Net Width	186 mm
Product Net Height	205 mm
Product Net Depth / Length	103.5 mm

Product Net Weight	4.15 kg
--------------------	---------

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	248 mm
Package Level 1 Height	240 mm
Package Level 1 Depth / Length	285 mm
Package Level 1 Gross Weight	4.5 kg
Package Level 1 EAN	8015644032050

Additional Information

Mechanical Durability	240 cycles per hour 20000 cycle
Number of Poles	4
Order Multiple	1 piece
Product Main Type	SACE Tmax XT
Product Name	Moulded Case Circuit Breaker
Product Type	Breaking Part
Rated Operational Voltage	600 V AC 600 V DC
Rated Uninterrupted Current (I _u)	600 A
Short-Circuit Performance Level	S
Standards	UL489
Sub-type	XT5
Suitable for Product Class	SACE Tmax XT
Terminal Connection Type	Front
Version	F

Technical UL/CSA

Interrupting Rating acc. to UL489	(240 V AC) 100 kA (480 V AC) 50 kA (600 V AC) 25 kA (250 V DC) 2 Poles in Series 50 kA (500 V DC) 2 Poles in Series 35 kA (600 V DC) 3 Poles in Series 25 kA
-----------------------------------	---

Certificates and Declarations

Data Sheet, Technical Information	1SDC210200D0206 1SDC210199D0206
Declaration of Conformity - CE	9AKK107680A2824
Instructions and Manuals	1SDH002011A1002

Classifications	
ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax XT

