




PRODUCT-DETAILS

XT6S 800 Ekip Dip LIG In800 3p FF UL/CSA  
XT6S 800 Ekip Dip LIG In800 3p FF UL/CSA



| General Information   |                                                                                                                       |
|-----------------------|-----------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | XT6S 800 Ekip Dip LIG In800 3p FF UL/CSA                                                                              |
| Product ID            | 1SDA102852R1                                                                                                          |
| EAN                   | 8015644033637                                                                                                         |
| Catalog Description   | XT6S 800 Ekip Dip LIG In800 3p FF UL/CSA                                                                              |
| Long Description      | C.BREAKER TMAX XT6S 800 UL/CSA FIXED THREE-POLE WITH FRONT TERMINALS AND SOLID-STATE RELEASE IN AC EKIP DIP LIG R 800 |

| ABB EcoSolutions |     |
|------------------|-----|
| ABB EcoSolutions | Yes |

| Circular Value                                |                                                             |
|-----------------------------------------------|-------------------------------------------------------------|
| Circular Design Principles Recyclability Rate | Design for Closing Resource Loops - Standard EN45555 - 60 % |
| Conflict Minerals Reporting Template          | 9AKK108467A5658                                             |

(CMRT)

|                                     |                                                     |
|-------------------------------------|-----------------------------------------------------|
| End of Life Instructions            | 9AKK108468A2356                                     |
| Group Waste to Landfill Target      | UL 2799 Zero Waste To Landfill Validation available |
| Toxic Substances Control Act - TSCA | 9AKK108467A8326                                     |

Eco Transparency

|                                         |                 |
|-----------------------------------------|-----------------|
| Environmental Product Declaration - EPD | 9AKK108468A2295 |
|-----------------------------------------|-----------------|

Environmental

|                           |                                                                        |
|---------------------------|------------------------------------------------------------------------|
| Environmental Information | 9AKK108467A6707                                                        |
| REACH Declaration         | 9AKK108466A1425                                                        |
| RoHS Information          | 9AKK108466A1424                                                        |
| RoHS Status               | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |

Ordering

|                          |                    |
|--------------------------|--------------------|
| Order Code US and Canada | XT6SU3800CFF000XXX |
| EAN                      | 8015644033637      |
| Minimum Order Quantity   | 1 piece            |
| Customs Tariff Number    | 85362090           |

Dimensions

|                            |          |
|----------------------------|----------|
| Product Net Width          | 210 mm   |
| Product Net Height         | 268 mm   |
| Product Net Depth / Length | 103.5 mm |
| Product Net Weight         | 9.652 kg |

Container Information

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Units          | box 1 piece   |
| Package Level 1 Width          | 305 mm        |
| Package Level 1 Height         | 285 mm        |
| Package Level 1 Depth / Length | 370 mm        |
| Package Level 1 Gross Weight   | 10.16 kg      |
| Package Level 1 EAN            | 8015644033637 |

Additional Information

|                                       |                     |
|---------------------------------------|---------------------|
| Circuit Breaker Type to be Associated | Power Distribution  |
| Current Type                          | AC                  |
| Mechanical Durability                 | 240 cycles per hour |

|                                                                   |                                                                                                                                                                                                                                                                                                    |
|-------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                                                   | 20000 cycle                                                                                                                                                                                                                                                                                        |
| Number of Poles                                                   | 3                                                                                                                                                                                                                                                                                                  |
| Order Multiple                                                    | 1 piece                                                                                                                                                                                                                                                                                            |
| Power Loss                                                        | at Rated Operating Conditions per Pole 53 W                                                                                                                                                                                                                                                        |
| Product Main Type                                                 | SACE Tmax XT                                                                                                                                                                                                                                                                                       |
| Product Name                                                      | Moulded Case Circuit Breaker                                                                                                                                                                                                                                                                       |
| Product Type                                                      | Automatic Circuit Breaker                                                                                                                                                                                                                                                                          |
| Rated Current (I <sub>n</sub> )                                   | 800 A                                                                                                                                                                                                                                                                                              |
| Rated Operational Voltage                                         | 600 V AC                                                                                                                                                                                                                                                                                           |
| Rated Ultimate Short-Circuit Breaking Capacity (I <sub>cu</sub> ) | (220 V AC) 85 kA<br>(230 V AC) 85 kA<br>(240 V AC) 85 kA<br>(380 V AC) 50 kA<br>(415 V AC) 50 kA<br>(440 V AC) 45 kA<br>(500 V AC) 35 kA<br>(525 V AC) 35 kA<br>(690 V AC) 22 kA<br>(250 V DC) 2 Poles in Series 50 kA<br>(500 V DC) 2 Poles in Series 35 kA<br>(750 V DC) 3 Poles in Series 24 kA |
| Rated Uninterrupted Current (I <sub>u</sub> )                     | 800 A                                                                                                                                                                                                                                                                                              |
| Release                                                           | Ekip Dip LIG                                                                                                                                                                                                                                                                                       |
| Release Type                                                      | EL                                                                                                                                                                                                                                                                                                 |
| Short-Circuit Performance Level                                   | S                                                                                                                                                                                                                                                                                                  |
| Standards                                                         | UL489                                                                                                                                                                                                                                                                                              |
| Sub-type                                                          | XT6                                                                                                                                                                                                                                                                                                |
| Suitable for Product Class                                        | SACE Tmax XT                                                                                                                                                                                                                                                                                       |
| Terminal Connection Type                                          | Front                                                                                                                                                                                                                                                                                              |
| Version                                                           | F                                                                                                                                                                                                                                                                                                  |
| CAD Dimensional Drawing                                           | 1SDH002065A1190<br>1SDH002065A1245                                                                                                                                                                                                                                                                 |

## Technical UL/CSA

|                                   |                                                           |
|-----------------------------------|-----------------------------------------------------------|
| Interrupting Rating acc. to UL489 | (240 V AC) 100 kA<br>(480 V AC) 50 kA<br>(600 V AC) 25 kA |
|-----------------------------------|-----------------------------------------------------------|

## Certificates and Declarations

|                                   |                                    |
|-----------------------------------|------------------------------------|
| Data Sheet, Technical Information | 1SDC210200D0206<br>1SDC210199D0206 |
| Declaration of Conformity - CE    | 9AKK107680A2825                    |
| Mechanical Drawings               | 1SDH002012A1101                    |
| Wiring Diagram                    | 1SDM000005A1001                    |
| Instructions and Manuals          | 1SDH002012A1002                    |

## Classifications

|        |                                                                   |
|--------|-------------------------------------------------------------------|
| ETIM 7 | EC000228 - Power circuit-breaker for trafo/generator/installation |
|--------|-------------------------------------------------------------------|

|                                    |                                                                              |
|------------------------------------|------------------------------------------------------------------------------|
|                                    | protection                                                                   |
| ETIM 8                             | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| ETIM 9                             | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| IDEA Granular Category Code (IGCC) | 4932 >> 3 Pole Non-Interchangeable Trip Electronic Circuit Breakers          |
| UNSPSC                             | 39121616                                                                     |
| WEEE Category                      | 5. Small Equipment (No External Dimension More Than 50 cm)                   |
| eClass                             | V11.1 : 27370409                                                             |

## Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax XT

