




PRODUCT-DETAILS

XT7S 1200 Ekip Dip LSI In1200A 3p F F UL

XT7S 1200 Ekip Dip LSI In1200A 3p F F UL



General Information	
Extended Product Type	XT7S 1200 Ekip Dip LSI In1200A 3p F F UL
Product ID	1SDA102904R1
EAN	8056221025133
Catalog Description	XT7S 1200 Ekip Dip LSI In1200A 3p F F UL
Long Description	C.BREAKER TMAX T7S 1200 UL/CSA FIXED THREE-POLE WITH FRONT TERMINALS AND LEVER OPERATING MECHANISM AND SOLID-STATE RELEASE IN AC EKIP DIP LSI

ABB EcoSolutions	
ABB EcoSolutions	Yes

Circular Value	
Circular Design Principles Recyclability Rate	Design for Closing Resource Loops - Standard EN45555 - 64.1 %
Conflict Minerals Reporting Template	9AKK108467A5658

(CMRT)

End of Life Instructions	9AKK108468A2357
Group Waste to Landfill Target	UL 2799 Zero Waste To Landfill Validation available
Toxic Substances Control Act - TSCA	9AKK108467A8326

Eco Transparency

Environmental Product Declaration - EPD	9AKK108468A1895 9AKK108468A4404
---	------------------------------------

Environmental

Ambient Air Temperature	Operation -40 ... 125 °C
Environmental Information	9AKK108467A6707
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
SCIP	677a04ed-c39f-474d-bbea-8ef32ca75ed0 Italy (IT)
Simplified SCIP	0506832d-2137-40cf-a63c-56db19dd145c Germany (DE) 3fb9c5ea-5826-407d-bb98-41c2925a1b72 Bulgaria (BG) 970f5c87-899c-4c41-b6da-5180b4e3c611 Denmark (DK) 5767c2e7-7f8d-46bd-a974-7924ae8f8c8f Sweden (SE) da29f92f-941b-4077-a4db-6ee9bdfa893f Germany (DE) abfbb80b-478a-49d7-aecb-c2a4ee65b3bb Poland (PL) b68d2d12-49b2-4ccf-a33b-2977d2b19509 Poland (PL) 75271c86-04f5-467c-82c4-0696eab8a836 Norway (NO) 19534f80-a613-4d29-b47b-6469561be518 Finland (FI) 57f7bdc3-efea-42c9-a1c5-05ce5e03b534 Croatia (HR) 7cd966a9-04d0-437a-8da3-ee7a31f09acf Estonia (EE) 70c5802d-a5a5-439d-a6bb-0a73a3bd7758 Greece (GR) 7d4f4506-96bb-473a-9ab1-c23f27bc8db7 Hungary (HU) a0b3199e-4c51-463f-8ce5-6f306d9a1299 France (FR) 2c722641-5865-4a94-906b-61f1dce7a776 Germany (DE) b327c037-3f24-4869-9921-d90cd27a9d8a Sweden (SE) 156fc35e-dc4e-4f70-a5e8-77ce4d3b3fe0 Germany (DE) 9bcaa95f-28f2-4a47-8c50-94868bd8d6ed France (FR) 73cfc193-1198-42e2-b1e1-a5c868604368 Czech Republic (CZ) cc95bdd8-f1b6-45e5-b39c-47ced9afc82b Spain (ES) 92415b98-d192-49a2-b61a-faa165ed29b8 Belgium (BE) deb66d1d-e30f-42f7-85ab-b2b9942961cc Netherlands (NL) 386cbe96-bb89-410c-9f6b-5088c2f2dd49 Poland (PL) 63254ca2-1ea8-4c87-93ae-155bd4885ec2 Germany (DE) ce1302eb-bbbb-4335-86db-3694a3448603 Belgium (BE) 9484fb2f-6b74-45fc-895d-9033c96d593d Hungary (HU) dc27d073-7725-4244-a5dd-a8710927f89a Portugal (PT)

Ordering

Order Code US and Canada	XT7SU312EFFF000XXX
EAN	8056221025133
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	210 mm
Product Net Height	268 mm
Product Net Depth / Length	178 mm
Product Net Weight	9.7 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	280 mm
Package Level 1 Height	350 mm
Package Level 1 Depth / Length	360 mm
Package Level 1 Gross Weight	11.2 kg
Package Level 1 EAN	8056221025133

Additional Information

Circuit Breaker Type to be Associated	Power Distribution
Current Type	AC
Mechanical Durability	240 cycles per hour 10000 cycle
Number of Poles	3
Order Multiple	1 piece
Power Loss	at Rated Operating Conditions per Pole 53 W
Product Main Type	SACE Tmax XT
Product Name	Moulded Case Circuit Breaker
Product Type	Automatic Circuit Breaker
Rated Current (I _n)	1200 A
Rated Frequency (f)	50 / 60 Hz
Rated Operational Voltage	600 V AC
Rated Uninterrupted Current (I _u)	1200 A
Release	Ekip Dip LSI
Release Type	EL
Short-Circuit Performance Level	S
Standards	UL489
Sub-type	XT7
Suitable for Product Class	SACE Tmax XT
Terminal Connection Type	Front
Version	F
CAD Dimensional Drawing	1SDH002065A1336 1SDH002065A1338

Technical UL/CSA

Interrupting Rating acc. to UL489	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 25 kA
-----------------------------------	--

Certificates and Declarations	
Data Sheet, Technical Information	1SDC210200D0206 1SDC210199D0206
Declaration of Conformity - CE	9AKK107046A9648
Mechanical Drawings	1SDH002013A1101
Wiring Diagram	1SDM000002A1001
Instructions and Manuals	1SDH002013A1001 1SDH002013A1002

Classifications	
ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
IDEA Granular Category Code (IGCC)	4932 >> 3 Pole Non-Interchangeable Trip Electronic Circuit Breakers
UNSPSC	39121616
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax XT

