



PRODUCT-DETAILS

XT7L 1200 Ekip Dip LS/I In1200A 3p FF UL

XT7L 1200 Ekip Dip LS/I In1200A 3p FF UL



General Information	
Extended Product Type	XT7L 1200 Ekip Dip LS/I In1200A 3p FF UL
Product ID	1SDA102997R1
EAN	8015644035082
Catalog Description	XT7L 1200 Ekip Dip LS/I In1200A 3p FF UL
Long Description	C.BREAKER TMAX XT7L 1200 UL/CSA FIXED THREE-POLE WITH FRONT TERMINALS AND LEVER OPERATING MECHANISM AND SOLID-STATE RELEASE IN AC EKIP DIP LS/I R 1200

ABB EcoSolutions	
ABB EcoSolutions	Yes

Circular Value	
Circular Design	Design for Closing Resource Loops - Standard EN45555 - 64.1 %
Principles Recyclability Rate	
Conflict Minerals	9AKK108467A5658

Reporting Template (CMRT)	
End of Life Instructions	9AKK108468A2357
Group Waste to Landfill Target	UL 2799 Zero Waste To Landfill Validation available
Toxic Substances Control Act - TSCA	9AKK108467A8326

Eco Transparency

Environmental Product Declaration - EPD	9AKK108468A1895 9AKK108468A4404
---	------------------------------------

Environmental

Ambient Air Temperature	Operation -40 ... 125 °C
Environmental Information	9AKK108467A6707
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
SCIP	fa42e3bd-049e-4e86-8de5-6166d41ba648 Italy (IT)
Simplified SCIP	ee9736a9-41ff-4591-a72a-79384b259f96 Germany (DE) 46fd4bb8-9593-4678-a995-fadb5e15e682 Sweden (SE) 58de2124-08a9-499a-8042-b38a717944ec Germany (DE) baace838-4ba0-4d58-ba4d-4e5bbc0d8308 Germany (DE) 4234fd9a-bbff-4669-8863-41573f9e8a11 Poland (PL) c1ad5d65-dfb5-4f61-8a85-9766f1f83ab1 Greece (GR) 445c521f-8ef8-4145-b9a6-a3dd7b01cf71 Portugal (PT) 874fbf57-9f8d-4232-8241-84db75717b29 Bulgaria (BG) 0179c10f-79a9-4e4c-aa1c-d7397f160bb6 Sweden (SE) dc2bfef1-d2bf-45e7-8cc4-6b4321349dfd Poland (PL) 6b26b47d-af6c-4626-86f0-50277fb8ee86 France (FR) e6379527-6b00-4d29-9a38-9af106dcbd61 Norway (NO) 72451365-84ce-4e8a-91ed-393c0651ce3b Finland (FI) e1518e71-fc6c-4a45-80f9-bc930328313f Netherlands (NL) cca59fd1-2b42-4c77-9afb-94840166793b Germany (DE) 3dc538ba-36b0-45f3-b4f6-e23a7fd1cc20 Denmark (DK) 924a8813-6f1f-44df-b7b2-4182dcc89c70 Germany (DE) 47736fc5-35fe-4a1a-b258-dfda7c4477bd Croatia (HR) c5dcab10-c958-4649-ae9-072e576dc395 Czech Republic (CZ) d4c48d67-3c91-49c2-928c-e6d9bdc9efec Poland (PL) d956e470-3fde-4154-b03a-58f28acd879f Netherlands (NL) b7f2c629-6a9f-4a4c-81c4-b0d5e01f74fe Netherlands (NL) 17de0907-6900-4cf9-80ad-bf4e076ac9c1 Estonia (EE) 7d790d30-d86a-4b8e-93b9-8bc1ec253860 France (FR) 5a565bc1-bd13-4b8c-bbdf-4a455ce5539a Netherlands (NL) 6d1741c6-5450-41a1-b0d1-cca8457c2196 Spain (ES) 3766cbeb-93cf-4f1c-af9e-5837edfb550b Netherlands (NL)

Ordering

Order Code US and Canada	XT7LU312EEFF000XXX
EAN	8015644035082
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	210 mm
Product Net Height	268 mm
Product Net Depth / Length	178 mm
Product Net Weight	13.585 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	280 mm
Package Level 1 Height	350 mm
Package Level 1 Depth / Length	360 mm
Package Level 1 Gross Weight	14.3 kg
Package Level 1 EAN	8015644035082

Additional Information

Circuit Breaker Type to be Associated	Power Distribution
Current Type	AC
Mechanical Durability	240 cycles per hour 10000 cycle
Number of Poles	3
Order Multiple	1 piece
Power Loss	at Rated Operating Conditions per Pole 53 W
Product Main Type	SACE Tmax XT
Product Name	Moulded Case Circuit Breaker
Product Type	Automatic Circuit Breaker
Rated Current (I_n)	1200 A
Rated Frequency (f)	50 / 60 Hz
Rated Operational Voltage	600 V AC
Rated Uninterrupted Current (I_u)	1200 A
Release	Ekip Dip LS/I
Release Type	EL
Short-Circuit Performance Level	L
Standards	UL489
Sub-type	XT7
Suitable for Product Class	SACE Tmax XT
Terminal Connection Type	Front
Version	F
CAD Dimensional Drawing	1SDH002065A1336 1SDH002065A1338

Technical UL/CSA

Interrupting Rating acc. to UL489	(240 V AC) 200 kA (480 V AC) 100 kA
-----------------------------------	--

(600 V AC) 65 kA

Certificates and Declarations

Data Sheet, Technical Information	1SDC210200D0206 1SDC210199D0206
Declaration of Conformity - CE	9AKK107046A9648
Mechanical Drawings	1SDH002013A1101
Wiring Diagram	1SDM000002A1001
Instructions and Manuals	1SDH002013A1001 1SDH002013A1002

Classifications

ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
IDEA Granular Category Code (IGCC)	4932 >> 3 Pole Non-Interchangeable Trip Electronic Circuit Breakers
UNSPSC	39121616
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax XT

