




PRODUCT-DETAILS

XT7L 800 Ekip Touch LSIG In800A 3p FF UL

XT7L 800 Ekip Touch LSIG In800A 3p FF UL



General Information	
Extended Product Type	XT7L 800 Ekip Touch LSIG In800A 3p FF UL
Product ID	1SDA103007R1
EAN	8015644035181
Catalog Description	XT7L 800 Ekip Touch LSIG In800A 3p FF UL
Long Description	C.BREAKER TMAX XT7L 800 UL/CSA FIXED THREE-POLE WITH FRONT TERMINALS AND LEVER OPERATING MECHANISM AND SOLID-STATE RELEASE IN AC EKIP TOUCH LSIG R 800

ABB EcoSolutions	
ABB EcoSolutions	Yes

Circular Value	
Circular Design	Design for Closing Resource Loops - Standard EN45555 - 64.1 %
Principles Recyclability Rate	
Conflict Minerals	9AKK108467A5658

Reporting Template (CMRT)	
End of Life Instructions	9AKK108468A2357
Group Waste to Landfill Target	UL 2799 Zero Waste To Landfill Validation available
Toxic Substances Control Act - TSCA	9AKK108467A8326

Eco Transparency

Environmental Product Declaration - EPD	9AKK108468A1895 9AKK108468A4404
---	------------------------------------

Environmental

Ambient Air Temperature	Operation -40 ... 125 °C
Environmental Information	9AKK108467A6707
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
SCIP	27dff302-4244-477f-94d7-f6b446ec6273 Italy (IT)
Simplified SCIP	44ca8d08-0fd8-4964-8993-95c75610a5e4 Belgium (BE) 8a5e3405-52ce-42c0-bfc1-14f5e0e5ccab Finland (FI) 7848e0b3-922e-4d2c-a3f4-d39b03fbad13 Poland (PL) d2131e75-1cea-47d2-9bc5-d9eb686cb673 Norway (NO) fbce0969-8590-4068-b522-045be878c48b Germany (DE) e7134512-0644-4207-bad2-5e9e5e8a1950 Netherlands (NL) 190c9ed5-37a9-49a4-96ed-e25e0c6c1ebd Estonia (EE) 8214c7ba-4961-4588-8e04-38bec824cf93 Denmark (DK) f0231fbb-43de-48f9-9896-1a8b15e0412f Germany (DE) 9fca961e-6aac-47d8-9c95-746295052617 Croatia (HR) b43edf60-29a5-48c8-a605-ea55cf0fa818 Czech Republic (CZ) dd756bd1-4ad4-451c-b281-aed4b422adc8 Greece (GR) 6e3db844-d792-413c-af83-8d709982a5d2 Portugal (PT) d71c1d7c-4fa2-469c-86c1-bbdc8bfb9d83 Bulgaria (BG) 5f8eb44a-f992-432e-b7be-86ef36225631 Poland (PL) 1a0b8ca1-6bc6-49d4-a3ef-67be5583301e Hungary (HU) e8078c75-bad9-4b14-9548-e126608b3702 Spain (ES) 0cfaf94f-e6d9-43c9-ba80-818481c28628 France (FR) ee78e220-7c6f-4590-867f-02045cae47ef Belgium (BE) ef0d7f55-0212-43a6-9a54-9beb3ef82671 Poland (PL) fb306c5d-3f06-40ef-9e16-f2bec4f7cfe2 Hungary (HU) cbc49e1b-d5d9-4cdf-8461-8baa68b2f39e Sweden (SE) a4d78fd6-3260-4bf8-9703-4171312cb12b France (FR) bd1c30be-1a8b-46af-858d-addcb5df69e3 Sweden (SE) 2d72038d-833f-4d9a-a9e5-72e88b52d15e Germany (DE) 09f1c018-66d8-443a-87fc-bdea798caa44 Germany (DE) 8f9b7855-1aef-4e10-adca-234575c975d7 Germany (DE)

Ordering

Order Code US and Canada	XT7LU380CQFF000XXX
EAN	8015644035181
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	210 mm
Product Net Height	268 mm
Product Net Depth / Length	178 mm
Product Net Weight	9.7 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	280 mm
Package Level 1 Height	350 mm
Package Level 1 Depth / Length	360 mm
Package Level 1 Gross Weight	11.2 kg
Package Level 1 EAN	8015644035181

Additional Information

Circuit Breaker Type to be Associated	Power Distribution
Current Type	AC
Mechanical Durability	240 cycles per hour 10000 cycle
Number of Poles	3
Order Multiple	1 piece
Power Loss	at Rated Operating Conditions per Pole 24 W
Product Main Type	SACE Tmax XT
Product Name	Moulded Case Circuit Breaker
Product Type	Automatic Circuit Breaker
Rated Current (I_n)	800 A
Rated Frequency (f)	50 / 60 Hz
Rated Operational Voltage	600 V AC
Rated Uninterrupted Current (I_u)	800 A
Release	Ekip Touch LSIG
Release Type	EL
Short-Circuit Performance Level	L
Standards	UL489
Sub-type	XT7
Suitable for Product Class	SACE Tmax XT
Terminal Connection Type	Front
Version	F
CAD Dimensional Drawing	1SDH002065A1336 1SDH002065A1338

Technical UL/CSA

Interrupting Rating acc. to UL489	(240 V AC) 200 kA (480 V AC) 100 kA
-----------------------------------	--

(600 V AC) 65 kA

Certificates and Declarations

Data Sheet, Technical Information	1SDC210200D0206 1SDC210199D0206
Declaration of Conformity - CE	9AKK107046A9648
Mechanical Drawings	1SDH002013A1101
Wiring Diagram	1SDM000002A1001
Instructions and Manuals	1SDH002013A1001 1SDH002013A1002 1SDH001821A1002

Classifications

ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
IDEA Granular Category Code (IGCC)	4932 >> 3 Pole Non-Interchangeable Trip Electronic Circuit Breakers
UNSPSC	39121616
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax XT

