



PRODUCT-DETAILS

XT7H 1000 EkipGHi-TouchLSIG 1000 4pFF UL

XT7H 1000 EkipGHi-TouchLSIG 1000 4pFF UL



General Information	
Extended Product Type	XT7H 1000 EkipGHi-TouchLSIG 1000 4pFF UL
Product ID	1SDA103215R1
EAN	8015644037260
Catalog Description	XT7H 1000 EkipGHi-TouchLSIG 1000 4pFF UL
Long Description	C.BREAKER TMAX XT7H 1000 UL/CSA FIXED FOUR-POLE WITH FRONT TERMINALS AND LEVER OPERATING MECHANISM AND SOLID-STATE RELEASE IN AC EKIP G HI-TOUCH LSIG R 1000

ABB EcoSolutions	
ABB EcoSolutions	Yes

Circular Value	
Circular Design	Design for Closing Resource Loops - Standard EN45555 - 64.1 %
Principles Recyclability Rate	
Conflict Minerals	9AKK108467A5658

Reporting Template (CMRT)		
End of Life Instructions		9AKK108468A2357
Group Waste to Landfill Target	UL 2799 Zero Waste To Landfill Validation available	
Toxic Substances Control Act - TSCA		9AKK108467A8326

Eco Transparency

Environmental Product Declaration - EPD	9AKK108468A1895
	9AKK108468A4404

Environmental

Ambient Air Temperature	Operation -40 ... 125 °C
Environmental Information	9AKK108467A6707
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

Order Code US and Canada	XT7HU410DZFF000XXX
EAN	8015644037260
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	280 mm
Product Net Height	268 mm
Product Net Depth / Length	178 mm
Product Net Weight	12.5 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	360 mm
Package Level 1 Height	350 mm
Package Level 1 Depth / Length	360 mm
Package Level 1 Gross Weight	14 kg
Package Level 1 EAN	8015644037260

Additional Information

Circuit Breaker Type to	Generator Protection
-------------------------	----------------------

be Associated		
Current Type	AC	
Mechanical Durability	240 cycles per hour 10000 cycle	
Number of Poles	4	
Order Multiple	1 piece	
Power Loss	at Rated Operating Conditions per Pole 37 W	
Product Main Type	SACE Tmax XT	
Product Name	Moulded Case Circuit Breaker	
Product Type	Automatic Circuit Breaker	
Rated Current (I _N)	1000 A	
Rated Frequency (f)	50 / 60 Hz	
Rated Operational Voltage	600 V AC	
Rated Uninterrupted Current (I _u)	1000 A	
Release	Ekip G Hi-Touch LSIG	
Release Type	EL	
Short-Circuit Performance Level	H	
Standards	UL489	
Sub-type	XT7	
Suitable for Product Class	SACE Tmax XT	
Terminal Connection Type	Front	
Version	F	
CAD Dimensional Drawing	1SDH002065A1390 1SDH002065A1338	

Technical UL/CSA

Interrupting Rating acc. to UL489	(240 V AC) 100 kA (480 V AC) 65 kA (600 V AC) 50 kA
-----------------------------------	---

Certificates and Declarations

Data Sheet, Technical Information	1SDC210200D0206 1SDC210199D0206
Declaration of Conformity - CE	9AKK107046A9648
Mechanical Drawings	1SDH002013A1101
Wiring Diagram	1SDM000002A1001
Instructions and Manuals	1SDH002013A1001 1SDH002013A1002 1SDH001821A1002

Classifications

ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection

IDEA Granular Category Code (IGCC)	4934 >> 4 Pole Non-Interchangeable Trip Electronic Circuit Breakers
UNSPSC	39121616
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax XT

