



PRODUCT-DETAILS

XT7H M 1200 Ekip Touch Meas.LSI 3p FF UL

XT7H M 1200 Ekip Touch Meas.LSI 3p FF UL



| General Information   |                                                                                                                                                                           |
|-----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | XT7H M 1200 Ekip Touch Meas.LSI 3p FF UL                                                                                                                                  |
| Product ID            | 1SDA103411R1                                                                                                                                                              |
| EAN                   | 8015644039226                                                                                                                                                             |
| Catalog Description   | XT7H M 1200 Ekip Touch Meas.LSI 3p FF UL                                                                                                                                  |
| Long Description      | C.BREAKER TMAX XT7H 1200 UL/CSA FIXED THREE-POLE WITH FRONT TERMINALS AND STORED ENERGY OPERATING MECHANISM AND SOLID-STATE RELEASE IN AC EKIP TOUCH MEASURING LSI R 1200 |

| ABB EcoSolutions |     |
|------------------|-----|
| ABB EcoSolutions | Yes |

| Circular Value                |                                                               |
|-------------------------------|---------------------------------------------------------------|
| Circular Design               | Design for Closing Resource Loops - Standard EN45555 - 64.1 % |
| Principles Recyclability Rate |                                                               |
| Conflict Minerals             | 9AKK108467A5658                                               |

|                                     |                                                     |                 |
|-------------------------------------|-----------------------------------------------------|-----------------|
| Reporting Template (CMRT)           |                                                     |                 |
| End of Life Instructions            |                                                     | 9AKK108468A2358 |
| Group Waste to Landfill Target      | UL 2799 Zero Waste To Landfill Validation available |                 |
| Toxic Substances Control Act - TSCA |                                                     | 9AKK108467A8326 |

Eco Transparency

|                                         |                 |
|-----------------------------------------|-----------------|
| Environmental Product Declaration - EPD | 9AKK108468A1896 |
|                                         | 9AKK108468A4411 |

Environmental

|                           |                                                                        |
|---------------------------|------------------------------------------------------------------------|
| Ambient Air Temperature   | Operation -40 ... 125 °C                                               |
| Environmental Information | 9AKK108467A6707                                                        |
| REACH Declaration         | 9AKK108466A1425                                                        |
| RoHS Information          | 9AKK108466A1424                                                        |
| RoHS Status               | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |

Ordering

|                          |                   |
|--------------------------|-------------------|
| Order Code US and Canada | XHUGGFAZZAAA00000 |
| EAN                      | 8015644039226     |
| Minimum Order Quantity   | 1 piece           |
| Customs Tariff Number    | 85362090          |

Dimensions

|                            |        |
|----------------------------|--------|
| Product Net Width          | 210 mm |
| Product Net Height         | 268 mm |
| Product Net Depth / Length | 178 mm |
| Product Net Weight         | 11 kg  |

Container Information

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Units          | box 1 piece   |
| Package Level 1 Width          | 280 mm        |
| Package Level 1 Height         | 350 mm        |
| Package Level 1 Depth / Length | 360 mm        |
| Package Level 1 Gross Weight   | 12.5 kg       |
| Package Level 1 EAN            | 8015644039226 |

Additional Information

|                         |                    |
|-------------------------|--------------------|
| Circuit Breaker Type to | Power Distribution |
|-------------------------|--------------------|

|                                               |                                             |                 |
|-----------------------------------------------|---------------------------------------------|-----------------|
| be Associated                                 |                                             |                 |
| Current Type                                  |                                             | AC              |
| Mechanical Durability                         | 240 cycles per hour<br>10000 cycle          |                 |
| Number of Poles                               |                                             | 3               |
| Order Multiple                                |                                             | 1 piece         |
| Power Loss                                    | at Rated Operating Conditions per Pole 53 W |                 |
| Product Main Type                             |                                             | SACE Tmax XT    |
| Product Name                                  | Moulded Case Circuit Breaker                |                 |
| Product Type                                  | Automatic Circuit Breaker                   |                 |
| Rated Current (I <sub>n</sub> )               |                                             | 1200 A          |
| Rated Frequency (f)                           |                                             | 50 / 60 Hz      |
| Rated Operational Voltage                     |                                             | 600 V AC        |
| Rated Uninterrupted Current (I <sub>u</sub> ) |                                             | 1200 A          |
| Release                                       | Ekip Touch Measuring LSI                    |                 |
| Release Type                                  |                                             | EL              |
| Short-Circuit Performance Level               |                                             | H               |
| Standards                                     |                                             | UL489           |
| Sub-type                                      |                                             | XT7M            |
| Suitable for Product Class                    |                                             | SACE Tmax XT    |
| Terminal Connection Type                      |                                             | Front           |
| Version                                       |                                             | F               |
| CAD Dimensional Drawing                       |                                             | 1SDH002065A1337 |

Technical UL/CSA

|                                   |                                                           |
|-----------------------------------|-----------------------------------------------------------|
| Interrupting Rating acc. to UL489 | (240 V AC) 100 kA<br>(480 V AC) 65 kA<br>(600 V AC) 50 kA |
|-----------------------------------|-----------------------------------------------------------|

Certificates and Declarations

|                                   |                                                       |
|-----------------------------------|-------------------------------------------------------|
| Data Sheet, Technical Information | 1SDC210200D0206<br>1SDC210199D0206                    |
| Declaration of Conformity - CE    | 9AKK107046A9648                                       |
| Mechanical Drawings               | 1SDH002013A1102                                       |
| Wiring Diagram                    | 1SDM000002A1001                                       |
| Instructions and Manuals          | 1SDH002013A1001<br>1SDH002013A1002<br>1SDH001821A1002 |

Classifications

|        |                                                                              |
|--------|------------------------------------------------------------------------------|
| ETIM 7 | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| ETIM 8 | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| ETIM 9 | EC000228 - Power circuit-breaker for trafo/generator/installation protection |

|                                    |                                                                     |
|------------------------------------|---------------------------------------------------------------------|
| IDEA Granular Category Code (IGCC) | 4932 >> 3 Pole Non-Interchangeable Trip Electronic Circuit Breakers |
| UNSPSC                             | 39121616                                                            |
| WEEE Category                      | 5. Small Equipment (No External Dimension More Than 50 cm)          |
| eClass                             | V11.1 : 27370409                                                    |

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax XT

