



PRODUCT-DETAILS

XT7L M 800 Ekip Dip LS/I In800A 3p FF UL

XT7L M 800 Ekip Dip LS/I In800A 3p FF UL



General Information	
Extended Product Type	XT7L M 800 Ekip Dip LS/I In800A 3p FF UL
Product ID	1SDA103439R1
EAN	8015644039509
Catalog Description	XT7L M 800 Ekip Dip LS/I In800A 3p FF UL
Long Description	C.BREAKER TMAX XT7L 800 UL/CSA FIXED THREE-POLE WITH FRONT TERMINALS AND STORED ENERGY OPERATING MECHANISM AND SOLID-STATE RELEASE IN AC EKIP DIP LS/I R 800

ABB EcoSolutions	
ABB EcoSolutions	Yes

Circular Value	
Circular Design Principles	Design for Closing Resource Loops - Standard EN45555 - 64.1 %
Recyclability Rate	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658

End of Life Instructions	9AKK108468A2358
Group Waste to Landfill Target	UL 2799 Zero Waste To Landfill Validation available
Toxic Substances Control Act - TSCA	9AKK108467A8326

Eco Transparency

Environmental Product Declaration - EPD	9AKK108468A1896 9AKK108468A4411
---	------------------------------------

Environmental

Ambient Air Temperature	Operation -40 ... 125 °C
Environmental Information	9AKK108467A6707
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

Order Code US and Canada	XLUCAFAZZAAAA00000
EAN	8015644039509
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	210 mm
Product Net Height	268 mm
Product Net Depth / Length	178 mm
Product Net Weight	11 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	280 mm
Package Level 1 Height	350 mm
Package Level 1 Depth / Length	360 mm
Package Level 1 Gross Weight	12.5 kg
Package Level 1 EAN	8015644039509

Additional Information

Circuit Breaker Type to be Associated	Power Distribution
Current Type	AC
Mechanical Durability	240 cycles per hour 10000 cycle
Number of Poles	3
Order Multiple	1 piece
Power Loss	at Rated Operating Conditions per Pole 24 W

Product Main Type	SACE Tmax XT
Product Name	Moulded Case Circuit Breaker
Product Type	Automatic Circuit Breaker
Rated Current (I _n)	800 A
Rated Frequency (f)	50 / 60 Hz
Rated Operational Voltage	600 V AC
Rated Uninterrupted Current (I _u)	800 A
Release	Ekip Dip LS/I
Release Type	EL
Short-Circuit Performance Level	L
Standards	UL489
Sub-type	XT7M
Suitable for Product Class	SACE Tmax XT
Terminal Connection Type	Front
Version	F
CAD Dimensional Drawing	1SDH002065A1337

Technical UL/CSA

Interrupting Rating acc. to UL489	(240 V AC) 200 kA (480 V AC) 100 kA (600 V AC) 65 kA
-----------------------------------	--

Certificates and Declarations

Data Sheet, Technical Information	1SDC210200D0206 1SDC210199D0206
Declaration of Conformity - CE	9AKK107046A9648
Mechanical Drawings	1SDH002013A1102
Wiring Diagram	1SDM000002A1001
Instructions and Manuals	1SDH002013A1001 1SDH002013A1002

Classifications

ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
IDEA Granular Category Code (IGCC)	4932 >> 3 Pole Non-Interchangeable Trip Electronic Circuit Breakers
UNSPSC	39121616
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax XT

