



PRODUCT-DETAILS

E1.2N/E9 1250 Ekip Dip LSIG 3p F F

E1.2N/E9 1250 Ekip Dip LSIG 3p F F



General Information	
Extended Product Type	E1.2N/E9 1250 Ekip Dip LSIG 3p F F
Product ID	1SDA104275R1
EAN	8015644063559
Catalog Description	E1.2N/E9 1250 Ekip Dip LSIG 3p F F
Long Description	C.BREAKER SACE EMAX2 E1.2N 1250 FIXED THREE-POLE WITH FRONT TERMINALS AND SOLID-STATE RELEASE IN AC EKIP/DIP-LSIG R 1250 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED 800V
Circular Value	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Toxic Substances Control Act - TSCA	9AKK108467A8326
Environmental	
Environmental Information	9AKK108467A6707
REACH Declaration	9AKK108466A1425

© 2024 ABB. All rights reserved.

2024/04/12

Subject to change without notice

RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
SCIP	83685ed3-99ff-4187-a5f5-83f317d6c594 Italy (IT)
Simplified SCIP	ed177e80-776a-4839-85e1-6c6627f9e8d7 Hungary (HU) 7859de3f-f820-4110-bdca-bc96d860aff0 Belgium (BE) ddb1b750-2268-4277-be60-75c1ccc8f111 Finland (FI) 109252f2-7a6e-46ba-81a6-b6798d7ea88d Poland (PL) 0d19f791-7f93-4f53-861d-7eaf1f648d7e Sweden (SE) 9adc37b3-86b4-41e7-9621-f9b51c0a42d0 Portugal (PT) dfd0cd1b-4c6e-4ac3-a5c9-c65d47e463d7 Poland (PL) 32d5434c-8046-4cc0-a7d7-11e7c9902b86 Czech Republic (CZ) da89175c-3586-4828-a12c-cf1a5336dd70 Germany (DE) 8427dbb2-78c1-47de-9c7e-0b5214a22575 Denmark (DK) 3cd84c8c-29d8-4270-ac6e-5cc89c5e450d Estonia (EE) 44afcb7f-fa10-4c0a-9f8d-98bfc26fa5a2 Norway (NO) dc911411-141e-43d0-984d-a44ad60b7b73 Bulgaria (BG) 6b449a80-bb6b-44a9-8405-061d7d5a80aa Netherlands (NL) de0a564c-66a9-4e6d-8cea-a44aad073f67 Greece (GR) e99544e7-d310-4e0e-ad0d-ece7ab0ffd27 Germany (DE) 919ede50-9947-435a-9d8f-1ad63d9eafdc Sweden (SE) 259f23b0-8f5a-47b8-8d94-6bb76bd2464b Germany (DE) 9a42fedd-7107-48bf-b719-c383a7521214 Hungary (HU) 9fb75734-9bf8-4ff1-a6e2-a6018ecae525 Belgium (BE) 40cb3bd0-1abf-41a4-b87e-aa84cb297d84 France (FR) 3c9ad633-faea-4905-b9bd-8a4da5537dd7 Spain (ES) 8ae84ed4-cc50-4853-a70a-c0f661a0de2a Poland (PL) 596b0806-2c93-4170-8b64-bc8515466326 Germany (DE) 4a930a55-4da8-46dd-a4f7-4a532b15dc52 Germany (DE) 4bff40d7-ddc5-4a5c-9ab7-a9b61289c3ef France (FR) afe9d0c4-c2c4-4b7c-a584-869a995e9f3d Croatia (HR)

Ordering

Order Code US and Canada	91NREHBC000A000000XX
EAN	8015644063559
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	210 mm
Product Net Height	296 mm
Product Net Depth / Length	183 mm
Product Net Weight	14 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	270 mm
Package Level 1 Height	350 mm
Package Level 1 Depth / Length	330 mm
Package Level 1 Gross Weight	20 kg
Package Level 1 EAN	8015644063559

Additional Information

Current Type	AC
Electrical Durability	Ue = 800 V 500 cycle 30 cycles per hour
Mechanical Durability	20000 cycle

	60 cycles per hour
Number of Poles	3
Power Loss	122 W
Product Main Type	SACE Emax 2
Product Name	Air Circuit Breaker
Product Type	Air Circuit Breaker
Rated Current (I _n)	1250 A
Rated Voltage (U _r)	800 V
Rated Impulse Withstand Voltage (U _{imp})	acc. to IEC 60947-2 12 kV
Rated Insulation Voltage (U _i)	AC 1000 V
Rated Operational Voltage	800 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(800 V AC) 35 kA
Rated Short-time Withstand Current Low Voltage (I _{cw})	for 1 s 35 kA for 3 s 30 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu})	(800 V AC) 35 kA
Rated Uninterrupted Current (I _u)	1250 A
Release	Ekip Dip LSIG
Release Type	EL
Remarks	E9
Short-Circuit Performance Level	N
Standards	IEC
Sub-type	E1.2
Terminal Connection Type	Rear flat Horizontal
Version	F

Certificates and Declarations

Data Sheet, Technical Information	1SDC200023D0209
Instructions and Manuals	1SDH000999R0002

Classifications

ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
Object Classification Code	Q
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax 2

