




---

 PRODUCT-DETAILS

## E2.2S/E9 1250 Ekip Touch LSI 3p FHR

### E2.2S/E9 1250 Ekip Touch LSI 3p FHR




---

**General Information**

Extended Product Type	E2.2S/E9 1250 Ekip Touch LSI 3p FHR
Product ID	1SDA104321R1
EAN	8015644064013
Catalog Description	E2.2S/E9 1250 Ekip Touch LSI 3p FHR
Long Description	C.BREAKER SACE EMAX2 E2.2S 1250 FIXED THREE-POLE WITH TERMINALS REAR HORIZONTAL AND SOLID-STATE RELEASE IN AC Ekip/TOUCH-LSI R 1250 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED 900V

---

**Circular Value**

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Toxic Substances Control Act - TSCA	9AKK108467A8326

---

**Environmental**

Environmental Information	9AKK108467A6707
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
SCIP	5db9272f-d385-4a4a-a0e6-73274e7613b2 Italy (IT)

## Ordering

Order Code US and Canada	92SREHBE000A000000XX
EAN	8015644064013
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

## Dimensions

Product Net Width	276 mm
Product Net Height	371 mm
Product Net Depth / Length	270 mm
Product Net Weight	41 kg

## Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	515 mm
Package Level 1 Height	610 mm
Package Level 1 Depth / Length	515 mm
Package Level 1 Gross Weight	53 kg
Package Level 1 EAN	8015644064013

## Additional Information

Current Type	AC
Electrical Durability	U <sub>e</sub> = 900 V 2000 cycle 30 cycles per hour
Mechanical Durability	25000 cycle 60 cycles per hour
Number of Poles	3
Power Loss	83 W
Product Main Type	SACE Emax 2
Product Name	Air Circuit Breaker
Product Type	Air Circuit Breaker
Rated Current (I <sub>n</sub> )	1250 A
Rated Voltage (U <sub>r</sub> )	900 V
Rated Impulse Withstand Voltage (U <sub>imp</sub> )	acc. to IEC 60947-2 12 kV
Rated Insulation Voltage (U <sub>i</sub> )	AC 1000 V
Rated Operational	900 V AC

**Voltage**

Rated Service Short-Circuit Breaking Capacity ( $I_{cs}$ )	(800 V AC) 50 kA (900 V AC) 50 kA
Rated Short-time Withstand Current Low Voltage ( $I_{cw}$ )	for 1 s 50 kA for 3 s 50 kA
Rated Ultimate Short-Circuit Breaking Capacity ( $I_{cu}$ )	(800 V AC) 50 kA (900 V AC) 50 kA
Rated Uninterrupted Current ( $I_u$ )	1250 A
Release	Ekip Touch LSI
Release Type	EL
Remarks	E9
Short-Circuit Performance Level	S
Standards	IEC
Sub-type	E2.2
Terminal Connection Type	Rear flat Horizontal
Version	F

**Certificates and Declarations**

Data Sheet, Technical Information	1SDC200023D0209
Declaration of Conformity - CE	9AKK107680A4888
Instructions and Manuals	1SDH001000R0002
Instructions and Manuals (Part 2)	1SDH001316R1002

**Classifications**

ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
Object Classification Code	Q
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

---

## Categories

---

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax 2

