



PRODUCT-DETAILS

E2.2H/E9 1250 Ekip Dip LSIG 3p FHR

E2.2H/E9 1250 Ekip Dip LSIG 3p FHR



General Information	
Extended Product Type	E2.2H/E9 1250 Ekip Dip LSIG 3p FHR
Product ID	1SDA104348R1
EAN	8015644064280
Catalog Description	E2.2H/E9 1250 Ekip Dip LSIG 3p FHR
Long Description	C.BREAKER SACE EMAX2 E2.2H 1250 FIXED THREE-POLE WITH TERMINALS REAR HORIZONTAL AND SOLID-STATE RELEASE IN AC EKIP/DIP-LSIG R 1250 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED 900V

Circular Value	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Toxic Substances Control Act - TSCA	9AKK108467A8326

Environmental

Environmental Information	9AKK108467A6707
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
SCIP	851d5ce5-a9eb-4fb0-ade0-ab68492b68a4 Italy (IT)
Simplified SCIP	3aec2553-09d2-44f5-8052-17f47f441fbd Germany (DE) 725c30f1-c8a0-4a60-b63c-1645e7dbe836 Sweden (SE) b285b98b-eb66-4b44-812d-cdce9d5cfc6a Bulgaria (BG) dc00234e-c8ee-49ad-bdf4-5293d4650d0a Hungary (HU) 747b8003-00f0-4f84-8ee0-8aaee66a3c4e Spain (ES) dc938a32-780b-4885-b812-512171ddf124 Belgium (BE) 7d7a1873-7e64-4d1a-a1a8-841338656e2e Poland (PL) 5945f9d8-e4f1-4c7c-a58c-d3182236277c Czech Republic (CZ) 89789e52-4057-4f7b-b8e9-d82d443757a4 Poland (PL) 3a17927b-b91b-4406-83ba-a0ccee9a89df Croatia (HR) 3ff34d00-aa0c-4b89-a31a-70a7d6568077 Netherlands (NL) 6245fcb6-9fd2-48dd-961c-cc0e84d1ffde Germany (DE) d3f55b36-41cb-4eba-83ec-d9a37ee2ef2b France (FR) 1a99a59a-f8a9-422e-8c59-dd800ddc08c0 Germany (DE) 953f8205-0edb-48a9-8447-7709677b204e Germany (DE) 3d74a1ee-b9a0-473d-8d37-a9f10095aec1 Denmark (DK) c1814a57-2a72-4b3a-b964-24603d480fc0 Germany (DE) 0b322ecd-dc19-4734-acd8-e52eb826c8be Hungary (HU) 39e1543a-71ba-4458-b8ee-9d2f343b9071 Poland (PL) e51ac7f5-e66f-465d-825a-5ff13e9b3535 Norway (NO) d0a3d530-f0cc-43e9-948f-6599a7a1c68a Finland (FI) a03a9c36-3838-420d-85ea-501ac492ebdc Estonia (EE) 085e0300-3def-4b3f-bc58-71c37eb90ec6 France (FR) 95a728a3-25c7-44da-8717-72f07202d200 Belgium (BE) 9744ade7-a71d-4964-b990-794407b6ccf6 Sweden (SE) 5a62d722-ec5e-4711-b784-9f8b708dd6e9 Greece (GR) 8094350a-c292-4c6d-87a2-b9af2f763b17 Portugal (PT)

Ordering

Order Code US and Canada	92HREHBC000A000000XX
EAN	8015644064280
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	276 mm
Product Net Height	371 mm
Product Net Depth / Length	270 mm
Product Net Weight	41 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	515 mm
Package Level 1 Height	610 mm
Package Level 1 Depth / Length	515 mm
Package Level 1 Gross Weight	53 kg
Package Level 1 EAN	8015644064280

Additional Information	
Current Type	AC
Electrical Durability	Ue = 900 V 2000 cycle 30 cycles per hour
Mechanical Durability	25000 cycle 60 cycles per hour
Number of Poles	3
Power Loss	83 W
Product Main Type	SACE Emax 2
Product Name	Air Circuit Breaker
Product Type	Air Circuit Breaker
Rated Current (I _n)	1250 A
Rated Voltage (U _r)	900 V
Rated Impulse Withstand Voltage (U _{imp})	acc. to IEC 60947-2 12 kV
Rated Insulation Voltage (U _i)	AC 1000 V
Rated Operational Voltage	900 V AC
Rated Service Short- Circuit Breaking Capacity (I _{cs})	(800 V AC) 65 kA (900 V AC) 65 kA
Rated Short-time Withstand Current Low Voltage (I _{cw})	for 1 s 65 kA for 3 s 65 kA
Rated Ultimate Short- Circuit Breaking Capacity (I _{cu})	(800 V AC) 65 kA (900 V AC) 65 kA
Rated Uninterrupted Current (I _u)	1250 A
Release	Ekip Dip LSIG
Release Type	EL
Remarks	E9
Short-Circuit Performance Level	H
Standards	IEC
Sub-type	E2.2
Terminal Connection Type	Rear flat Horizontal
Version	F

Certificates and Declarations	
Data Sheet, Technical Information	1SDC200023D0209
Declaration of Conformity - CE	9AKK107680A4888
Instructions and Manuals	1SDH001000R0002

Classifications	
ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection

ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
Object Classification Code	Q
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax 2

