



PRODUCT-DETAILS

E2.2S/E9 1250 Ekip Dip LSI 3p WMP 900V

E2.2S/E9 1250 Ekip Dip LSI 3p WMP 900V



General Information	
Extended Product Type	E2.2S/E9 1250 Ekip Dip LSI 3p WMP 900V
Product ID	1SDA104437R1
EAN	8056221026284
Catalog Description	E2.2S/E9 1250 Ekip Dip LSI 3p WMP 900V
Long Description	MOVING PART FOR C.BREAKER SACE EMAX2 E2.2S 1250 THREE-POLE WITH SOLID-STATE RELEASE IN AC Ekip/DIP-LSI R 1250 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED 900V

Circular Value	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Toxic Substances Control Act - TSCA	9AKK108467A8326

Environmental	
Environmental Information	9AKK108467A6707
REACH Declaration	9AKK108466A1425

RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
SCIP	91612d35-f6bb-4ab7-a0c0-1838d592dca0 Italy (IT)
Simplified SCIP	58ccc6eb-ba4e-4cf8-840b-59eb5402c86c Germany (DE) 33b538a4-b5fa-4269-844b-8b44ed468761 Germany (DE) b7a5b976-e457-48bb-a2a3-793782a78c52 Hungary (HU) 91c341c3-d5ec-46fd-ac1f-7ce5395e7150 France (FR) 2f57b36c-71ae-4d1c-812e-78b857f7406a Belgium (BE) f3cab02c-586a-496b-80b6-d8aac4b1e9a8 Sweden (SE) 31c35e12-67cb-4ee9-b7a2-a102b049e597 Poland (PL) 8646171f-ce0b-462c-bf3f-7c100f0453eb Portugal (PT) f753d192-9feb-421b-8f88-7ffb7846291a Bulgaria (BG) 5a90714b-df3d-4628-b896-068979abc240 Sweden (SE) 06ae3b52-070d-4451-884d-fd01d4d680b2 Hungary (HU) 767f649f-181f-48cb-86aa-0f5f6dbd1c91 Estonia (EE) 5b3036db-e274-43a5-9bf8-e78403767c71 Greece (GR) f5152dd8-cc05-4fd6-b6d2-fdc0ab7c9e91 Germany (DE) 4f6ac9ed-b995-4ac7-9cda-10a7d986670a Poland (PL) 9eeb92fe-9fe8-435d-b45e-1d4a44ce03ba Denmark (DK) 6681c902-151c-4efa-9ead-f83d67149073 Finland (FI) 91553d32-19ac-4025-bbd5-3ddab4d2926c Norway (NO) 21230d90-ae82-4205-8087-6ebb80a9ef3e France (FR) 1c7aba53-f96b-4016-89b6-767b2ff2cf50 Croatia (HR) abd23c38-ab32-410e-9057-2a1619c27f5b Spain (ES) 9709728d-a563-4bed-a1ec-1693d86f3475 Netherlands (NL) bc638d2f-531b-4aae-ac4c-5ca54228ebbc Belgium (BE) 6ce70c54-9233-4dee-b6fc-fc077b239f4d Germany (DE) 38c976f6-4934-4e7a-a073-7dae6b7a9288 Czech Republic (CZ) a1e8486e-9d26-498d-90f5-5e9acc8f672e Poland (PL) bba0d3d8-972d-4a96-ba0a-0e6eb1267de0 Germany (DE)

Ordering

Order Code US and Canada	92SREHAB000A000000XX
EAN	8056221026284
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	317 mm
Product Net Height	425 mm
Product Net Depth / Length	383 mm
Product Net Weight	48 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	515 mm
Package Level 1 Height	610 mm
Package Level 1 Depth / Length	515 mm
Package Level 1 Gross Weight	53 kg
Package Level 1 EAN	8015644065171

Additional Information

Current Type	AC
Electrical Durability	Ue = 900 V 2000 cycle 30 cycles per hour
Mechanical Durability	25000 cycle

	60 cycles per hour
Number of Poles	3
Power Loss	176 W
Product Main Type	SACE Emax 2
Product Name	Air Circuit Breaker
Product Type	Air Circuit Breaker
Rated Current (I _n)	1250 A
Rated Voltage (U _r)	900 V
Rated Impulse Withstand Voltage (U _{imp})	acc. to IEC 60947-2 12 kV
Rated Insulation Voltage (U _i)	AC 1000 V
Rated Operational Voltage	900 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(800 V AC) 50 kA (900 V AC) 50 kA
Rated Short-time Withstand Current Low Voltage (I _{cw})	for 1 s 50 kA for 3 s 50 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu})	(800 V AC) 50 kA (900 V AC) 50 kA
Rated Uninterrupted Current (I _u)	1250 A
Release	Ekip Dip LSI
Release Type	EL
Remarks	E9
Short-Circuit Performance Level	S
Standards	IEC
Sub-type	E2.2
Terminal Connection Type	Rear flat Horizontal
Version	W

Certificates and Declarations

Data Sheet, Technical Information	1SDC200023D0209
Declaration of Conformity - CE	9AKK107680A4888
Instructions and Manuals	1SDH001000R0002

Classifications

ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
Object Classification Code	Q
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax 2

