



 PRODUCT-DETAILS

T5X-HA400 PR222DS-LSIG In320 4p FF800VAC

T5X-HA400 PR222DS-LSIG In320 4p FF800VAC



General Information

Extended Product Type	T5X-HA400 PR222DS-LSIG In320 4p FF800VAC
Product ID	1SDA113737R1
EAN	8056221042703
Catalog Description	T5X-HA400 PR222DS-LSIG In320 4p FF800VAC
Long Description	C.BREAKER TMAX T5X-HA 400 800V FIXED FOUR-POLE WITH FRONT TERMINALS AND ELECTRONIC RELEASE IN AC PR222DS-LSIG R 320

Circular Value

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Toxic Substances Control Act - TSCA	9AKK108467A8326

Environmental

Environmental	9AKK10103A1056
---------------	----------------

Information	9AKK108467A6707
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8056221042703
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	186 mm
Product Net Height	205 mm
Product Net Depth / Length	103.5 mm
Product Net Weight	5.1 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	248 mm
Package Level 1 Height	240 mm
Package Level 1 Depth / Length	285 mm
Package Level 1 Gross Weight	5.1 kg
Package Level 1 EAN	8056221042703

Additional Information

Current Type	AC
Mechanical Durability	20000 cycle
Number of Poles	4
Power Loss	30 W
Product Main Type	SACE Tmax T
Product Name	Moulded case circuit breaker
Product Type	Automatic Circuit Breaker
Rated Current (I_n)	400 A
Rated Voltage (U_r)	800 V
Rated Impulse Withstand Voltage (U_{imp})	8 kV
Rated Insulation Voltage (U_i)	1000 V
Rated Operational Voltage	800 V
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu})	(800 V AC) 35 kA
Rated Uninterrupted Current (I_u)	400 A
Short-Circuit Performance Level	X

Standards	IEC
Sub-type	T5
Terminal Connection Type	Fixed Circuit-Breakers Front for Copper Cables
Version	F

Certificates and Declarations

Data Sheet, Technical Information	1SDC210300D0201
Declaration of Conformity - CE	9AKK1074920313
Instructions and Manuals	1SDH001608R0001

Classifications

ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax T

