



PRODUCT-DETAILS

T4V-HA250 PR222DS-LSIG In250 4p
FF800VAC

T4V-HA250 PR222DS-LSIG In250 4p FF800VAC



General Information	
Extended Product Type	T4V-HA250 PR222DS-LSIG In250 4p FF800VAC
Product ID	1SDA113740R1
EAN	8056221042734
Catalog Description	T4V-HA250 PR222DS-LSIG In250 4p FF800VAC
Long Description	C.BREAKER TMAX T4V-HA 250 800V FIXED FOUR-POLE WITH FRONT TERMINALS AND ELECTRONIC RELEASE IN AC PR222DS-LSIG R 250
Circular Value	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Toxic Substances Control Act - TSCA	9AKK108467A8326
Environmental	
Environmental	9AKK10103A1057

Information	9AKK108467A6707
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8056221042734
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Depth / Length	108.5 mm
----------------------------	----------

Container Information

Package Level 1 Width	248 mm
Package Level 1 Height	240 mm
Package Level 1 Depth / Length	285 mm
Package Level 1 Gross Weight	2.5 kg
Package Level 1 EAN	8056221042734

Additional Information

Current Type	AC
Electrical Durability	2000 cycle
Mechanical Durability	20000 cycle
Number of Poles	4
Power Loss	14 W
Product Main Type	SACE Tmax T
Product Name	Moulded case circuit breaker
Product Type	Switch Disconnecter
Rated Current (I_n)	250 A
Rated Voltage (U_r)	800 V
Rated Impulse Withstand Voltage (U_{imp})	8 kV
Rated Insulation Voltage (U_i)	1000 V
Rated Operational Voltage	800 V
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu})	(800 V AC) 25 kA
Rated Uninterrupted Current (I_u)	250 A
Short-Circuit Performance Level	V
Standards	IEC
Sub-type	T4

Terminal Connection Type	Fixed Circuit-Breakers Front for Copper Cables
Version	F

Certificates and Declarations

Data Sheet, Technical Information	1SDC210300D0201
Declaration of Conformity - CE	9AKK1074920315
Instructions and Manuals	1SDH001607R0001

Classifications

ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax T

