



PRODUCT-DETAILS

E2.2H/E10 2500 Ekip Dip LSIG 3p WMP

E2.2H/E10 2500 Ekip Dip LSIG 3p WMP



General Information	
Extended Product Type	E2.2H/E10 2500 Ekip Dip LSIG 3p WMP
Product ID	1SDA115928R1
EAN	8056221079983
Catalog Description	E2.2H/E10 2500 Ekip Dip LSIG 3p WMP
Long Description	MOVING PART FOR C.BREAKER 1000V SACE EMAX2 E2.2H/E10 2500 THREE-POLE WITH SOLID-STATE RELEASE IN AC EKIP/DIP-LSIG R 2500 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Toxic Substances Control Act - TSCA	9AKK108467A8326

Environmental

Environmental Information	9AKK108467A6707
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
SCIP	811967a9-381d-4885-98f1-4e94d4ba325a Italy (IT)
Simplified SCIP	198c0f79-4c6c-40a8-b412-932de6ffa0e1 Germany (DE) 5898d21a-6b14-48cc-9c2d-dc2ee43cd174 Germany (DE) a9c615fb-5363-4e06-9e1d-ead0770c6b27 Sweden (SE) f4c1ea69-3af3-4f7d-8272-dddfefb8fa1a9 Belgium (BE) e38a9c0e-2fce-4817-adcd-39eae192fc56 France (FR) 230aa365-08e3-4dcd-870e-f9e1b9c90291 Estonia (EE) 9d191510-7287-465f-9481-7139ca71f1d1 Finland (FI) cd02d5d6-495d-4093-8e70-4ec93ac3ff66 France (FR) ef78aa0c-26fe-4485-b829-729e7778189c Germany (DE) 2b38b113-e882-4819-a241-776a9b6501a2 Germany (DE) 38f41a45-d45c-46df-a0fb-461e0d0e9162 Spain (ES) df62a5f1-30f7-4335-8822-24865a8e3443 Belgium (BE) df74d554-efea-451f-96a0-f269df372f69 Sweden (SE) 7994c43c-50a9-4482-8190-887f531e70f8 Portugal (PT) e97ee1d3-45f2-4885-be0f-6fe2353e3dfb Bulgaria (BG) 4a447c84-f606-4f85-875c-ad8ebf33414b Greece (GR) 951aab7d-e788-41c5-8363-f52db8b2c3c8 Hungary (HU) 695dcff7-c7b1-4077-8f84-f900b33d6026 Czech Republic (CZ) 097b74ef-6e87-4ce2-a358-be3db2117bc1 Poland (PL) 2da28ea1-fff7-4b31-b45a-5439a78029de Netherlands (NL) 938819cf-516b-47d0-85a0-4c9a098cc6f2 Croatia (HR) 4ca3b89e-90ee-43f9-adad-0082a3a527a4 Poland (PL) 9893232d-aa4c-4808-a908-21a936dad1c2 Hungary (HU) 69b0b289-4b5e-4f95-946b-6d4c225ab0d8 Norway (NO) b4ea09ae-2adb-4f80-be1e-19f874f39c26 Poland (PL) 52aeb9c8-e6a1-4803-a980-7d434d89580a Denmark (DK) 9a0bd2a9-5f8e-4556-9b85-5690405c8f4f Germany (DE)

Ordering

EAN	8056221079983
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	317 mm
Product Net Height	425 mm
Product Net Depth / Length	383 mm
Product Net Weight	48 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	515 mm
Package Level 1 Height	610 mm
Package Level 1 Depth / Length	515 mm
Package Level 1 Gross Weight	53 kg
Package Level 1 EAN	8056221079983

Additional Information		
Current Type		AC
Electrical Durability	Ue = 1000 V AC 500 cycle 30 cycles per hour	
Mechanical Durability	20000 cycle 60 cycles per hour	
Number of Poles		3
Power Loss		550 W
Product Main Type		SACE Emax 2
Product Name		Air Circuit Breaker
Product Type		Air Circuit Breaker
Rated Current (I _n)		2500 A
Rated Voltage (U _r)		1000 V
Rated Insulation Voltage (U _i)		1000 V
Rated Operational Voltage		1000 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs})		1000 V AC 50 kA
Rated Short-time Withstand Current Low Voltage (I _{cw})		for 1 s 50 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu})		1000 V AC 50 kA
Release		Ekip Dip LSIG
Release Type		EL
Remarks		1000V
Short-Circuit Performance Level		N
Standards		IEC
Sub-type		E2.2
Version		W

Certificates and Declarations		
Data Sheet, Technical Information		1SDC200023D0209
Declaration of Conformity - CE		9AKK106713A5902
Instructions and Manuals		1SDH001000R0002

Classifications		
ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection	
ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection	
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection	
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)	
eClass		V11.1 : 27370409

Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax 2

