




---

 PRODUCT-DETAILS

# E4.2H/E9/LF MS 4000 3p WMP

## E4.2H/E9/LF MS 4000 3p WMP




---

**General Information**

Extended Product Type	E4.2H/E9/LF MS 4000 3p WMP
Product ID	1SDA119553R1
EAN	8056221140775
Catalog Description	E4.2H/E9/LF MS 4000 3p WMP
Long Description	C.BREAKER SWITCH-DISCONNECTOR SACE EMAX2 E4.2H/E9/LF MS 4000A THREE-POLE MOVING PART - VF

---

**Circular Value**

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Toxic Substances Control Act - TSCA	9AKK108467A8326

---

**Environmental**

Environmental	9AKK108467A6707
---------------	-----------------

## Information

REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

## Ordering

EAN	8056221140775
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

## Dimensions

Product Net Width	425 mm
Product Net Height	425 mm
Product Net Depth / Length	383 mm
Product Net Weight	60 kg

## Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	515 mm
Package Level 1 Height	600 mm
Package Level 1 Depth / Length	785 mm
Package Level 1 Gross Weight	95 kg
Package Level 1 EAN	8056221140775

## Additional Information

Current Type	AC
Electrical Durability	U <sub>e</sub> = 900 V 1000 cycle 10 cycles per hour
Mechanical Durability	15000 cycle 60 cycles per hour
Number of Poles	3
Power Loss	900 W
Product Main Type	SACE Emax 2
Product Name	Switch Disconnecter
Product Type	Switch Disconnecter
Rated Current (I <sub>n</sub> )	4000 A
Rated Voltage (U <sub>r</sub> )	900 V
Rated Impulse Withstand Voltage (U <sub>imp</sub> )	12 kV
Rated Insulation Voltage (U <sub>i</sub> )	1000 V
Rated Operational Voltage	900 V AC
Rated Short-time Withstand Current Low Voltage (I <sub>cw</sub> )	75 kA
Rated Uninterrupted	4000 A

Current (I <sub>u</sub> )	
Remarks	E9
Short-Circuit Performance Level	H
Standards	IEC
Sub-type	E4.2
Version	W

### Certificates and Declarations

Data Sheet, Technical Information	1SDC200023D0209
Declaration of Conformity - CE	9AKK107680A4889
Instructions and Manuals	1SDH001000R0002

### Classifications

ETIM 7	EC000216 - Switch disconnecter
ETIM 8	EC000216 - Switch disconnecter
ETIM 9	EC000216 - Switch disconnecter (low voltage)
Object Classification Code	Q
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

### Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax 2

