



PRODUCT-DETAILS

E4.2S/E10 4000 Ekip Dip LSIG 3p FHR
E4.2S/E10 4000 Ekip Dip LSIG 3p FHR



General Information	
Extended Product Type	E4.2S/E10 4000 Ekip Dip LSIG 3p FHR
Product ID	1SDA121094R1
EAN	8056221156868
Catalog Description	E4.2S/E10 4000 Ekip Dip LSIG 3p FHR
Long Description	CIRCUIT BREAKER SACE EMAX2 E4.2S/E10 4000 FIXED THREE-POLE 1000V WITH SOLID-STATE RELEASE IN AC EKIP/DIP-LSIG R 4000A FITTED WITH: 4 AUXILIARY CONTACTS AND REAR HORIZONTAL TERMINALS

Circular Value	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Toxic Substances Control Act - TSCA	9AKK108467A8326

Environmental

Environmental Information	1SDL000197R0003 9AKK108467A6707
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8056221156868
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	384 mm
Product Net Height	371 mm
Product Net Depth / Length	270 mm
Product Net Weight	56 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	515 mm
Package Level 1 Height	600 mm
Package Level 1 Depth / Length	785 mm
Package Level 1 Gross Weight	95 kg
Package Level 1 EAN	8056221156868

Additional Information

Current Type	AC
Electrical Durability	Ue = 1000 V 1000 cycle 10 cycles per hour
Mechanical Durability	15000 cycle 60 cycles per hour
Number of Poles	3
Power Loss	465 W
Product Main Type	SACE Emax 2
Product Name	Air Circuit Breaker
Product Type	Air Circuit Breaker
Rated Current (I _n)	4000 A
Rated Voltage (U _r)	1000 V
Rated Impulse Withstand Voltage (U _{imp})	15 kV
Rated Insulation Voltage (U _i)	1000 V
Rated Operational Voltage	1000 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(800 V AC) 50 kA (1000 V AC) 50 kA

Rated Short-time Withstand Current Low Voltage (I_{cw})	for 1 s 50 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu})	(800 V AC) 50 kA (1000 V AC) 50 kA
Rated Uninterrupted Current (I_u)	4000 A
Release	Ekip Dip LSIG
Release Type	EL
Remarks	E10
Short-Circuit Performance Level	S
Standards	IEC
Sub-type	E4.2
Terminal Connection Type	Rear flat Horizontal
Version	F

Certificates and Declarations

Data Sheet, Technical Information	1SDC200074B0201 1SDC200023D0209
Declaration of Conformity - CE	9AKK107680A4889
Instructions and Manuals	1SDH001000R0002

Classifications

ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
Object Classification Code	Q
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax 2

