XLP00-4P-8BC 1/3



PRODUCT-DETAILS

XLP00-4P-8BC

XLP00-4P-8BC Fuse Switch Disconnector



| General Information | | |
|-----------------------|--|--|
| Extended Product Type | XLP00-4P-8BC | |
| Product ID | 1SEP600115R0002 | |
| EAN | 7025840086550 | |
| Catalog Description | XLP00-4P-8BC Fuse Switch Disconnector | |
| Long Description | XLP00,4-pole,160A, incl. 8 Bridge Clamps | |

| Circular Value | | |
|---|-----------------|--|
| Conflict Minerals Reporting Template (CMRT) | 9AKK108467A5658 | |
| REACH Declaration | 1SCC011021D0201 | |
| RoHS Information | 1SCC011020D0201 | |

| Ordering | |
|------------------------|----------|
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85389099 |

XLP00-4P-8BC 2/3

Country of Origin China (CN)

| Popular Downloads | | |
|--------------------------------------|------------------------------------|--|
| Data Sheet, Technical Information | 1SEC312012D0201 | |
| Instructions and | No Instructions and Manuals needed | |

| Dimensions | |
|----------------------------|---------|
| Product Net Width | 145 mm |
| Product Net Height | 88 mm |
| Product Net Depth / Length | 185 mm |
| Product Net Weight | 0.99 kg |

| Technical | |
|--|---------------------------|
| Rated Operational Current AC-22B (I _e) | (500 V) 160 A |
| Rated Impulse Withstand Voltage (U _{imp}) | Main Circuit 8 kV |
| Rated Operational Voltage | 500 V AC |
| Rated Frequency (f) | Main Circuit 50/60 Hz |
| Rated Conditional Short- Circuit Current (I _{nc}) | (690 V) 50 kiloampere rms |
| Power Loss | at Rated Load 3.5 W |
| Handle Type | Front cover 4P |
| Fuse Size | NH00 NH000 |
| Fuse System | DIN |
| Standards | IEC60947-3 GB/T14048.3 |
| Special Functions | Not Included |
| Mounting Type | Baseplate |
| Number of Poles | 4 |
| Degree of Protection | IP30 |
| Terminal Type | Cable Clamp |
| Device Type Manager (DTM) | Fuseswitchdisconnector |
| Rated Current (In) | 160 A |
| Rated Voltage (U _r) | 500 V AC |
| Electronic Fuse Monitoring | No |

| Environmental | |
|---------------|--|
| RoHS Status | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |

| • | Cartif | icates | and | Decl | aratio | ne |
|---|--------|--------|-----|------|--------|----|
| ч | cerun | ICALES | and | 1100 | aranc | |

XLP00-4P-8BC 3/3

| Declaration of | 1SEP500050P0001 |
|-------------------|-----------------|
| Conformity - CE | |
| REACH Declaration | 1SCC011021D0201 |

| Container Information | | |
|-----------------------------------|---------------------|--|
| Package Level 1 Units | shrink-wrap 1 piece | |
| Package Level 1 Width | 145 mm | |
| Package Level 1 Depth / Length | 185 mm | |
| Package Level 1 Height | 88 mm | |
| Package Level 1 Gross Weight | 0.99 kg | |
| Package Level 1 EAN | 7025840086550 | |
| Package Level 2 EAN | 7025840086550 | |

| Classifications | |
|-------------------------------|--|
| Object Classification Code | S |
| ETIM 7 | EC001040 - Fuse switch disconnector |
| ETIM 8 | EC001040 - Fuse switch disconnector |
| ETIM 9 | EC001040 - Fuse switch disconnector |
| eClass | V11.1 : 27371401 |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |
| E-Number (Sweden) | 3171969 |

Categories

 $\textbf{Low Voltage Products and Systems} \rightarrow \textbf{Fusegear} \rightarrow \textbf{Fuse Switch Disconnectors} \rightarrow \textbf{EasyLine}$

