



PRODUCT-DETAILS

# XLP1-2P

## XLP1-2P Fuse Switch Disconnecter



| General Information   |                                           |
|-----------------------|-------------------------------------------|
| Extended Product Type | XLP1-2P                                   |
| Product ID            | 1SEP600117R0001                           |
| EAN                   | 7025840086604                             |
| Catalog Description   | XLP1-2P Fuse Switch Disconnecter          |
| Long Description      | XLP1.2-pole,250A, without clamps or bolts |

| Circular Value                              |                 |
|---------------------------------------------|-----------------|
| Conflict Minerals Reporting Template (CMRT) | 9AKK108467A5658 |
| REACH Declaration                           | 1SCC011021D0201 |
| RoHS Information                            | 1SCC011020D0201 |

| Ordering               |            |
|------------------------|------------|
| Minimum Order Quantity | 1 piece    |
| Customs Tariff Number  | 85389099   |
| Country of Origin      | China (CN) |

|                                   |                                    |
|-----------------------------------|------------------------------------|
| <b>Popular Downloads</b>          |                                    |
| Data Sheet, Technical Information | 1SEC312012D0201                    |
| Instructions and Manuals          | No Instructions and Manuals needed |

|                            |         |
|----------------------------|---------|
| <b>Dimensions</b>          |         |
| Product Net Width          | 140 mm  |
| Product Net Height         | 117 mm  |
| Product Net Depth / Length | 269 mm  |
| Product Net Weight         | 1.63 kg |

|                                                      |                                  |
|------------------------------------------------------|----------------------------------|
| <b>Technical</b>                                     |                                  |
| Rated Operational Current AC-21B ( $I_e$ )           | (690 V) 200 A                    |
| Rated Operational Current AC-22B ( $I_e$ )           | (500 V) 250 A                    |
| Rated Operational Current DC-22B                     | (440 V) 250 A                    |
| Rated Impulse Withstand Voltage ( $U_{imp}$ )        | Main Circuit 8 kV                |
| Rated Operational Voltage                            | 440 V DC<br>500 V AC<br>690 V AC |
| Rated Frequency (f)                                  | Main Circuit 50/60 Hz            |
| Rated Conditional Short-Circuit Current ( $I_{nc}$ ) | (690 V) 50 kiloampere rms        |
| Power Loss                                           | at Rated Load 7.5 W              |
| Handle Type                                          | Front cover 2P                   |
| Fuse Size                                            | NH1                              |
| Fuse System                                          | DIN                              |
| Standards                                            | IEC60947-3<br>GB/T14048.3        |
| Special Functions                                    | Not Included                     |
| Mounting Type                                        | Baseplate                        |
| Number of Poles                                      | 2                                |
| Degree of Protection                                 | IP30                             |
| Terminal Type                                        | Lug terminals                    |
| Device Type Manager (DTM)                            | Fuseswitchdisconnector           |
| Rated Current ( $I_n$ )                              | 250 A                            |
| Rated Voltage ( $U_r$ )                              | 440 V DC<br>500 V AC<br>690 V AC |
| Electronic Fuse Monitoring                           | No                               |

|                      |                                                                        |
|----------------------|------------------------------------------------------------------------|
| <b>Environmental</b> |                                                                        |
| RoHS Status          | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |

|                                      |                 |
|--------------------------------------|-----------------|
| <b>Certificates and Declarations</b> |                 |
| Declaration of Conformity - CE       | 1SEP500050P0001 |

REACH Declaration

1SCC011021D0201

Container Information

|                                |                     |
|--------------------------------|---------------------|
| Package Level 1 Units          | shrink-wrap 1 piece |
| Package Level 1 Width          | 140 mm              |
| Package Level 1 Depth / Length | 269 mm              |
| Package Level 1 Height         | 117 mm              |
| Package Level 1 Gross Weight   | 1.63 kg             |
| Package Level 1 EAN            | 7025840086604       |
| Package Level 2 EAN            | 7025840086604       |

Classifications

|                            |                                                            |
|----------------------------|------------------------------------------------------------|
| Object Classification Code | S                                                          |
| ETIM 7                     | EC001040 - Fuse switch disconnecter                        |
| ETIM 8                     | EC001040 - Fuse switch disconnecter                        |
| ETIM 9                     | EC001040 - Fuse switch disconnecter                        |
| eClass                     | V11.1 : 27371401                                           |
| WEEE Category              | 5. Small Equipment (No External Dimension More Than 50 cm) |

Categories

Low Voltage Products and Systems → Fusegear → Fuse Switch Disconnectors → EasyLine

