



PRODUCT-DETAILS

XLP3-2P

XLP3-2P Fuse Switch Disconnecter



General Information	
Extended Product Type	XLP3-2P
Product ID	1SEP600127R0001
EAN	7025840086741
Catalog Description	XLP3-2P Fuse Switch Disconnecter
Long Description	XLP3,2-pole,630A, without clamps or bolts

Circular Value	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	1SCC011021D0201
RoHS Information	1SCC011020D0201

Ordering	
Minimum Order Quantity	1 piece
Customs Tariff Number	85389099

Country of Origin	China (CN)
-------------------	------------

Popular Downloads	
Data Sheet, Technical Information	1SEC312012D0201
Instructions and Manuals	No Instructions and Manuals needed

Dimensions	
Product Net Width	179 mm
Product Net Height	142 mm
Product Net Depth / Length	330 mm
Product Net Weight	3.95 kg

Technical	
Rated Operational Current AC-21B (I _e)	(690 V) 500 A
Rated Operational Current AC-22B (I _e)	(500 V) 630 A
Rated Operational Current DC-22B	(440 V) 630 A
Rated Impulse Withstand Voltage (U _{imp})	Main Circuit 8 kV
Rated Operational Voltage	440 V DC 500 V AC 690 V AC
Rated Frequency (f)	Main Circuit 50/60 Hz
Rated Conditional Short-Circuit Current (I _{nc})	(690 V) 50 kiloampere rms
Power Loss	at Rated Load 24 W
Handle Type	Front cover 2P
Fuse Size	NH3
Fuse System	DIN
Standards	IEC60947-3 GB/T14048.3
Special Functions	Not Included
Mounting Type	Baseplate
Number of Poles	2
Degree of Protection	IP30
Terminal Type	Lug terminals
Device Type Manager (DTM)	Fuseswitchdisconnector
Rated Current (I _n)	630 A
Rated Voltage (U _r)	440 V DC 500 V AC 690 V AC
Electronic Fuse Monitoring	No

Environmental	
---------------	--

