



PRODUCT-DETAILS

CP-S.1 24/3.0

CP-S.1 24/3.0 Power supply In:100-240VAC/100-250VDC Out:DC 24V/3A



General Information

Extended Product Type	CP-S.1 24/3.0
Product ID	1SVR320361R1000
EAN	4013614561092
Catalog Description	CP-S.1 24/3.0 Power supply In:100-240VAC/100-250VDC Out:DC 24V/3A

Long Description

The CP-S.1 24/3.0 is a power supply from the new generation CP-S.1 range. The primary switch mode power supply offers a wide range input of 85-264 V AC and 90-277 V DC, rated input voltage is 100-240 V AC, respectively 100-250 V DC. The rated output power is 72 W, rated output current is 3 A at an output voltage of 24 V DC. The output voltage is adjustable within a range of 24 to 28 V DC. The power supply provides a U/I output characteristic with a power reserve of up to 150 % for 5 s and allows parallel operation to increase capacity and to enable redundancy. Redundancy unit and buffer modules are available as accessories.

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85044095

Popular Downloads

Data Sheet, Technical	1SAC200137H0001
-----------------------	-----------------

Information	
Instructions and Manuals	1SVC320360M0000
Wiring Diagram	9AKK107992A8774

Dimensions

Product Net Width	30.5 mm
Product Net Height	129.4 mm
Product Net Depth / Length	127 mm
Product Net Weight	0.55 kg

Container Information

Package Level 1 Width	64 mm
Package Level 1 Depth / Length	155 mm
Package Level 1 Height	169 mm
Package Level 1 Gross Weight	0.67 kg
Package Level 1 EAN	4013614561092
Package Level 1 Units	box 1 piece
Package Level 2 Width	393 mm
Package Level 2 Depth / Length	600 mm
Package Level 2 Height	190 mm
Package Level 2 Gross Weight	15 kg
Package Level 2 Units	carton 21 piece

Technical

Function	Switch mode power supply
Number of Phases	1
Rated Input Voltage (U_{IN})	100 ... 240 V AC 100 ... 250 V DC
Input Voltage (U_{in})	85 ... 264 V AC 90 ... 277 V DC
Typical Input Current	(115 V AC) 1.38 A (230 V AC) 0.95 A
Hold-up Time	(230 V AC) min. 20 ms
Rated Frequency (f)	50 / 60 Hz DC
Rated Frequency Limits	45 ... 65 Hz
Characteristic of Output	U/I characteristic curve with power reserve
Rated Output Power	72 W
Output Power	72 W
Rated Output Voltage	24 V DC
Output Voltage (U_{out})	24 V DC
Output Current	3 A
Output Current Maximum (I_{out})	4.5 A
Rated Impulse Withstand Voltage (U_{imp})	Input Circuit / Output Circuit 4 kV Input Circuit / PE 4 kV Input Circuit / Relay Contact 4 kV Output Circuit / PE 0.8 kV Output Circuit 0.8 kV
Rated Insulation Voltage (U_i)	Input Circuit / Output Circuit 300 V Input Circuit / PE 300 V Input Circuit / Relay Contact 300 V Output Circuit / PE 50 V

Degree of Protection	Housing IP20 Terminals IP20
Pollution Degree	2
Connecting Capacity Input Circuit	Flexible with Ferrule 0.5 ... 2.5 mm² Flexible 0.5 ... 2.5 mm² Rigid 0.5 ... 2.5 mm²
Connecting Capacity Output Circuit	Flexible with Ferrule 0.5 ... 2.5 mm² Flexible 0.5 ... 2.5 mm² Rigid 0.5 ... 2.5 mm²
Tightening Torque	Input Circuit 0.5 N·m Output Circuit 0.5 N·m
Wire Stripping Length	Auxiliary Circuit 7 mm Input Circuit 9 mm Output Circuit 9 mm
Minimum Mounting Distance	Other Device Same Type, Horizontal 30 mm Other Device Same Type, Vertical 50 mm
Mounting Position	1
Mounting on DIN Rail	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715

Technical UL/CSA

Connecting Capacity Input Circuit UL/CSA	Flexible with Ferrule 20-14 AWG Flexible 20-14 AWG Rigid 20-14 AWG
Connecting Capacity Output Circuit UL/CSA	Flexible with Ferrule 20-14 AWG Flexible 20-14 AWG Rigid 20-14 AWG
Tightening Torque UL/CSA	Input Circuit 4.4 in·lb Output Circuit 4.4 in·lb

Electromagnetic Compatibility

Electrostatic Discharge (ESD Immunity) acc. to IEC 61000-4-2	Level 4 Air Discharge 15 kV Level 4 Contact Discharge 8 kV
Radiated Electromagnetic Field Immunity acc. to IEC 61000-4-3	Level 3 10 V/m
Surge Immunity acc. to IEC 61000-4-5	Level 4 Line-to-Ground 4 kV Level 4 Line-to-Line 2 kV
Electromagnetic Compatibility (EMC)	Immunity - Class B Emission - Class B

Environmental

Ambient Air Temperature	Operation -25 ... +70 °C Storage -40 ... +85 °C
Maximum Operating Altitude Permissible	5000 m
Resistance to Damp Heat acc. to IEC 60068-2-30	Test Db: 55°C, 2 cycles
Resistance to Shock acc. to IEC 60068-2-27	30g 3 shocks 6 ms
Resistance to Vibrations	±0.15 mm 10 ... 58 Hz 10 Sweep Cycles Each Axis: 2g 58 ... 150 Hz

Material Compliance

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	1SVD982001-4501

WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Certificates and Declarations

CB Certificate	CB_DE_2-029400
Declaration of Conformity - CE	1SVD982043-00
Declaration of Conformity - UKCA	1SVD982043-10
DNV Certificate	DNV_TAA0000300
EAC Certificate	EAC_RU_C-DE.MO05.B.01461

Classifications

Object Classification Code	T
ETIM 5	EC002540 - DC-power supply
ETIM 6	EC002540 - DC-power supply
ETIM 7	EC002540 - DC-power supply
ETIM 8	EC002540 - DC-power supply
eClass	V11.0 : 27040701
UNSPSC	39121004
E-Number (Finland)	2712886
E-Number (Sweden)	5213654

Categories

Low Voltage Products and Systems → Control Products → Power Supplies → CP-S.1

