




PRODUCT-DETAILS

CP-S.1 24/20.0

CP-S.1 24/20.0 Power supply In:100-240VAC/100-250VDC Out:DC 24V/20A



General Information	
Extended Product Type	CP-S.1 24/20.0
Product ID	1SVR320761R1000
EAN	4013614561122
Catalog Description	CP-S.1 24/20.0 Power supply In:100-240VAC/100-250VDC Out:DC 24V/20A
Long Description	The CP-S.1 24/20.0 is a power supply from the new generation CP-S.1 range. The primary switch mode power supply offers a wide range input of 85-264 V AC and 90-277 V DC, rated input voltage is 100-240 V AC, respectively 100-250 V DC. The rated output power is 480 W, rated output current is 20 A at an output voltage of 24 V DC. The output voltage is adjustable within a range of 24 to 28 V DC. The power supply provides a U/I output characteristic with a power reserve of up to 150 % for 5 s and allows parallel operation to increase capacity and to enable redundancy. Further features are: power factor correction acc. to EN 61000-3-2. Redundancy unit and buffer modules are available as accessories.

Ordering	
Minimum Order Quantity	1 piece
Customs Tariff Number	85044095

Popular Downloads

Data Sheet, Technical Information	1SAC200140H0001
Instructions and Manuals	1SVC320360M0000
Wiring Diagram	9AKK107992A8774

Dimensions

Product Net Width	68 mm
Product Net Height	129.4 mm
Product Net Depth / Length	127 mm
Product Net Weight	1.355 kg

Container Information

Package Level 1 Width	119 mm
Package Level 1 Depth / Length	158 mm
Package Level 1 Height	188 mm
Package Level 1 Gross Weight	1.6 kg
Package Level 1 EAN	4013614561122
Package Level 1 Units	box 1 piece
Package Level 2 Width	375 mm
Package Level 2 Depth / Length	495 mm
Package Level 2 Height	210 mm
Package Level 2 Gross Weight	15.7 kg
Package Level 2 Units	carton 9 piece

Technical

Function	Switch mode power supply
Number of Phases	1
Rated Input Voltage (U_{IN})	100 ... 240 V AC 100 ... 250 V DC
Input Voltage (U_{in})	85 ... 264 V AC 90 ... 277 V DC
Typical Input Current	(115 V AC) 4.85 A (230 V AC) 2.55 A
Hold-up Time	(230 V AC) min. 20 ms
Rated Frequency (f)	50 / 60 Hz DC
Rated Frequency Limits	45 ... 65 Hz
Characteristic of Output	U/I characteristic curve with power reserve
Rated Output Power	480 W
Output Power	480 W
Rated Output Voltage	24 V DC
Output Voltage (U_{out})	24 V DC
Output Current	20 A
Output Current Maximum (I_{out})	30 A

Rated Impulse Withstand Voltage (U _{imp})	Input Circuit / Output Circuit 4 kV Input Circuit / PE 4 kV Input Circuit / Relay Contact 4 kV Output Circuit / PE 0.8 kV Output Circuit 0.8 kV
Rated Insulation Voltage (U _i)	Input Circuit / Output Circuit 300 V Input Circuit / PE 300 V Input Circuit / Relay Contact 300 V Output Circuit / PE 50 V
Degree of Protection	Housing IP20 Terminals IP20
Pollution Degree	2
Connecting Capacity Input Circuit	Flexible with Ferrule 0.5 ... 4.0 mm ² Flexible 0.5 ... 4.0 mm ² Rigid 0.5 ... 4 mm ²
Connecting Capacity Output Circuit	Flexible with Ferrule 0.5 ... 4.0 mm ² Flexible 0.5 ... 4.0 mm ² Rigid 0.5 ... 4 mm ²
Tightening Torque	Input Circuit 0.5 N·m Output Circuit 1.13 N·m
Wire Stripping Length	Auxiliary Circuit 7 mm Input Circuit 9 mm Output Circuit 9 mm
Minimum Mounting Distance	Other Device Same Type, Horizontal 30 mm Other Device Same Type, Vertical 50 mm
Mounting Position	1
Mounting on DIN Rail	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715

Technical UL/CSA

Connecting Capacity Input Circuit UL/CSA	Flexible with Ferrule 20-12 AWG Flexible 20-12 AWG Rigid 20-12 AWG
Connecting Capacity Output Circuit UL/CSA	Flexible with Ferrule 20-12 AWG Flexible 20-12 AWG Rigid 20-12 AWG
Tightening Torque UL/CSA	Input Circuit 4.4 in·lb Output Circuit 4.4 in·lb

Electromagnetic Compatibility

Electrostatic Discharge (ESD Immunity) acc. to IEC 61000-4-2	Level 4 Air Discharge 15 kV Level 4 Contact Discharge 8 kV
Radiated Electromagnetic Field Immunity acc. to IEC 61000-4-3	Level 3 10 V/m
Surge Immunity acc. to IEC 61000-4-5	Level 4 Line-to-Ground 4 kV Level 4 Line-to-Line 2 kV
Electromagnetic Compatibility (EMC)	Immunity - Class B Emission - Class B

Environmental

Ambient Air Temperature	Operation -25 ... +70 °C Storage -40 ... +85 °C
Maximum Operating Altitude Permissible	5000 m

Resistance to Damp	Test Db: 55°C, 2 cycles
Heat acc. to IEC 60068-2-30	
Resistance to Shock acc. to IEC 60068-2-27	30g 3 shocks 6 ms
Resistance to Vibrations	±0.15 mm 10 ... 58 Hz 10 Sweep Cycles Each Axis: 2g 58 ... 150 Hz

Material Compliance

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	1SVD982001-4501
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Certificates and Declarations

CB Certificate	CB_DE_2-029956
Declaration of Conformity - CE	1SVD982043-00
Declaration of Conformity - UKCA	1SVD982043-10
DNV Certificate	DNV_TAA0000300
EAC Certificate	EAC_RU_C-DE.MO05.B.01455

Classifications

Object Classification Code	T
ETIM 5	EC002540 - DC-power supply
ETIM 6	EC002540 - DC-power supply
ETIM 7	EC002540 - DC-power supply
ETIM 8	EC002540 - DC-power supply
eClass	V11.0 : 27040701
UNSPSC	39121004
E-Number (Finland)	2712889
E-Number (Sweden)	5213657

Categories

Low Voltage Products and Systems → Control Products → Power Supplies → CP-S.1

Medium Voltage Products and Systems → Service → Spares and Consumables → Parts → All Spare Parts (Relays-SWG-CB)

